



Coudes à 45°, PE100 S5/SDR11

Exécution:

- Soudage conventionnel bout à bout selon DVS 2207
- IR = (IR Plus®) compatible. A souder avec les paramètres: PE 100

d	DN	PN	MDS	Code	poids	Lmax	Q1	s1	z
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
20	15	16	IR	753 158 606	0,007	61,70	24	1,9	8
25	20	16	IR	753 158 607	0,013	66,88	25	2,3	9
32	25	16	IR	753 158 608	0,019	72,77	25	2,9	11
40	32	16	IR	753 158 609	0,036	80,72	25	3,7	14
50	40	16	IR	753 158 610	0,059	89,38	26	4,6	16
63	50	16	IR	753 158 611	0,103	102,51	29	5,8	18
75	65	16	IR	753 158 612	0,146	110,16	29	6,8	20
90	80	16	IR	753 158 613	0,241	127,42	34	8,2	23
110	100	16	IR	753 158 614	0,442	158,39	43	10,0	27
125	100	16	IR	753 158 615	0,638	179,06	48	11,4	31
140	125	16	IR	753 158 616	0,902	199,72	55	12,7	33
160	150	16	IR	753 158 617	1,340	227,28	60	14,6	40
200	200	16	IR	753 158 619	2,612	282,39	75	18,2	49
225	200	16	IR	753 158 620	3,638	318,54	85	20,5	55

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>