




## COOL-FIT 2.0 T90° égal

### Exécution:

- PE100 SDR11 pré-isolé, métrique
- Isolation en mousse GF HE
- Impact résistant. Couleur: noir
- A: Raccord électrosoudable avec lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur



A

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	Code	poids (kg)	L (mm)	L1 (mm)	Type	z (mm)	z1 (mm)
32	75	25	11	16	<b>738 204 108</b>	0,154	73	36	A	18	98,0
40	90	32	11	16	<b>738 204 109</b>	0,230	81	40	A	22	112,0
50	90	40	11	16	<b>738 204 110</b>	0,306	88	44	A	25	125,0
63	110	50	11	16	<b>738 204 111</b>	0,492	97	48	A	30	147,0
75	125	65	11	16	<b>738 204 112</b>	0,673	110	55	A	36	140,0
90	140	80	11	16	<b>738 204 113</b>	1,022	124	62	A	43	161,0
110	160	100	11	16	<b>738 204 114</b>	1,751	148	72	A	57	184,0
140	200	125	11	16	<b>738 204 166</b>	4,390	169	84	A	66	257,3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>