





Raccord d'adaptation PE/acier inoxydable avec écrou libre G COOL-FIT 2.0

Exécution:

- Raccord avec bout lisse PE100 SDR11 métrique
- Filetage femelle G acier inoxydable 1.4404 / 316L
- Inclus joint plat EPDM
- Y compris isolation en mousse de NBR



d (mm)	D (mm)	Thread (inch)	Pouces (inch)	DN (mm)	SDR	PN (bar)	Code	poids (kg)	L (mm)	L1 (mm)	z (mm)
32	70	G	½	25	11	16	738 944 308	0,204	135	36	126
32	70	G	¾	25	11	16	738 944 318	0,219	135	36	129
32	70	G	1	25	11	16	738 944 328	0,317	135	36	129
40	78	G	1 ¼	32	11	16	738 944 309	0,538	155	40	148
40	116	G	1 ½	32	11	16	738 944 319	0,615	157	40	148
50	88	G	1 ½	40	11	16	738 944 310	0,758	164	44	154
63	101	G	2	50	11	16	738 944 311	1,237	186	48	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>