



Mamelon d'adaptation PE/acier inoxydable avec filetage mâle R COOL-FIT 2.0

Exécution:

- Raccord avec bout lisse PE100 SDR11 métrique
- Filetage mâle R acier inoxydable 1.4405 / 316L
- Joint: joint torique EPDM
- Y compris isolation en mousse de NBR

| d (mm) | D (mm) | Thread (inch) | Pouces (inch) | DN (mm) | SDR | PN (bar) | Code | poids (kg) | L1 (mm) | z (mm) |
|-----------|-----------|------------------|------------------|------------|-----|-------------|--------------------|---------------|------------|-----------|
| 32 | 70 | R | ½ | 25 | 11 | 16 | 738 944 508 | 0,194 | 36 | 130 |
| 32 | 70 | R | ¾ | 25 | 11 | 16 | 738 944 518 | 0,202 | 36 | 134 |
| 32 | 70 | R | 1 | 25 | 11 | 16 | 738 944 528 | 0,211 | 36 | 134 |
| 40 | 78 | R | 1 ¼ | 32 | 11 | 16 | 738 944 509 | 0,595 | 40 | 156 |
| 50 | 88 | R | 1 ½ | 40 | 11 | 16 | 738 944 510 | 0,954 | 44 | 168 |
| 63 | 101 | R | 2 | 50 | 11 | 16 | 738 944 511 | 1,381 | 48 | 179 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>