



Embouts d'adaptation filetés égaux, PVC-U métrique - R

Exécution:

- avec emboîtures pour collage métrique et filetage mâle conique R
- assurer un montage sans contraintes et éviter les grandes variations de températures et les chocs thermiques.
- ne pas utiliser de pâte à joint nuisible au PVC-U

Pouces (inch)	R (inch)	d (mm)	PN (bar)	Code	SP	poids (kg)	z (mm)	L (mm)	s (mm)
3/8	3/8	16	16	721 910 705	10	0,011	20	34	27
1/2	1/2	20	16	721 910 706	10	0,018	24	40	32
3/4	3/4	25	16	721 910 707	10	0,025	25	44	36
1	1	32	16	721 910 708	10	0,039	28	50	46
1 1/4	1 1/4	40	16	721 910 709	10	0,061	31	57	55
1 1/2	1 1/2	50	16	721 910 710	10	0,092	32	63	65
2	2	63	16	721 910 711	5	0,161	38	76	80
2 1/2	2 1/2	75	10	721 910 712	6	0,227	42	86	90
3	3	90	10	721 910 713	5	0,389	46	97	110
4	4	110	10	721 910 714	5	0,572	53	114	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>