




Raccords pour instruments type 313 COOL-FIT 2.0

Exécution:

- PE100 SDR11 pré-isolé, métrique
- Isolation en mousse GF HE
- Impact résistant. Couleur: noir
- Avec départ fileté pour senseur (p.e. température, pression)
- A: Raccord électrosoudable avec lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur



d	D	Thread	Pouces	DN	SDR	PN	Code	poids	H	L	L1	Type	z
(mm)	(mm)		(inch)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)		(mm)
32	75	Rp	½	25	11	16	738 313 408	0,138	75	73	36	A	16
40	90	Rp	½	32	11	16	738 313 409	0,216	85	81	40	A	21
40	90	Rp	¾	32	11	16	738 313 459	0,216	88	81	40	A	21
50	90	Rp	½	40	11	16	738 313 410	0,308	94	88	44	A	24
50	90	Rp	¾	40	11	16	738 313 460	0,307	97	88	44	A	24
63	110	Rp	½	50	11	16	738 313 411	0,493	113	97	48	A	29
63	110	Rp	¾	50	11	16	738 313 461	0,492	116	97	48	A	29
75	125	Rp	½	65	11	16	738 313 412	0,678	99	110	55	A	35
75	125	Rp	¾	65	11	16	738 313 462	0,677	102	110	55	A	35
90	140	Rp	½	80	11	16	738 313 413	1,025	113	123	62	A	42
90	140	Rp	¾	80	11	16	738 313 463	1,023	116	123	62	A	42
110	160	Rp	½	100	11	16	738 313 414	1,765	128	148	72	A	56
110	160	Rp	¾	100	11	16	738 313 464	1,763	131	148	72	A	56
140	200	Rp	½	125	11	16	738 313 436	3,747	190	169	84	A	66
140	200	Rp	¾	125	11	16	738 313 486	3,747	190	169	84	A	66

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>