




Tube COOL-FIT 2.0

Exécution:

- PE100 SDR11 pré-isolé, métrique
- Isolation en mousse GF HE
- Impact résistant. Couleur: noir
- A bout lisse pour l'électrosoudage

Remarque:

bigger dimensions available via COOL-FIT 4.0 product range



d	D	DN	SDR	PN	Code	poids	di	L	L1	pouce
(mm)	(mm)	(mm)		(bar)		(kg/m)	(mm)	(mm)	(mm)	(inch)
32	75	25	11	16	738 174 108	1,140	26,2	5000	36	1
40	90	32	11	16	738 174 109	1,534	32,6	5000	40	1 ½
50	90	40	11	16	738 174 110	1,722	40,8	5000	44	1 ½
63	110	50	11	16	738 174 111	2,711	51,4	5000	48	2
75	125	65	11	16	738 174 112	3,405	61,4	5000	55	2 ½
90	140	80	11	16	738 174 113	4,320	73,5	5000	62	3
110	160	100	11	16	738 174 114	5,692	90,0	5000	72	4
140	200	125	11	16	738 174 116	9,021	114,6	5000	84	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>