




A



A

COOL-FIT 2.0 coude 45°

Exécution:

- PE100 SDR11 pré-isolé, métrique
- Isolation en mousse GF HE
- Impact résistant. Couleur: noir
- A: Raccord électrosoudable avec lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur

d	D	DN	SDR	PN	Code	poids	L	L1	Type	z
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)		(mm)
32	75	25	11	16	738 154 108	0,101	66	36	A	11
40	90	32	11	16	738 154 109	0,143	70	40	A	11
50	90	40	11	16	738 154 110	0,206	76	44	A	13
63	110	50	11	16	738 154 111	0,307	83	48	A	16
75	125	65	11	16	738 154 112	0,407	92	55	A	18
90	140	80	11	16	738 154 113	0,686	111	62	A	30
110	160	100	11	16	738 154 114	1,123	132	72	A	41
140	200	125	11	16	738 154 166	2,775	151	84	A	48

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>