

Coudes 45° avec fixation du tube intégrée

- PE 100 SDR 11 (ISO S5)
- 10 bar gaz / 16 bar eau
- connecteurs 4 mm
- indicateur de soudage


d (mm)	Code	EUR	SP	poids (kg)	d1 (mm)	L (mm)	L1 (mm)	z (mm)	Tube SDR
32	753 151 608	25,61	1	0,075	44	44	36	8	9-11
40	753 151 609	31,05	1	0,106	54	50	39	11	9-11
50	753 151 610	38,87	1	0,171	66	56	43	13	9-11
63	753 151 611	44,33	1	0,252	81	63	48	15	9-17.6



Coudes 45°

- PE 100 SDR 11 (ISO S5)
- 10 bar gaz / 16 bar eau
- connecteurs 4 mm
- indicateur de soudage

d (mm)	Code	EUR	SP	poids (kg)	d1 (mm)	L (mm)	L1 (mm)	z (mm)	Tube SDR
75	753 151 612	63,30	1	0,332	97	71	54	17	9-11
90	753 151 813	78,53	1	0,583	115	91	62	29	9-11
110	753 151 814	113,99	1	0,985	140	112	72	40	9-17.6
125	753 151 815	157,18	1	1,438	160	119	78	49	9-17.6
160	753 151 817	311,45	1	3,055	196	135	92	42	11-17.6
180	753 151 818	392,69	1	4,037	217	144	95	47	11-17.6



Coudes 45°

- PE 100 SDR 11 (ISO S5)
- 10 bar gaz / 16 bar eau
- connecteurs 4 mm
- indicateur de soudage
- 2 zones de soudage séparées

d (mm)	Code	EUR	SP	poids (kg)	d1 (mm)	L (mm)	L1 (mm)	z (mm)	Tube SDR
200	753 151 819	1.238,55	1	7,566	250	232	104	128	11-26
225	753 151 820	1.527,90	1	11,300	280	247	112	135	11-26
250	753 151 821	1.985,10	1	13,500	310	275	123	152	11-26