



Rotamètre type 350 Ecrou (5)

*also for diaphragm valves type 514/DIASTAR, pressure regulating valves type 582/586 and variable area flow

**just for variable area flow meter

***for adaptor unions PVC-U / malleable iron only

d (mm)	PN (bar)	PVC-U Code	poids (kg)	Thread size	D (mm)	L (mm)
10 - 12	16	721 890 004	0,009	5/8	19	19
16	16	721 890 005	0,011	3/4	22	21
*	20	721 890 006	0,020	1	28	23
*	25	721 890 007	0,020	1 1/4	36	24
*	32	721 890 008	0,030	1 1/2	41	26
*	40	721 890 009	0,049	2	53	29
*	50	721 890 010	0,087	2 1/4	59	34
*	63	721 890 011	0,138	2 3/4	74	38
	75	721 890 012	0,256	Tr 108x5	92	40
	90	721 890 013	0,490	Tr 128x5	110	43
***	90	721 890 023	0,355	Tr 128x5	105	43
	110	721 890 014	0,574	Tr 154x6	133	48
**	75	198 806 429	0,200			

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>