




A

COOL-FIT 2.0 coude 90°

Exécution:

- PE100 SDR11 pré-isolé, métrique
- Isolation en mousse GF HE
- Impact résistant. Couleur: noir
- A: Raccord électrosoudable avec lèvre d'étanchéité intégrée pour un assemblage étanche à l'eau et à la vapeur



d	D	DN	SDR	PN	Code	poids	L	L1	Type	z
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)		(mm)
32	75	25	11	16	738 104 108	0,127	75	36	A	20
40	90	32	11	16	738 104 109	0,185	82	40	A	23
50	90	40	11	16	738 104 110	0,242	93	44	A	30
63	110	50	11	16	738 104 111	0,384	101	48	A	34
75	125	65	11	16	738 104 112	0,510	114	55	A	40
90	140	80	11	16	738 104 113	0,960	144	62	A	63
110	160	100	11	16	738 104 114	1,406	168	72	A	77
140	200	125	11	16	738 104 166	3,454	190	84	A	87

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>