



## COOL-FIT 2.0 manchon

### Exécution:

- PE100 SDR11 pré-isolé, métrique
- Isolation en mousse GF HE
- Impact résistant. Couleur: noir
- Electrofusion fitting with integrated sealing lip, for a moisture-proof and vapour tight sealing

### Remarque:

bigger dimensions available via COOL-FIT 4.0 product range

d	D	DN	SDR	PN	Code	poids	L	L1	z
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)
32	75	25	11	16	<b>738 914 108</b>	0,092	113	36	5
40	90	32	11	16	<b>738 914 109</b>	0,126	121	40	3
50	90	40	11	16	<b>738 914 110</b>	0,160	129	44	3
63	110	50	11	16	<b>738 914 111</b>	0,237	137	48	3
75	125	65	11	16	<b>738 914 112</b>	0,339	152	55	3
90	140	80	11	16	<b>738 914 113</b>	0,476	166	62	4
110	160	100	11	16	<b>738 914 114</b>	0,778	188	72	4
140	200	125	11	16	<b>738 914 116</b>	1,097	210	84	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>