

Raccords électrosoudables ELGEF Plus

Manchons



Manchons avec système de fixation intégré du tube

- PE 100 SDR 11 (ISO S5)
- 10 bar gaz / 16 bar eau
- connecteurs 4 mm
- indicateur de soudage
- butée centrale amovible


d (mm)	Code	EUR	poids (kg)	d1 (mm)	L (mm)	Tube SDR
20	753 911 606	9,08	0,053	31	70	9-11
25	753 911 607	10,30	0,050	36	70	9-11
32	753 911 608	11,10	0,071	44	72	9-11
40	753 911 609	11,67	0,095	54	80	9-11
50	753 911 610	18,00	0,131	66	88	9-11
63	753 911 611	18,97	0,160	81	96	9-17.6



Manchon électrosoudable

- PE 100 SDR 11 (ISO S5)
- 10 bar gaz / 16 bar eau
- connecteurs 4 mm
- indicateur de soudage
- butée centrale amovible jusqu'à d160

d (mm)	Code	EUR	GP	poids (kg)	d1 (mm)	L (mm)	Tube SDR
75	753 911 612	26,55	12	0,282	96	110	9-17.6
90	753 911 613	35,50	10	0,406	113	125	9-17.6
110	753 911 614	43,34	5	0,692	138	145	9-17.6
125	753 911 615	59,26	5	0,718	154	156	9-17.6
140	753 911 616	68,22	5	0,945	172	166	9-17.6
160	753 911 617	78,96	6	1,362	196	180	9-17.6
180	753 911 618	116,15	5	1,747	219	192	9-17.6
200	753 911 619	134,73	4	1,866	244	208	9-17.6
225	753 911 620	165,66	3	3,329	273	225	9-17.6
250	753 911 621	324,27	2	4,678	304	248	9-17.6
280	753 911 622	458,32	2	7,500	340	252	9-17.6
315	753 911 623	523,80	2	8,142	382	267	9-17.6



Manchon

- **PE 100 SDR 11** (ISO S5)
- 10 bar gaz / 16 bar eau
- connecteurs 4 mm
- indicateur de soudage
- Avec renforcement actif

d (mm)	Code	EUR	GP	poids (kg)	d1 (mm)	L (mm)	Tube SDR
355	753 911 704	637,28	1	13,098	438	291	9-17
400	753 911 705	767,16	1	18,320	493	295	9-17
450	753 911 706	1.388,03	1	24,700	554	327	9-17
500	753 911 707	1.717,28	1	33,700	616	358	9-17
560	753 911 708	2.816,69	1	46,200	689	396	9-17
630	753 911 709	3.686,48	1	65,300	775	440	9-17
710	753 911 710	5.019,79	1	97,400	874	463	9-17
800	753 911 711	7.190,47	1	114,500	982	484	9-17

Manchon électrosoudable



- **PE 100 SDR 11** (ISO S5)
- 16 bar eau
- Applications uniquement pour l'eau
- connecteurs 4 mm
- Avec renforcement actif

d (mm)	Code	EUR	SP	GP	poids (kg)	d1 (mm)	L (mm)	Tube SDR
900	753 911 652	18.121,03	1	1	137,930	1110	550	9-17.6



Manchon électrosoudable

- PE 100 SDR 17/17,6 (ISO S8)
- 5 bars gaz / 10 bars eau
- connecteurs 4 mm
- indicateur de soudage
- d 160 avec butée centrale amovible

d (mm)	Code	EUR	SP	poids (kg)	d1 (mm)	L (mm)	Tube SDR
160	753 911 817	66,18	1	1,017	186	180	9-26
180	753 911 818	97,46	1	1,434	213	192	9-26
200	753 911 819	113,01	1	1,726	233	206	9-26
225	753 911 820	138,97	1	2,545	261	225	9-26
250	753 911 821	270,78	1	4,616	304	248	9-26
280	753 911 822	383,50	1	5,606	340	252	9-26
315	753 911 823	438,05	1	6,100	382	267	9-26



Manchon

- PE 100 SDR 17 (ISO S8)
- 5 bar gaz / 10 bar eau
- connecteurs 4 mm
- indicateur de soudage
- Avec renforcement actif

d (mm)	Code	EUR	poids (kg)	d1 (mm)	L (mm)	Tube SDR
355	753 911 804	528,61	9,522	416	291	17-33
400	753 911 805	631,77	13,000	467	295	17-33
450	753 911 806	976,63	18,000	526	327	17-33
500	753 911 807	1.073,10	22,000	584	358	17-33
560	753 911 808	2.287,56	34,000	647	396	17-33
630	753 911 809	2.888,09	46,000	727	440	17-33
710	753 911 810	4.013,69	55,600	820	463	17-33
800	753 911 811	5.399,63	73,000	922	484	17-33



Manchon électrosoudable

- PE 100 SDR 17/17,6 (ISO S8)
- 10 bar eau
- Applications uniquement pour l'eau
- connecteurs 4 mm
- Avec renforcement actif

d (mm)	Code	EUR	SP	poids (kg)	d1 (mm)	L (mm)	Tube SDR
900	753 911 852	16.409,07	1	93,150	1030	550	9-26
1000	753 911 853	18.572,66	1	125,650	1143	600	9-26
1200	753 911 854	25.238,39	1	196,450	1370	650	9-26

Manchon électrosoudable



- **PE 100 SDR 26 (ISO S12.5)**
- 6 bar eau
- Applications uniquement pour l'eau
- connecteurs 4 mm
- Avec renforcement actif

d (mm)	Code	EUR	SP	poids (kg)	d1 (mm)	L (mm)	Tube SDR
710	753 911 950	4.571,24	1	31,920	797	360	9-26
800	753 911 951	8.581,65	1	42,800	897	380	9-26
900	753 911 952	14.871,94	1	57,580	1009	400	9-26
1000	753 911 953	16.154,12	1	79,270	1121	440	9-26
1200	753 911 954	20.401,17	1	125,700	1345	480	9-26

