

Accessoires PVC pression à emboîte
PVC fittings met steekmof voor drukbuis

BENOR

NBN T42-603

NBN EN ISO 1452

16 bar/20 bar
≤ 90 mm = 16 bar / ≥ 110 mm = 20 bar

Manchons à joints élastiques dentelés – Moffen met lipringen

Type	Ø	Code	Ø ext. / buiten Ø	Pronfondeur d'emboi- tement / instekdiepte	longueur / lengte	p-st./carton	
	RW20	63	RO3208400	84	50	162	56
		75	RO3201400	100	52	166	44
		90	RO3202400	115	54	176	30
		110	RO3203400	140	57	183	18
		160	RO3204400	200	65	219	12
		225	RO3214400	276	74	253	-

Manchons coulissants : même modèle sans butée Schuifmof : hetzelfde model zonder stootrand

Type	Ø	Code	Ø ext. / buiten Ø	Pronfondeur d'emboî- tement / instekdiepte	longueur / lengte	p-st./carton	
	RW20 A	63	RO3231401	84	50	162	56
		75	RO3232400	100	52	166	42
		90	RO3233400	115	54	176	30
		110	RO3234400	140	57	183	18
		160	RO3237400	200	65	219	46
		225	RO3240400	276	74	253	-

Joints caoutchouc à lèvres – Rubberlipring

Type	Ø	Code	p-st./carton
	RW 12 SN	63	RO2631450
		75	RO2632450
		90	RO2633450
		110	RO2634450
		160	RO2635450
		225	RO2499450