



**Pièces folles 546 PVC-U (G07)
avec emboîture taraudée, Rp renforcée**

Exécution:

- raccordement pour filetage plastique ou métallique
- anneau de renforcement inoxydable (A2)
- ne pas utiliser de pâte à joint nuisible au PVC-U

Rp (inch)	PN (bar)	Code	poids (kg)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	z (mm)
3/8	16	161 490 825	0,013	38	24	20	4	7
1/2	16	161 490 826	0,016	38	28	22	4	6
3/4	16	161 490 827	0,023	44	34	25	5	7
1	16	161 490 828	0,036	53	42	28	5	7
1 1/4	16	161 490 829	0,058	65	52	30	5	7
1 1/2	16	161 490 830	0,084	77	63	32	6	9
2	16	161 490 831	0,166	99	78	38	7	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>