

SMART Digital S

DIGITAL DOSING up to 30 l/h

DDA, DDC, DDE

Pumps and accessories




1. General data	4
Performance range	4
Features at a glance	5
2. Identification	7
Type key	7
3. Functions	9
Overview of functions	9
Functional description	10
Control cube DDA and DDC	11
Menu	13
Operation modes	14
Functions	18
Wiring diagram, DDA	26
Wiring diagram, DDC	27
Wiring diagram, DDE-PR, -P	28
4. Construction	30
DDA and DDC	30
DDE	32
5. Dimensions	34
Dimensions, SMART S DDA	34
Dimensions, SMART S DDC	35
Dimensions, SMART S DDE	36
6. Technical data	37
Technical data, SMART S DDA	37
Technical data, SMART S DDC	39
Technical data, SMART S DDE	41
Technical data for CIP (Clean-In-Place) applications	42
7. Pump selection	43
DDA, standard range	43
DDC, standard range	44
DDE, standard range	45
DDA, DDC, DDE, non-standard range	46
8. Accessories for small dosing pumps up to 60 l/h	48
Accessories overview	48
Installation kits for dosing pumps	50
Cables and plugs	52
E-box for SMART digital S DDA	53
Hoses	55
Foot valves FV	56
Rigid suction lances RSL	59
Injection units	64
Multi-function valves, pressure relief valves, pressure loading valves	68
Pump connection kits and inlay kits	72
Adapters	74
Dosing tanks	77
Water meter	87
9. Pumped liquids	88

10. Grundfos Product Center 90

1. General data

Performance range



TM041480

Performance range

Features at a glance



TM085625

DDA, DDC, DDE

Digital Dosing™

The SMART Digital S generation DDA, DDC and DDE with powerful variable-speed stepper motor brings state-of-the-art technology to perfection. Combined expert knowledge and patented solutions set future standards. Traditional technologies, such as stroke length or stroke frequency adjustment with synchronous motor or solenoid drive, become a thing of the past.

Unique flexibility with only a few variants

The included click-stop mounting plate makes the pump more flexible. Three different positions are possible without using any additional accessories, such as wall brackets. Service and pump exchange can now be done easily by clicking the pump in and out of the mounting plate.

The control cube on the DDA and DDC pump can be lifted and turned easily into three different positions: front, left or right.



TM041662


Modularity of the control cube

A turn-down ratio of up to 1:3000, a wide supply voltage range (100-240 V; 50/60 Hz), combined connection sets and other features reduce the models and variants to a minimum.

Precise and easy setting / usability and interaction

The operator can easily install the pump and set it to discharge exactly the quantity of dosing liquid required for the application. In the display, the setting of the pump is read out directly, the flow is shown in ml/h, l/h, or gph.

The click wheel (turn-and-push knob) and the graphical LC display with plain-text menu in more than 25 languages make commissioning and operation intuitive. As the LCD is backlit in different colours, the pump status can be seen from a distance (traffic-light concept).



TM041157

Display DDA, DDC

Thanks to a variety of operation modes, signal inputs and outputs, the pump can easily be integrated into every process.

Advanced process reliability

An intelligent drive and microprocessor control ensures that dosing is performed precisely and with low pulsation, even if the pump is dosing high-viscosity or degassing liquids. Malfunctions, caused by, for example, air bubbles, are detected quickly by the maintenance-free FlowControl system, and then displayed in the alarm menu.

The AutoFlowAdapt function automatically adjusts the pump according to the process conditions, such as varying backpressure. The integrated flow measurement makes additional monitoring and control equipment redundant.

Designed to save costs

In general, the investment for a dosing pump installation is low compared to its life cycle costs, including the cost of the chemicals. The following features make the SMART Digital S DDA, DDC and DDE pumps contribute to low life cycle costs:

- no underdosing or overdosing due to high dosing accuracy and FlowControl
- longer maintenance intervals due to the universal chemical resistance of the full-PTFE diaphragm
- reduced energy consumption due to the state-of-the-art drive technology.

Three application-oriented type ranges

DDA is a high-end pump range for extended flow and pressure ranges with sensor-based FlowControl and measurement functions for challenging industrial applications such as the following:

- process water
- food and beverage
- ultrafiltration and reverse osmosis
- pulp and paper
- boiler feed water
- CIP (Cleaning-In-Place).

DDC is a user-friendly pump range with standard inputs and outputs for common applications like the following:

- drinking water
- waste water
- swimming pool water
- cooling tower
- chemical industry.

DDE is a low-budget pump range with basic functions including manual operation or control via PLC for OEM applications, for example:

- car wash
- irrigation.

2. Identification

Type key

The type key is used to identify the precise pump and is not used for configuration purposes.

Type	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
DDA	
DDC	
DDE	
Nominal dosing capacity [l/h]	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
Max. pressure [bar]	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
Control variant	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
B	Basic
AR	DDA, Standard
FC	AR with FlowControl
FCM	FC with integrated flow measurement
P	B with pulse mode
PR	P with relay output
A	Standard
AR	A with alarm relay and analog input
Dosing head variant	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
PP	Polypropylene
PV	Polyvinylidene fluoride (PVDF)
SS	Stainless steel 1.4435
PVC	PVC (polyvinyl chloride, only up to 10 bar)
Gasket material	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
E	EPDM
V	FKM
T	PTFE
Valve ball material	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
SS	Stainless steel 1.4401
C	Ceramic
Control Cube	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
F	Front-mounted (change to left or right is possible)
X	No control cube
Supply voltage	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
3	1 x 100-240 V, 50/60 Hz
Valve type	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	

Valve type	
1	Standard (not spring-loaded)
2	Spring-loaded (HV version)
Connection, suction/discharge	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
U2U2	Hose, 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm
U7U7	Hose 0.17" × 1/4"; 1/4" × 3/8"; 3/8" × 1/2"
AA	Threaded Rp 1/4, female (stainless steel)
VV	Threaded 1/4 NPT, female (stainless steel)
XX	No connection
Installation set ¹⁾	
I001	Hose, 4/6 mm (up to 7.5 l/h, 13 bar)
I002	Hose, 9/12 mm (up to 60 l/h, 9 bar)
I003	Hose, 0.17" × 1/4" (up to 7.5 l/h, 13 bar)
I004	Hose, 3/8" × 1/2" (up to 60 l/h, 10 bar)
¹⁾ Including: 2 pump connections, foot valve, injection unit, 6 m PE discharge hose, 2 m PVC suction hose, 2 m PVC de-aeration hose (4/6 mm)	
Power plug	
DDA 7.5-16 AR-PP/V/C-F-31U2U2FG	
F	EU (Schuko)
B	USA, Canada
G	UK
I	Australia, New Zealand, Taiwan
E	Switzerland
J	Japan
L	Argentina
Pump design	
G	Grundfos

3. Functions

Overview of functions

Control variant:	DDA			DDC		DDE		
	FCM	FC	AR	AR	A	PR	P	B
General								
Digital Dosing: Internal stroke speed and frequency control	•	•	•	•	•	•	•	•
Mounting plate (basic/wall mounting)	•	•	•	•	•	•	•	•
Control panel, see section Control cube DDA and DDC								
Control cube mountable in three positions: front, left, right	•	•	•	•	•			
Control panel position: front-fitted						•	•	•
Transparent protective cover for control elements	•	•	•	•	•			
Capacity setting in millilitres, litres or US-gallons	•	•	•	•	•			
Graphical display with background light in four colours for status indication: white, green, yellow, red	•	•	•	•	•			
Plain-text menu in different languages	•	•	•	•	•			
Turn-and-push knob (click wheel) for easy navigation	•	•	•	•	•			
Capacity adjustment knob (0.1 - 100 %)						•	•	•
Start/Stop key	•	•	•	•	•			
100 % key (de-aeration)	•	•	•	•	•	•	•	
Operation mode switch (manual/pulse)						•	•	
Operation modes, see section on operation modes								
Manual speed control	•	•	•	•	•	•	•	•
Pulse control in ml/pulse	•	•	•	•	•			
Pulse control (1:n)						•	•	
Analog control 0/4-20 mA	•	•	•	•				
Batch control (pulse-based)	•	•	•					
Dosing timer cycle	•	•	•					
Dosing timer week	•	•	•					
Fieldbus control	•	•	•					
Functions, see section on functions								
Auto de-aeration also during pump standby	•	•	•					
FlowControl system with selective fault diagnosis	•	•						
Pressure monitoring (min/max)	•	•						
Flow measurement	•							
AutoFlowAdapt	•							
SlowMode (anti-cavitation)	•	•	•	•	•			
Calibration mode	•	•	•	•	•			
Scaling of analog input	•	•	•					
Service information display	•	•	•	•	•			
Relay setting: alarm, warning, stroke signal, pump dosing, pulse input ²⁾	•	•	•	•		•		
Relay setting (additionally): timer cycle, timer week	•	•	•					
Inputs/outputs, see section Level control								
Input for external stop	•	•	•	•	•	•	•	
Input for pulse control	•	•	•	•	•	•	•	
Input for analog 0/4-20 mA control	•	•	•	•				
Input for low-level signal	•	•	•	•	•	•	•	
Input for empty tank signal	•	•	•	•	•	•	•	
Output relay (2 relays)	•	•	•	•		•		

Output analog 0/4-20 mA	•	•	•		
Input/Output for GENIbus	•	•	•		
Input/Output for E-box (for example, E-box 150 with Profibus DP)	•	•	•		

2) DDE-PR: relay 1: alarm; relay 2: low-level signal, stroke signal, pulse input

Related information

[Control cube DDA and DDC](#)

[Manual control](#)

[SlowMode](#)

[Level control](#)

Functional description


The electronically controlled variable-speed motor (stepper motor) of the DDA, DDC and DDE pumps provides optimum control of the stroke speed. The duration of each discharge stroke varies according to the capacity set, resulting in optimum discharge flow in any operating situation, while the duration of each suction stroke is constant. See the figure below.

The advantages are as follows:

- The pump always operates at full stroke length, irrespective of the capacity set, which ensures optimum accuracy, priming and suction.
- A capacity range of up to 1:3000 (turn-down ratio) results in less variants and spare parts
- Smooth and continuous dosing ensures an optimum mixing ratio at the injection point without static mixers.
- There is a significant reduction of pressure peaks, preventing mechanical stress on wearing parts such as diaphragm, tubes, connections, resulting in extended maintenance intervals.
- The installation is less affected by long suction and discharge lines.
- Dosing of high-viscosity and degassing liquids (SlowMode) is easier.


The optimum dosing control shown below applies to any operation mode.

Relation between stroke-frequency adjustment and capacity



Control cube DDA and DDC

DDA and DDC pumps are supplied with front-mounted control cube. The position of the control cube can easily be changed by unfastening 2 screws, lifting the cube, turning it to the left or to the right, and fastening both screws again.




TM069584

Two of three possible control cube positions

Operating elements, DDA and DDC

The pump operating panel includes a display and operating elements.



TM041188

Pos.	Description
1	Graphical LC display
2	Click wheel
3	Start/Stop key
4	100% key

Click wheel

The click wheel is used for navigating through the menus, selecting settings and confirming them.

Turning the click wheel clockwise moves the cursor clockwise in increments on the display. Turning the click wheel counterclockwise moves the cursor counterclockwise.


Start/Stop key

The Start/Stop key is used for starting and stopping the pump.

100% key

The pump doses at maximum flow regardless of the operation mode.

Operating elements, DDE




TM041150

Pos.	Description
1	Logarithmic scale
2	Capacity adjusting knob
3	Status LED "Pulse" (only DDE-PR/P control variant)
4	Operation mode key (only DDE-PR/P control variant)
5	Status LED "Manual"
6	100% key (only DDE-PR/P control variant)
7	Mechanical lock

Menu

The DDA and DDC dosing pumps feature a user-friendly plain-text menu. The menu consists of 4 tabs: Operation; Info; Alarm; Setup. During initial start-up, all menu texts appear in English. The menu can be set to display other languages.

The following example applies to DDA pumps:



TM041553

Menu overview (example of main menus)

The menu text appears in more than 25 languages on a big graphical display, backlit in four different colours according to the traffic light concept.

Display	Fault	Pump status
White	-	Stop Standby
Green	-	Running
Yellow	Warning	Stop Standby Running
Red	Alarm	Stop Standby

Operation modes

Manual control

The pump ensures constant dosing according to the quantity set in l/h or ml/h or gph by the click wheel. The pump automatically changes between the measuring units.

Setting range

Pump type	Setting range ³⁾	
	From [l/h]	To [l/h]
DDA 7.5-16	0.0025	7.5
DDA 12-10	0.0120	12.0
DDA 17-7	0.0170	17.0
DDA 30-4	0.0300	30.0
DDC 6-10	0.0060	6.0
DDC 9-7	0.0090	9.0
DDC 15-4	0.0150	15.0
DDE 6-10	0.0060	6.0
DDE 15-4	0.0150	15.0

³⁾ When the SlowMode function is enabled, the maximum flow is reduced, see section SlowMode.

Related information

[SlowMode](#)

Pulse control

The pump doses in proportion to an external potential-free pulse signal, for example, from a water meter. There is no direct relation between pulses and dosing strokes. The pump automatically calculates its optimal speed to ensure that the required quantity is dosed for each incoming pulse.

For DDA and DDC:

The quantity to be dosed is set in ml/pulse. The pump adjusts its speed according to two factors:

- the frequency of external pulses
- the set quantity per pulse.

Setting range

Pump type	Setting range [ml/pulse]
DDA 7.5-16	0.0015 - 14.9
DDA 12-10	0.0029 - 29.0
DDA 17-7	0.0031 - 31.0
DDA 30-4	0.0062 - 62.0
DDC 6-10	0.0016 - 16.2
DDC 9-7	0.0017 - 16.8
DDC 15-4	0.0032 - 31.6

The frequency of external pulses is multiplied by the set quantity. If the product exceeds the maximum flow of the pump, a maximum of 65,000 pulses can be stored for later processing with the Memory pulse function, when activated.

For DDE-PR, DDE-P control variant:

The dosing quantity per pulse is adjusted with the adjustment knob according to a scale from 0.1 to 100 % of the stroke volume. The pump adjusts its speed according to two factors:

- the frequency of external pulses
- the set percentage of stroke volume.

Setting range, DDE-PR, DDE-P


Pump type	Setting range [ml/pulse]
DDE 6-10	0.0008 - 0.81
DDE 15-4	0.0016 - 1.58

Analog 0/4-20 mA control

This section applies to the DDA and DDC-AR control variant.

The pump ensures dosing according to an external analog signal. The dosed capacity is proportional to the input value in mA.

Operation mode	Input signal	Dosing capacity
4-20	$\leq 4.1 \text{ mA}$	0 %
	$\geq 19.8 \text{ mA}$	100 %
0-20	$\leq 0.1 \text{ mA}$	0 %
	$\geq 19.8 \text{ mA}$	100 %




TM041120

0/4-20 mA control

This section applies to the DDA.

With the analog scaling function, the curve can be individually drawn between two arbitrary points: I_1/Q_1 and I_2/Q_2 .



TM041575


Analog scaling

Pos.	Description
Q [%]	Dosing capacity
[mA]	Input signal

Pulse-based batch control

This section applies to the DDA.

The set quantity is dosed in batches within the set dosing time (t_1). A batch is dosed every time the pump receives an external pulse. If the pump receives new pulses before a batch is completed, these pulses are ignored. In the event of an interrupt, such as external stop or alarm, incoming pulses are ignored. After the interrupt ends, a new batch is dosed with the next incoming pulse.



TM041105

Pulse-based batch control

Pos.	Description
V	Batch volume
I	Pulse
t	Time

Setting range


Pump type	Setting range		
	From [ml/batch]	To [l/batch]	Resolution [ml] ⁴⁾
DDA 7.5-16	0.74	999	0.09
DDA 12-10	1.45	999	0.18
DDA 17-7	1.55	999	0.19
DDA 30-4	3.10	999	0.39

⁴⁾ Due to the digital motor control, down to 1/8 of the dosing volume can be dosed.

Dosing timer cycle

This section applies to the DDA.

After a start delay (t_2), the set batch volume is repeatedly dosed in the set cycle time (t_3). The dosing time (t_1) can be adjusted. Batch dosing is stopped during any interrupt, for example, power supply failure or external stop, while the time continues running in the background (real-time clock). After the interrupt ends, batch dosing proceeds according to the current status in the timeline.



TM041107

Dosing timer cycle

Pos.	Description
V	Batch volume
t1	Dosing time
t2	Start delay
t3	Cycle time

Setting range

The batch volume setting range corresponds to the pulse-based batch control setting range.

Dosing timer week

This section applies to the DDA.

The integrated real-time clock also features batch dosing based on a weekly period. There is a maximum of 16 procedures per week. Each dosing procedure consists of the following:

- batch volume
- dosing time
- start time
- 1 to 7 weekdays (Monday to Sunday).

In case several procedures overlap, the procedure with the highest flow rate has the highest priority. Batch dosing stops during any interrupt, for example, power supply failure or external stop, while the time continues running in the background (real-time clock). After the interrupt ends, batch dosing proceeds according to the current status in the timeline.

0:00							
6:00	1		1		1		1
12:00						4	4
18:00		2		2			
0:00	3	3	3	3	3	3	3

TM041576

Dosing timer week (example with 4 procedures)

Pos.	Description
1	Mo
2	Tu
3	We
4	Th
5	Fr
6	Sa
7	Su

Setting range

The batch volume setting range corresponds to the pulse-based batch control setting range.

Functions

SlowMode

This section applies to the DDA, DDC.

When the SlowMode function (anti-cavitation) is selected, the pump extends and smooths its suction stroke. This results in a softer suction stroke.

The SlowMode function is used in the following situations:

- when pumping high-viscosity liquids
- when pumping degassing liquids
- when the suction line is long
- when the suction lift is high.

Depending on the application, the motor speed during the suction stroke can be reduced individually to approximately 50 % or 25 % of the normal motor speed.

The maximum pump capacity is reduced accordingly. See sections DDA and DDC for further details.

Related information

[DDA and DDC](#)

Auto de-aeration

This section applies to the DDA.

The auto de-aeration function avoids breakdown of the dosing process due to air-locking when dosing degassing liquids, such as sodium hypochlorite. During long dosing breaks, for example at the weekend or overnight, air-bubbles can form in the suction line and get into the dosing head. If there is too much air in the dosing head and the dosing process starts again, no liquid is dosed (air-lock). Software-controlled diaphragm movements at regular intervals encourage the air bubbles to rise and get out of the dosing head.

These movements are executed in the following conditions:

- when the pump is not stopped
- during dosing breaks (for example, external stop or no incoming pulse).

Calibration

This section applies to the DDA, DDC.

The pump is calibrated in the factory at the nominal pressure of the respective pump type (see Technical data section for DDA and DDC for the maximum pressure). After start-up, the dosing pump can be calibrated for the actual installation to ensure that the displayed value (ml, l or gph) is correct. A calibration program in the setup menu facilitates this process. The AutoFlowAdapt function keeps the dosing precision (DDA-FCM control variant), even if the backpressure changes. For the description of the AutoFlowAdapt function, see section AutoFlowAdapt.

Related information

[AutoFlowAdapt](#)

External stop

This section applies to the DDA, DDC, DDE-PR and DDE-P.

With the external stop function, the pump can be stopped from a remote place via an external contact. It is not recommended to switch on and off the power supply as it was usual when working with a conventional dosing pump. When working with microprocessor-controlled digital dosing pumps, the external stop signal has to be used to keep the optimal dosing precision and prevent damages to the electronics.

When activating the external stop signal, the pump changes from running to standby. The operation display shows an activated external stop. The signal input can be set to normally open (default) or normally closed contact.

Counters

This section applies to the DDA, DDC.

The pump displays resettable and non-resettable counters in the info menu tab.

Counter	Description	Resettable
Volume	Accumulated dosed quantity in litres or US gallons	Yes
Operating hours	Accumulated number of operating hours (power-on)	No
Motor runtime	Accumulated number of motor runtime hours	No
Strokes	Accumulated number of dosing strokes	No
Power on/off	Accumulated number of times the mains supply has been switched on	No

Service display

This section applies to the DDA, DDC.

Due to the optimised construction and the smooth digital dosing principle, the service periods are more than twice as long as that of conventional pumps. However, the wear parts have to be exchanged at regular intervals to keep the dosing precision and process reliability at a high level. The service display in the pump shows when service of the wear parts is required. The displayed service kit product number makes service more convenient. The following information is presented in the Info display:

Display	Description
Service	-
	Soon
	Now
Service kit	8-digit Grundfos product number
Reset service system	After performing the service, reset the system.

The following service messages appear, depending on what happens first:

Display	Motor runtime [h]	Regular intervals [months] ⁵⁾
Service soon	7,500	23
Service now	8,000	24

⁵⁾ Applies to DDA only

In case of difficult liquids, the service intervals may be shorter and service has to be performed earlier.

Level control

This section applies to the DDA, DDC, DDE-PR and DDE-P.

The pump can be connected to a dual level control unit for monitoring the chemical level in the tank. The pump can react to two level signals:

Level sensors	Pump reaction ⁶⁾	
	DDA, DDC	DDE-PR, DDE-P
 Low-level signal	The display is yellow (Warning). The Low-level signal is flashing. The pump continues running.	The LED lights up in yellow. The pump continues running.
 Empty tank signal	The display is red (Alarm). The Empty tank signal is flashing. The pump stops.	The LED lights up in red. The pump stops.

⁶⁾ Depending on the pump model and settings, the relay outputs can be activated, see section Relay output.

Related information

[Relay output](#)

Relay output

This section applies to DDA, DDC-AR and DDE-PR.

The pump can activate 2 external signals by built-in relays switched via internal potential-free contacts. Depending on the process control requirements, the following relay output settings can be selected:

For the DDA and DDC-AR:

Signal		Description
Relay 1	Relay 2	
Alarm ⁷⁾	Alarm	The display is red, the pump stops (for example Empty signal).
Warning ⁷⁾	Warning	The display is yellow, the pump is running (for example Low-level signal).
Stroke signal	Stroke signal	It signals each full stroke.
Pump dosing	Pump dosing ⁷⁾	The pump is running and dosing.
Pulse input	Pulse input	It signals each incoming pulse from pulse input.
Bus control	Bus control	It is activated by a command in the bus communication. See section Bus communication (only DDA).
	Timer cycle	Timer can be set in menu: on-time, cycle-time, start delay (only DDA)
	Timer week	Timer can be set in menu: procedure, on-time, start time and weekdays (only DDA)

Signal		Description
Relay 1	Relay 2	
Contact type		
NO ⁷⁾	NO ⁷⁾	Normally Open Contact
NC	NC	Normally Closed Contact

⁷⁾ Default setting

For the DDE-PR control variant:

Signal		Description
Relay 1	Relay 2	
Contact type		
Alarm ⁸⁾		Empty tank, motor blocked
	Low level ⁸⁾	Low level tank
	Stroke signal	Every completed stroke
	Pulse input	Every pulse coming in from pulse input
Contact type		
NO ⁸⁾	NO ⁸⁾	Normally Open Contact
NC	NC	Normally Closed Contact

⁸⁾ Default setting

Related information

[Bus communication](#)

Analog output

This section applies to the DDA.

In addition to the analog input (operation mode: analog 0/4-20 mA), the pump is also equipped with an analog 0/4-20 mA output signal. Depending on the process control requirements, the following analog output settings are available:

Setting	Description of analog output signal	Control variant		
		FCM	FC	AR
Output = Input	Analog feedback signal (not for master-slave application): the analog input signal is mapped 1:1 to the analog output.	X	X	X
Actual flow	Flow is measured in the dosing head. (See section Flow measurement.)	X	X ⁹⁾	X ⁹⁾
Backpressure	Backpressure is measured in the dosing head. (See section Pressure monitoring.)	X	X	
Bus control	It is set by a command in the bus communication. (See section Bus communication.)	X	X	X

⁹⁾ Output signal is calculated based on motor speed and pump status (target flow rate).

Related information

[FlowControl](#)

[Pressure monitoring](#)

[Bus communication](#)

Bus communication

This section applies to the DDA.

The pump is equipped with a built-in module for GENIbus communication. With the additional E-Box module (see section E-box for SMART digital S DDA), the pump can be integrated into a fieldbus network.

The bus communication possibilities enable remote monitoring and setting via the fieldbus system.



TM041640

DDA with E-box

Key lock and mechanical lock

For the DDA, DDC:

To protect the pump from maloperation, a key lock can be set by entering a 4-digit PIN code. When the pump is locked, it is still possible to navigate through the menus Alarm and Info, and to acknowledge alarms. Two levels of protection are available:

- Settings: the start/stop key and 100% key are still available.
- Settings + keys: the start/stop key and 100% key are also locked.

For temporary (2 minutes) or final deactivation, the 4-digit preset PIN code has to be entered again.

For the DDE:

The adjustment knob can be locked with a locking screw to fix the current setting.

Basic settings

This section applies to the DDA and DDC.

With load factory settings, the pump can be reset to the default settings. In addition, with save customer settings, the current configuration of the pump is stored and can be activated later by load customer settings. The latest saved configuration is stored in the memory.

Units

This section applies to the DDA and DDC.


It is possible to select metric units (litre/millilitre/bar) or US units (US gallons/psi). Depending on the operation mode and menu, the following units are displayed:

Operation mode/Function	Metric units	US units
Manual control	ml/h or l/h	gph
Pulse control	ml/pulse	ml/pulse
Analog 0/4-20 mA control	ml/h or l/h	gph
Batch control (pulse- or timer-based)	ml or l	gal
Calibration	ml	ml
Volume counter	l	gal
Pressure monitoring	bar	psi

Additional display

This section applies to the DDA and DDC.

The additional display function provides further useful status information, such as the target flow rate or the actual flow rate. The value is shown in the operation display together with the corresponding symbol.



TM041151

Additional display

Pos.	Description
1	Additional display

The following additional information can be selected:

Settings	Description
Default display	Depending on the operation mode:
	Q Actual flow (manual, pulse) ¹⁰⁾
	Q Target flow (pulse)
	↻ Input current (analog) ¹¹⁾
	▮ Remaining batch volume (batch, timer) ¹²⁾
	⏰ Time until next batch (timer) ¹²⁾
Dosed volume	V Total dosed volume, see section Counters
Actual flow	Q Actually measured flow ¹¹⁾
Backpressure	P Current backpressure in the dosing head ¹³⁾

¹⁰⁾ Only DDA-FCM control variant

¹¹⁾ Only DDA pumps and DDC-AR control variant

¹²⁾ Only DDA pumps

¹³⁾ Only DDA-FCM/FC control variant

Related information

[Counters](#)

FlowControl

This section applies to the DDA-FC/FCM control variant.



TM041641

DDA FlowControl


The pump monitors the dosing process of liquids when the FlowControl function is activated. While the pump operates, some influences, such as air bubbles, may cause reduced flow rates or even stop the dosing process. For optimal process safety and reliability, the activated FlowControl function immediately detects and displays the following malfunctions:

- overpressure
- discharge line burst
- air bubbles in the dosing head
- cavitation at the suction side
- suction valve leakage
- discharge valve leakage.

The unique FlowControl is based on an intelligent and maintenance-free sensor integrated in the dosing head. During the dosing process, the sensor measures the actual pressure and sends the measured value to the microprocessor in the pump. An internal indicator diagram is generated combining the actual pressure value with the diaphragm position (stroke length). The dosing process is monitored as the different malfunctions can immediately be detected due to their specific deviations in the curve. Compressible air bubbles, for instance, reduce the discharge phase and the stroke volume.

The sensitivity and delay of the FlowControl function can be adjusted individually.

FlowControl requires a minimum backpressure of 2 bar. Grundfos recommends an additional spring-loaded valve (approx. 3 bar) on the discharge side for dosing low capacities, that is, below 1 l/h.



TM041610

Indicator diagram

Pos.	Description
p	Pressure
S	Stroke length
1	Compression phase
2	Discharge phase
2a	Trouble-free dosing stroke
2b	Air bubbles disturbing the dosing stroke
3	Expansion phase
4	Suction phase

Pressure monitoring

This section applies to the DDA-FCM control variant.

The integrated pressure sensor measures the actual pressure of the system which is shown in the display. A maximum pressure can be set. If the pressure in the system exceeds the set maximum, for example, if there is a closed valve, the pressure monitoring function stops the dosing process immediately. As soon as the backpressure falls below the set maximum, the dosing process continues. In case the pressure drops below the minimum limit, for example, if an outlet line bursts, the pump stops and major chemical spills are prevented.

Pressure setting range

Flow measurement

This section applies to the DDA-FCM control variant.

The pump can precisely measure and display the actual dosing flow. Via the analog 0/4-20 mA output, the actual flow signal can easily be integrated in any process control system without any additional measurement equipment.

The Flow measurement function is based on an indicator diagram, see section FlowControl. Accumulating the length of each discharge stroke phase and multiplying it with the stroke frequency results in the actual flow displayed. Malfunctions, such as air bubbles or lower backpressure, result in a reduced or increased actual flow rate. When the AutoFlowAdapt function, see section AutoFlowAdapt, is activated, the pump compensates these influences by correcting the stroke speed.

AutoFlowAdapt

This section applies to the DDA-FCM control variant.


When activating the AutoFlowAdapt function, even environmental changes are compensated so that the required target flow rate is achieved. The integrated AutoFlowAdapt makes additional monitoring and control devices redundant. The AutoFlowAdapt function is based on the following factors:

- FlowControl: malfunctions are detected.
- Pressure monitoring: system pressure changes are detected.
- Flow measurement: deviations in the target flow are detected.

Examples:

- FlowControl detects air bubbles in the system. Due to a special motor drive strategy and a certain speed increase, the pump tries to keep the flow rate constant. This is especially important when dosing degassing liquids.
- In general, increasing system pressure reduces the stroke volume whereas falling system pressure increases the stroke volume. The AutoFlowAdapt function compensates this by automatically and continuously adapting the motor speed. Despite fluctuating system pressure, dosing accuracy is maintained.

Wiring diagram, DDA



TM041121

Input: Analog, External stop, Pulse

	Function	Pins			
		1/brown	2/white	3/blue	4/black
	Analog	GND/(-) mA	(+) mA		
	External stop	GND		X	
	Pulse	GND			X

Level signals: Empty signal, Low-level signal

	Function	Pins			
		1	2	3	4
	Low-level signal	X		GND	
	Empty signal		X	GND	

GENIbus, Analog output

	Function	Pins				
		1/brown	2/white	3/blue	4/black	5/yellow/green
	GENIbus	+30 V	RS-485 A	RS-485 B		GENIbus Y
	Analog output				(+) mA	GND/(-) mA


Relay outputs

	Function	Pins			
		1/brown	2/white	3/blue	4/black
	Relay 1	X			X
	Relay 2		X	X	

Cable selection

	Cable 1 Analog/external stop/pulse	Cable 2 Level input	Cable 3 GENIbus, analog output	Cable 4 Relay output
Product No.	2 m cable: 96609014 5 m cable: 96609016	See section about suction lances in Accessories.	2 m cable: 96632921 5 m cable: 96632922	2 m cable: 96609017 5 m cable: 96609019

FlowControl signal connection




TM041158

Related information

[Rigid suction lances RSL](#)

Wiring diagram, DDC



TM041187

Input: Analog, External stop, Pulse

	Function	Pins			
		1/brown	2/white	3/blue	4/black
	Analog	GND/(-) mA	(+) mA		
	External stop	GND		X	
	Pulse	GND			X

Level signals: Empty signal, Low-level signal

	Function	Pins			
		1	2	3	4
	Low-level signal	X		GND	
	Empty signal		X	GND	

Relay outputs

Applies to DDC-AR control variant.

	Function	Pins			
		1/brown	2/white	3/blue	4/black
	Relay 1	X			X
	Relay 2		X	X	

Cable selection


	Cable 1 Analog/external stop/pulse	Cable 2 Level input	Cable 4 Relay output
Product No.	2 m cable: 96609014 5 m cable: 96609016	See section about suction lances in Accessories.	2 m cable: 96609017 5 m cable: 96609019

Related information

[Rigid suction lances RSL](#)

Wiring diagram, DDE-PR, -P

This section applies to the DDE-PR/P control variant.



TM048172

Input: External stop, Pulse

	Function	Pins			
		1/brown	2/white	3/blue	4/black
	External stop	GND		X	
	Pulse	GND			X

Level signals: Empty signal, Low-level signal

	Function	Pins			
		1	2	3	4
	Low-level signal	X		GND	
	Empty signal		X	GND	

Relay outputs

This section applies to the DDE-PR control variant.

	Function	Pins			
		1/brown	2/white	3/blue	4/black
	Relay 1 (alarm)	X			X
	Relay 2 (selectable)		X	X	

Cable selection


	Cable 1 External stop/pulse	Cable 2 Level input	Cable 4 Relay output
Product No.	2 m cable: 96609014 5 m cable: 96609016	See section about suction lances in Accessories.	2 m cable: 96609017 5 m cable: 96609019

Related information

[Rigid suction lances RSL](#)

4. Construction

DDA and DDC



Sectional drawing, DDA

Construction

The DDA and DDC pumps are motor-driven diaphragm dosing pumps consisting of the following main parts:

Dosing head: It has a patented design with a minimum clearance space optimised for degassing liquids. It is supplied with integrated de-aeration valve for priming and venting, complete with connection for a 4/6 mm or 0.17" x 1/4" tubing. DDA-FCM/FC pumps have an integrated pressure sensor in the dosing head.

Valves: The double-ball discharge and suction valve ¹⁴⁾ design allows for less clearance space, which is optimal for degassing liquids. Spring-loaded valves for higher viscosities are available as an option.

Connections: The robust and easy-to-use connection packages are optimal for various sizes of tubing or pipes.

Diaphragm: The full PTFE diaphragm is designed for long life and universal chemical resistance.

Flange: The flange is offered with separation chamber, safety diaphragm and drain hole.

Drive unit: It has a positive return crank with patented noiseless spur gear drive, energy recovery spring for high efficiency (only DDA), stepper motor, all mounted in a robust gear housing.

Control cube: It contains operation electronics with display, keys, click-wheel and protective cover.

Housing: It contains drive unit and power electronics with robust signal sockets. The housing can be clicked on the mounting plate.

¹⁴⁾ It is only for pumps up to 7.5 l/h with standard valves.

Material specification


Pos.	Description	Material options
1	Stepper motor	-
2	Cooling element ¹⁵⁾	Aluminium
3	Suction valve, complete ¹⁶⁾	-
4	Valve ball, DN 4 ¹⁷⁾	Ceramic Al ₂ O ₃ 99.5 %, SS 1.4401
5	Dosing head	PP, PVC, PVDF, SS 1.4435
6	Safety diaphragm	EPDM
7	Dosing head screw	SS 1.4301
8	Diaphragm	full PTFE
9	Pressure sensor	-
10	Dosing head cover	PP, SS 1.4301
11	De-aeration valve	PP, PVC, PVDF
12	De-aeration valve O-ring	EPDM/FKM
13	Discharge valve, complete ¹⁶⁾	-
14	Discharge valve O-ring	EPDM, FKM, PTFE
15	Discharge valve ball, DN 8	Ceramic Al ₂ O ₃ 99.5 %, SS 1.4401
16	Discharge valve seat	EPDM, FKM, PTFE
17	Discharge valve ball cage	PP, PVC, PVDF, SS 1.4435
18	Flange	PPO/PS 20 % gf
19	Energy recovery spring ¹⁵⁾	EN 10270-2/VD SiCr
20	Connecting rod	PA 6.6 30 % gf
21	Gear box	PPO/PS 20 % gf
22	Housing	PPO/PS 20 % gf
23	Control cube	PPO/PS 20 % gf
24	Display cover	PC
25	Operation PCB	-
26	Click wheel	PPO/PS 20 % gf
27	Hall sensor	-
28	Power PCB	-
29	Mounting plate	PPO/PS 20 % gf

¹⁵⁾ It is only for DDA.

¹⁶⁾ The pump can be supplied with spring-loaded valves (Material: Tantal).

¹⁷⁾ It is only for pumps up to 7.5 l/h with standard valves.

DDE



TM04-1609

Sectional drawing, DDE

Construction

The DDE pump is a motor-driven diaphragm dosing pump consisting of the following main parts:

Dosing head: It has a patented design with a minimum clearance space optimised for degassing liquids. It is supplied with integrated de-aeration valve for priming and venting, complete with connection for a 4/6 mm or 0.17" x 1/4" tubing.

Valves: The double-ball discharge and suction valve ¹⁸⁾ design allows for less clearance space optimised for degassing liquids. Spring-loaded valves for higher viscosities are available as an option.

Connections: The robust and easy-to-use connection packages are optimal for various sizes of tubing or pipes.

Diaphragm: The full PTFE diaphragm is designed for long life and universal chemical resistance.

Flange: The flange is offered with separation chamber, safety diaphragm and drain hole.

Drive unit: It has a positive return crank with patented noiseless spur gear drive, stepper motor, all mounted in a robust gear housing.

Housing: It contains drive unit, control panel and electronics with robust signal sockets. The housing can be clicked on the mounting plate.

¹⁸⁾ It is only for pumps up to 6 l/h with standard valves.

Material specification


Pos.	Description	Material options
1	Stepper motor	-
2	Suction valve, complete ¹⁹⁾	-
3	Valve ball, DN 4 ²⁰⁾	Ceramic Al ₂ O ₃ 99.5 %, SS 1.4401
4	Dosing head	PP, PVC, PVDF, SS 1.4435
5	Safety diaphragm	EPDM
6	Dosing head screw	SS 1.4301
7	Diaphragm	full PTFE
8	Dosing head cover	PP, SS 1.4301
9	De-aeration valve	PP, PVC, PVDF
10	De-aeration valve O-ring	EPDM/FKM
11	Discharge valve, complete ¹⁹⁾	-
12	Discharge valve O-ring	EPDM, FKM, PTFE
13	Discharge valve ball, DN 8	Ceramic Al ₂ O ₃ 99.5 %, SS 1.4401
14	Discharge valve ball cage	PP, PVC, PVDF, SS 1.4435
15	Discharge valve seat	EPDM, FKM, PTFE
16	Flange	PPO/PS 20 % gf
17	Connecting rod	PA 6.6 30 % gf
18	Gear box	PPO/PS 20 % gf
19	Housing	PPO/PS 20 % gf
20	Hall sensor	-
21	Capacity adjustment knob	PPO/PS 20 % gf
22	Power PCB	-
23	Mounting plate	PPO/PS 20 % gf

¹⁹⁾ The pump can be supplied with spring-loaded valves (Material: Tantal).

²⁰⁾ It is only for pumps up to 6 l/h with standard valves.

5. Dimensions

Dimensions, SMART S DDA




TM041103

Dimensions in mm.

Pump type	A [mm]	A1 [mm]	B [mm]	C [mm]	D [mm]
DDA 7.5-16	280	251	196	46.5	24
DDA 12-10/17-7	280	251	200.5	39.5	24
DDA 30-4	295	267	204.5	35.5	38.5

Dimensions, SMART S DDC



Dimensions in mm.


Pump type	A [mm]	A1 [mm]	B [mm]	C [mm]	D [mm]
DDC 6-10	280	251	196	46.5	24
DDC 9-7	280	251	196	46.5	24
DDC 15-4	280	251	200.5	39.5	24

TM048169

Dimensions, SMART S DDE

The indicated dimensions are the same for all control variants of the DDE range.

The following drawing shows the DDE-PR control variant.



TM041147

Dimensions in mm.

Pump type	A1 [mm]	B [mm]	C [mm]	D [mm]
DDE 6-10	251	196	46.5	24
DDE 15-4	251	200.5	39.5	24

6. Technical data

Technical data, SMART S DDA

Mechanical data		7.5-16	12-10	17-7	30-4
Turn-down ratio (setting range)	[1:X]	3000	1000	1000	1000
Max. dosing capacity	[l/h]	7.5	12.0	17.0	30.0
	[gph]	2.0	3.1	4.5	8.0
Max. dosing capacity with SlowMode 50 %	[l/h]	3.75	6.00	8.50	15.00
	[gph]	1.00	1.55	2.25	4.00
Max. dosing capacity with SlowMode 25 %	[l/h]	1.88	3.00	4.25	7.50
	[gph]	0.50	0.78	1.13	2.00
Min. dosing capacity	[l/h]	0.0025	0.0120	0.0170	0.0300
	[gph]	0.0007	0.0031	0.0045	0.0080
Max. operating pressure ²¹⁾	[bar]	16	10	7	4
	[psi]	230	150	100	60
Max. stroke frequency ²²⁾	[strokes/min]	190	155	205	180
Stroke volume	[ml]	0.74	1.45	1.55	3.10
Accuracy of repeatability	[%]	± 1 (of setpoint)			
Max. suction lift during operation ²³⁾	[m]	6			
Max. suction lift when priming with wet valves ²³⁾	[m]	2	3	3	2
Min. pressure differential between suction and discharge side	[bar]	1 (FC and FCM: 2)			
Max. inlet pressure, suction side	[bar]	2			
Max. viscosity in SlowMode 25 % with spring-loaded valves ²⁴⁾	[mPas] (= cP)	2500	2500	2000	1500
Max. viscosity in SlowMode 50 % with spring-loaded valves ²⁴⁾	[mPas] (= cP)	1800	1300	1300	600
Max. viscosity without SlowMode with spring-loaded valves ²⁴⁾	[mPas] (= cP)	600	500	500	200
Max. viscosity without spring-loaded valves ²⁴⁾	[mPas] (= cP)	50	300	300	150
Min. internal hose/pipe diameter suction/discharge side ^{23) 25)}	[mm]	4	6	6	9
Min. internal hose/pipe diameter suction/discharge side (high viscosity) ²⁵⁾	[mm]	9			
Min./Max. liquid temperature	[°C]	-10/45			
Min./max. ambient temperature	[°C]	0/45			
Min./max. storage temperature	[°C]	-20/70			
Max. relative humidity (non-condensing)	[%]	96			
Max. altitude above sea level	[m]	2000			

²¹⁾ For PVC dosing heads, the maximum pressure is up to 10 bar.

²²⁾ The maximum stroke frequency varies depending on calibration.

²³⁾ Data is based on measurements with water.

²⁴⁾ The maximum suction lift is 1 m, dosing capacity reduced (approx. 30 %).

²⁵⁾ The length of the suction line is 1.5 m, the length of the discharge line is 10 m (at max. viscosity).

Electrical data		7.5-16	12-10	17-7	30-4
Voltage	[V]	100-240 V (- 10 %/+ 10 %), 50/60 Hz			
Length of power cable	[m]	1.5			
Max. inrush current for 2 ms (100 V)	[A]	8			
Max. inrush current for 2 ms (230 V)	[A]	25			
Max. power consumption P ₁ (with E-Box)	[W]	24			
Enclosure class		IP65, Type 4X			
Electrical safety class		II			
Pollution degree		2			

Signal input		7.5-16	12-10	17-7	30-4
Max. load for level input		12 V, 5 mA			
Max. load for pulse input		12 V, 5 mA			
Max. load for External stop input		12 V, 5 mA			
Min. pulse length	[ms]	5			
Max. pulse frequency	[Hz]	100			
Impedance at 0/4-20 mA analog input	[Ω]	15			
Accuracy of analog input (full-scale value)	[%]	± 1.5			
Min. resolution of analog input	[mA]	0.05			
Max. resistance in level/pulse circuit	[Ω]	1000			

Signal output		7.5-16	12-10	17-7	30-4
Max. ohmic load on relay output	[A]	0.5			
Max. voltage on relay/analog output	[V]	30 VDC/30 VAC			
Impedance at 0/4-20 mA analog output	[Ω]	500			
Accuracy of analog output (full-scale value)	[%]	± 1.5			
Min. resolution of analog output	[mA]	0.02			

Weight and size		7.5-16	12-10	17-7	30-4
Weight (PVC, PP, PVDF)	[kg]	2.4	2.4		2.6
Weight (stainless steel)	[kg]	3.2	3.2		4.0
Diaphragm diameter	[mm]	44	50		74

Sound pressure		7.5-16	12-10	17-7	30-4
Max. sound pressure level	[dB(A)]	60			

Approvals: CE, CB, CSA-US, NSF61, EAC, ACS, RCM

Technical data, SMART S DDC

Mechanical data		6-10	9-7	15-4
Turn-down ratio (setting range)	[1:X]	1000	1000	1000
Max. dosing capacity	[l/h]	6.0	9.0	15.0
	[gph]	1.5	2.4	4.0
Max. dosing capacity with SlowMode 50 %	[l/h]	3.00	4.50	7.50
	[gph]	0.75	1.20	2.00
Max. dosing capacity with SlowMode 25 %	[l/h]	1.50	2.25	3.75
	[gph]	0.38	0.60	1.00
Min. dosing capacity	[l/h]	0.0060	0.0090	0.0150
	[gph]	0.0015	0.0024	0.0040
Max. operating pressure	[bar]	10	7	4
	[psi]	150	100	60
Max. stroke frequency ²⁶⁾	[strokes/min]	140	200	180
Stroke volume	[ml]	0.81	0.84	1.58
Accuracy of repeatability	[%]	± 1 (of setpoint)		
Max. suction lift during operation ²⁷⁾	[m]	6		
Max. suction lift when priming with wet valves ²⁷⁾	[m]	2	2	3
Min. pressure differential between suction and discharge side	[bar]	1		
Max. inlet pressure, suction side	[bar]	2		
Max. viscosity in SlowMode 25 % with spring-loaded valves ²⁸⁾	[mPas] (= cP)	2500	2000	2000
Max. viscosity in SlowMode 50 % with spring-loaded valves ²⁸⁾	[mPas] (= cP)	1800	1300	1300
Max. viscosity without SlowMode with spring-loaded valves ²⁸⁾	[mPas] (= cP)	600	500	500
Max. viscosity without spring-loaded valves ²⁸⁾	[mPas] (= cP)	50	50	300
Min. internal hose/pipe diameter suction/discharge side ^{27) 29)}	[mm]	4	6	6
Min. internal hose/pipe diameter suction/discharge side (high viscosity) ²⁹⁾	[mm]	9		
Min./Max. liquid temperature	[°C]	-10/45		
Min./max. ambient temperature	[°C]	0/45		
Min./max. storage temperature	[°C]	-20/70		
Max. relative humidity (non-condensing)	[%]	96		
Max. altitude above sea level	[m]	2000		

²⁶⁾ The maximum stroke frequency varies depending on calibration.

²⁷⁾ Data is based on measurements with water.

²⁸⁾ The maximum suction lift is 1 m, dosing capacity reduced (approx. 30 %).

²⁹⁾ The length of the suction line is 1.5 m, the length of discharge line is 10 m (at max. viscosity).

Electrical data		6-10	9-7	15-4
Voltage	[V]	100-240 V, - 10 %/+ 10 %, 50/60 Hz		
Length of power cable	[m]	1.5		
Max. inrush current for 2 ms (100 V)	[A]	8		
Max. inrush current for 2 ms (230 V)	[A]	25		
Max. power consumption P ₁	[W]	22		
Enclosure class		IP65, Type 4x		
Electrical safety class		II		
Pollution degree		2		

Signal input		6-10	9-7	15-4
Max. load for level input		12 V, 5 mA		
Max. load for pulse input		12 V, 5 mA		
Max. load for External stop input		12 V, 5 mA		
Min. pulse length	[ms]	5		
Max. pulse frequency	[Hz]	100		
Impedance at 0/4-20 mA analog input	[Ω]	15		

Signal input	6-10	9-7	15-4
Accuracy of analog input (full-scale value) [%]	± 1.5		
Min. resolution of analog input [mA]	0.05		
Max. resistance in level/pulse circuit [Ω]	1000		
Signal output	6-10	9-7	15-4
Max. ohmic load on relay output [A]	0.5		
Max. voltage on relay output [V]	30 VDC / 30 VAC		
Weight and size	6-10	9-7	15-4
Weight (PVC, PP, PVDF) [kg]	2.4		
Weight (stainless steel) [kg]	3.2		
Diaphragm diameter [mm]	44		50
Sound pressure	6-10	9-7	15-4
Max. sound pressure level [dB(A)]	60		

Approvals: CE, CB, CSA-US, NSF61, EAC, ACS, RCM

Technical data, SMART S DDE

Mechanical data		6-10	15-4
Turn-down ratio (setting range)	[1:X]	1000	1000
Max. dosing capacity	[l/h]	6.0	15.0
	[gph]	1.5	4.0
Min. dosing capacity	[l/h]	0.006	0.015
	[gph]	0.0015	0.0040
Max. operating pressure	[bar]	10	4
	[psi]	150	60
Max. stroke frequency	[strokes/min]	140	180
Stroke volume	[ml]	0.81	1.58
Accuracy of repeatability	[%]	± 5 (of setpoint)	
Max. suction lift during operation ³⁰⁾	[m]	6	
Max. suction lift when priming with wet valves ³⁰⁾	[m]	2	3
Min. pressure differential between suction and discharge side	[bar]	1	
Max. inlet pressure, suction side	[bar]	2	
Max. viscosity with spring-loaded valves ³¹⁾	[mPas] (= cP)	600	500
Max. viscosity without spring-loaded valves ³¹⁾	[mPas] (= cP)	50	
Min. internal hose/pipe diameter suction/discharge side ^{30) 32)}	[mm]	4	6
Min. internal hose/pipe diameter suction/discharge side (high viscosity) ³²⁾	[mm]	9	
Min./max. liquid temperature	[°C]	-10/45	
Min./max. ambient temperature	[°C]	0/45	
Min./max. storage temperature	[°C]	-20/70	
Max. relative humidity (non-condensing)	[%]	96	
Max. altitude above sea level	[m]	2000	

³⁰⁾ Data is based on measurements with water

³¹⁾ Maximum suction lift: 1 m, dosing capacity reduced (approx. 30 %)

³²⁾ Length of suction line: 1.5 m, length of discharge line: 10 m (at max. viscosity)

Electrical data		6-10	15-4
Voltage	[V]	100-240 V, - 10 %/+ 10 %, 50/60 Hz	
Length of power cable	[m]	1.5	
Max. inrush current for 2 ms (100 V)	[A]	8	
Max. inrush current for 2 ms (230 V)	[A]	25	
Max. power consumption P ₁	[W]	19	
Enclosure class		IP65, Type 4x	
Electrical safety class		II	
Pollution degree		2	

Signal input		6-10	15-4
Max. load for level input		12 V, 5 mA	
Max. load for pulse input		12 V, 5 mA	
Max. load for external stop input		12 V, 5 mA	
Min. pulse length	[ms]	5	
Max. pulse frequency	[Hz]	100	
Max. resistance in level/pulse circuit	[Ω]	1000	

Signal output		6-10	15-4
Max. ohmic load on relay output	[A]	0.5	
Max. voltage on relay output	[V]	30 VDC/30 VAC	

Weight and size		6-10	15-4
Weight (PVC, PP, PVDF)	[kg]	2.4	
Weight (stainless steel)	[kg]	3.2	
Diaphragm diameter	[mm]	44	50

Sound pressure	6-10	15-4
Max. sound pressure level [dB(A)]	60	

Approvals: CE, CB, CSA-US, NSF61, EAC, ACS, RCM

Technical data for CIP (Clean-In-Place) applications

Short-term temperature limits for maximum 40 minutes at maximum 2 bar operating pressure:

Max. liquid temperature for dosing head material PVDF	[°C]	85
Max. liquid temperature for dosing head material stainless steel	[°C]	120

7. Pump selection

DDA, standard range

Power supply: 1 x 100-240 V, 50/60 Hz (switch mode)

Mains plug: EU

Valves: Standard

Connection set: U2U2 / I001 / AA, see section Type key

Max. flow [l/h]	Max. pressure [bar]	Materials			Installation set ³³⁾	Type designation ³⁴⁾	Product number		
		Dosing head	Gaskets	Valve ball			AR	FC	FCM
7.5	16	PP	EPDM	Ceramic	No	DDA 7.5-16 AR -PP/E/C-F-31U2U2FG	97721938	97721972	97722006
					Yes	DDA 7.5-16 AR -PP/E/C-F-31I001FG	97721939	97721973	97722007
			FKM	Ceramic	No	DDA 7.5-16 AR -PP/V/C-F-31U2U2FG	97721942	97721976	97722010
					Yes	DDA 7.5-16 AR -PP/V/C-F-31I001FG	97721943	97721977	97722011
		PVC ³⁵⁾	EPDM	Ceramic	No	DDA 7.5-16 AR -PVC/E/C-F-31U2U2FG	97721946	97721980	97722014
					Yes	DDA 7.5-16 AR -PVC/E/C-F-31I001FG	97721947	97721981	97722015
			FKM	Ceramic	No	DDA 7.5-16 AR -PVC/V/C-F-31U2U2FG	97721950	97721984	97722018
					Yes	DDA 7.5-16 AR -PVC/V/C-F-31I001FG	97721951	97721985	97722019
		PVDF	PTFE	Ceramic	No	DDA 7.5-16 AR -PV/T/C-F-31U2U2FG	97721966	97722000	97722034
					Yes	DDA 7.5-16 AR -PV/T/C-F-31I001FG	97721967	97722001	97722035
		SS	PTFE	SS 1.4401	No	DDA 7.5-16 AR -SS/T/SS-F-31AAFG	97721970	97722004	97722038
12	10	PP	EPDM	Ceramic	No	DDA 12-10 AR -PP/E/C-F-31U2U2FG	97722040	97722074	97722108
					Yes	DDA 12-10 AR -PP/E/C-F-31I002FG	97722041	97722075	97722109
			FKM	Ceramic	No	DDA 12-10 AR -PP/V/C-F-31U2U2FG	97722044	97722078	97722112
					Yes	DDA 12-10 AR -PP/V/C-F-31I002FG	97722045	97722079	97722113
		PVC	EPDM	Ceramic	No	DDA 12-10 AR -PVC/E/C-F-31U2U2FG	97722048	97722082	97722116
					Yes	DDA 12-10 AR -PVC/E/C-F-31I002FG	97722049	97722083	97722117
			FKM	Ceramic	No	DDA 12-10 AR -PVC/V/C-F-31U2U2FG	97722052	97722086	97722120
					Yes	DDA 12-10 AR -PVC/V/C-F-31I002FG	97722053	97722087	97722121
		PVDF	PTFE	Ceramic	No	DDA 12-10 AR -PV/T/C-F-31U2U2FG	97722068	97722102	97722136
					Yes	DDA 12-10 AR -PV/T/C-F-31I002FG	97722069	97722103	97722137
		SS	PTFE	SS 1.4401	No	DDA 12-10 AR -SS/T/SS-F-31AAFG	97722072	97722106	97722140
17	7	PP	EPDM	Ceramic	No	DDA 17-7 AR -PP/E/C-F-31U2U2FG	97722142	97722176	97722210
					Yes	DDA 17-7 AR -PP/E/C-F-31I002FG	97722143	97722177	97722211
			FKM	Ceramic	No	DDA 17-7 AR -PP/V/C-F-31U2U2FG	97722146	97722180	97722214
					Yes	DDA 17-7 AR -PP/V/C-F-31I002FG	97722147	97722181	97722215
		PVC	EPDM	Ceramic	No	DDA 17-7 AR -PVC/E/C-F-31U2U2FG	97722150	97722184	97722218
					Yes	DDA 17-7 AR -PVC/E/C-F-31I002FG	97722151	97722185	97722219
			FKM	Ceramic	No	DDA 17-7 AR -PVC/V/C-F-31U2U2FG	97722154	97722188	97722222
					Yes	DDA 17-7 AR -PVC/V/C-F-31I002FG	97722155	97722189	97722223
		PVDF	PTFE	Ceramic	No	DDA 17-7 AR -PV/T/C-F-31U2U2FG	97722170	97722204	97722238
					Yes	DDA 17-7 AR -PV/T/C-F-31I002FG	97722171	97722205	97722239
		SS	PTFE	SS 1.4401	No	DDA 17-7 AR -SS/T/SS-F-31AAFG	97722174	97722208	97722242

Max. flow [l/h]	Max. pressure [bar]	Materials			Installation set ³³⁾	Type designation ³⁴⁾	Product number		
		Dosing head	Gaskets	Valve ball			AR	FC	FCM
30	4	PP	EPDM	Ceramic	No	DDA 30-4 AR -PP/E/C-F-31U2U2FG	97722244	97722278	97722313
					Yes	DDA 30-4 AR -PP/E/C-F-31I002FG	97722245	97722279	97722314
			FKM	Ceramic	No	DDA 30-4 AR -PP/N/C-F-31U2U2FG	97722248	97722282	97722317
					Yes	DDA 30-4 AR -PP/N/C-F-31I002FG	97722249	97722283	97722318
		PVC	EPDM	Ceramic	No	DDA 30-4 AR -PVC/E/C-F-31U2U2FG	97722252	97722286	97722331
					Yes	DDA 30-4 AR -PVC/E/C-F-31I002FG	97722253	97722288	97722332
			FKM	Ceramic	No	DDA 30-4 AR -PVC/N/C-F-31U2U2FG	97722256	97722291	97722335
					Yes	DDA 30-4 AR -PVC/N/C-F-31I002FG	97722257	97722292	97722336
		PVDF	PTFE	Ceramic	No	DDA 30-4 AR -PV/T/C-F-31U2U2FG	97722272	97722307	97722351
					Yes	DDA 30-4 AR -PV/T/C-F-31I002FG	97722273	97722308	97722352
		SS	PTFE	SS 1.4401	No	DDA 30-4 AR -SS/T/SS-F-31AAFG	97722276	97722311	97722355

33) Installation set includes: 2 pump connections, foot valve, injection unit, 6 m PE discharge hose, 2 m PVC suction hose, 2 m PVC de-aeration hose (4/6 mm)

34) Also available in **FC**- and **FCM**-control version

35) PVC dosing heads only up to 10 bar

Related information

[Type key](#)

DDC, standard range

Power supply: 1 x 100-240 V, 50/60 Hz (switch mode)

Mains plug: EU

Valves: Standard

Connection set: U2U2 / I001 / AA, see section Type key

Max. flow [l/h]	Max. pressure [bar]	Materials			Installation set ³⁶⁾	Type designation ³⁷⁾	Product number	
		Dosing head	Gaskets	Valve ball			A	AR
6	10	PP	EPDM	Ceramic	No	DDC 6-10 A -PP/E/C-F-31U2U2FG	97721324	97721358
					Yes	DDC 6-10 A -PP/E/C-F-31I001FG	97721325	97721359
			FKM	Ceramic	No	DDC 6-10 A -PP/N/C-F-31U2U2FG	97721328	97721362
					Yes	DDC 6-10 A -PP/N/C-F-31I001FG	97721329	97721363
		PVC	EPDM	Ceramic	No	DDC 6-10 A -PVC/E/C-F-31U2U2FG	97721332	97721366
					Yes	DDC 6-10 A -PVC/E/C-F-31I001FG	97721333	97721367
			FKM	Ceramic	No	DDC 6-10 A -PVC/N/C-F-31U2U2FG	97721336	97721370
					Yes	DDC 6-10 A -PVC/N/C-F-31I001FG	97721337	97721371
		PVDF	PTFE	Ceramic	No	DDC 6-10 A -PV/T/C-F-31U2U2FG	97721352	97721387
					Yes	DDC 6-10 A -PV/T/C-F-31I001FG	97721353	97721388
		SS	PTFE	SS 1.4401	No	DDC 6-10 A -SS/T/SS-F-31AAFG	97721356	97721391
9	7	PP	EPDM	Ceramic	No	DDC 9-7 A -PP/E/C-F-31U2U2FG	97721393	97721427
					Yes	DDC 9-7 A -PP/E/C-F-31I002FG	97721394	97721428
			FKM	Ceramic	No	DDC 9-7 A -PP/N/C-F-31U2U2FG	97721397	97721431
					Yes	DDC 9-7 A -PP/N/C-F-31I002FG	97721398	97721432
		PVC	EPDM	Ceramic	No	DDC 9-7 A -PVC/E/C-F-31U2U2FG	97721401	97721435
					Yes	DDC 9-7 A -PVC/E/C-F-31I002FG	97721402	97721436
			FKM	Ceramic	No	DDC 9-7 A -PVC/N/C-F-31U2U2FG	97721405	97721439
					Yes	DDC 9-7 A -PVC/N/C-F-31I002FG	97721406	97721440
		PVDF	PTFE	Ceramic	No	DDC 9-7 A -PV/T/C-F-31U2U2FG	97721421	97721455
					Yes	DDC 9-7 A -PV/T/C-F-31I002FG	97721422	97721456
		SS	PTFE	SS 1.4401	No	DDC 9-7 A -SS/T/SS-F-31AAFG	97721425	97721459

Max. flow [l/h]	Max. pressure [bar]	Materials			Installation set ³⁶⁾	Type designation ³⁷⁾	Product number	
		Dosing head	Gaskets	Valve ball			A	AR
15	4	PP	EPDM	Ceramic	No	DDC 15-4 A-PP/E/C-F-31U2U2FG	97721461	97721495
					Yes	DDC 15-4 A-PP/E/C-F-31I002FG	97721462	97721496
			FKM	Ceramic	No	DDC 15-4 A-PP/N/C-F-31U2U2FG	97721465	97721499
					Yes	DDC 15-4 A-PP/N/C-F-31I002FG	97721466	97721500
		PVC	EPDM	Ceramic	No	DDC 15-4 A-PVC/E/C-F-31U2U2FG	97721469	97721503
					Yes	DDC 15-4 A-PVC/E/C-F-31I002FG	97721470	97721504
			FKM	Ceramic	No	DDC 15-4 A-PVC/N/C-F-31U2U2FG	97721473	97721507
					Yes	DDC 15-4 A-PVC/N/C-F-31I002FG	97721474	97721508
		PVDF	PTFE	Ceramic	No	DDC 15-4 A-PV/T/C-F-31U2U2FG	97721489	97721523
					Yes	DDC 15-4 A-PV/T/C-F-31I002FG	97721490	97721524
		SS	PTFE	SS 1.4401	No	DDC 15-4 A-SS/T/SS-F-31AAFG	97721493	97721527

³⁶⁾ Installation set includes: 2 pump connections, foot valve, injection unit, 6 m PE discharge hose, 2 m PVC suction hose, 2 m PVC de-aeration hose (4/6 mm)

³⁷⁾ Also available in **AR**-control version

Related information

[Type key](#)

DDE, standard range

Power supply: 1 x 100-240 V, 50/60 Hz (switch mode)

Mains plug: EU

Valves: Standard

Connection set: U2U2 / I001 / AA, see section Type key

Max. flow [l/h]	Max. pressure [bar]	Materials			Installation set ³⁸⁾	Type designation ³⁹⁾	Product number		
		Dosing head	Gaskets	Valve ball			B	P	PR
6	10	PP	EPDM	Ceramic	No	DDE 6-10 B-PP/E/C-X-31U2U2FG	97720905	97720949	98147240
					Yes	DDE 6-10 B-PP/E/C-X-31I001FG	97720906	97720950	98147261
			FKM	Ceramic	No	DDE 6-10 B-PP/N/C-X-31U2U2FG	97720909	97720953	98147264
					Yes	DDE 6-10 B-PP/N/C-X-31I001FG	97720910	97720954	98147265
		PVC	EPDM	Ceramic	No	DDE 6-10 B-PVC/E/C-X-31U2U2FG	97720923	97720957	98147268
					Yes	DDE 6-10 B-PVC/E/C-X-31I001FG	97720924	97720958	98147269
			FKM	Ceramic	No	DDE 6-10 B-PVC/N/C-X-31U2U2FG	97720927	97720961	98147272
					Yes	DDE 6-10 B-PVC/N/C-X-31I001FG	97720928	97720962	98147273
		PVDF	PTFE	Ceramic	No	DDE 6-10 B-PV/T/C-X-31U2U2FG	97720943	97720977	98147288
					Yes	DDE 6-10 B-PV/T/C-X-31I001FG	97720944	97720978	98147289
		SS	PTFE	SS 1.4401	No	DDE 6-10 B-SS/T/SS-X-31AAFG	97720947	97720981	98147292
15	4	PP	EPDM	Ceramic	No	DDE 15-4 B-PP/E/C-X-31U2U2FG	97720983	97721017	98147294
					Yes	DDE 15-4 B-PP/E/C-X-31I002FG	97720984	97721018	98147295
			FKM	Ceramic	No	DDE 15-4 B-PP/N/C-X-31U2U2FG	97720987	97721021	98147298
					Yes	DDE 15-4 B-PP/N/C-X-31I002FG	97720988	97721022	98147299
		PVC	EPDM	Ceramic	No	DDE 15-4 B-PVC/E/C-X-31U2U2FG	97720991	97721025	98147302
					Yes	DDE 15-4 B-PVC/E/C-X-31I002FG	97720992	97721026	98147303
			FKM	Ceramic	No	DDE 15-4 B-PVC/N/C-X-31U2U2FG	97720995	97721029	98147306
					Yes	DDE 15-4 B-PVC/N/C-X-31I002FG	97720996	97721030	98147307
		PVDF	PTFE	Ceramic	No	DDE 15-4 B-PV/T/C-X-31U2U2FG	97721011	97721045	98147322
					Yes	DDE 15-4 B-PV/T/C-X-31I002FG	97721012	97721046	98147323
		SS	PTFE	SS 1.4401	No	DDE 15-4 B-SS/T/SS-X-31AAFG	97721015	97721049	98147326

³⁸⁾ Installation set includes: 2 pump connections, foot valve, injection unit, 6 m PE discharge hose, 2 m PVC suction hose, 2 m PVC de-aeration hose (4/6 mm)

³⁹⁾ Also available in **P**- and **PR**-control versions

Related information

[Type key](#)

DDA, DDC, DDE, non-standard range

Note that not all material combinations are possible.

Key to the three following tables:

Maximum flow - pressure	[l/h] - [bar]
Control variant	B: Basic (DDE)
	P: B with pulse mode (DDE)
	PR: P with relay output (DDE)
	A: Standard (DDC)
	AR: A with alarm relay and analog input (DDA, DDC)
	FC: AR with FlowControl (DDA)
	FCM: FC with flow measurement (DDA)
Materials	Dosing head
	PP: PP
	PVC: PVC (PVC dosing heads only up to 10 bar)
	PV: PVDF
	SS: Stainless steel 1.4401
	Gaskets
	E: EPDM
	V: FKM
	T: PTFE
	Valve ball
	C: Ceramic
	SS: Stainless steel 1.4401
Control cube position	F: Front-mounted (change to left and right possible)
	X: No control cube (DDE)
Supply voltage	3: 1 x 100-240 V, 50/60 Hz
Valve type	1: Standard
	2: Spring-loaded (HV version)
Connection/Installation set	Suction / discharge connection
	U2U2: Union nut G 5/8" with parts for hose connection 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm
	U7U7: Union nut G 5/8" with parts for hose connection 0.17" x 1/4"; 1/4" x 3/8"; 3/8" x 1/2"
	AA: Union nut G 5/8" with threaded connection Rp 1/4", internal thread
	VV: Union nut G 5/8" with threaded connection 1/4" NPT, internal thread
	XX: No connections included
	Installation set⁴⁰⁾
	I001: 4/6 mm (up to 7.5 l/h, 13 bar)
	I002: 9/12 mm (up to 60 l/h, 9 bar)
	I003: 0.17" x 1/4" (up to 7.5 l/h, 13 bar)
	I004: 3/8" x 1/2" (up to 60 l/h, 10 bar)
Mains plug	F: EU
	B: USA, Canada
	G: UK
	I: Australia, New Zealand
	E: Switzerland
	J: Japan
	L: Argentina
Design	G: Grundfos red
	A: Grundfos green
	B: Grundfos black
	X: Neutral/black
	C: China approval
Special variant	C3: Inspection Certificate 3.1 (EN 10204)

⁴⁰⁾ The installation set includes 2 pump connections, foot valve, injection unit, 6 m PE discharge hose, 2 m PVC suction hose, 2 m PVC de-aeration hose (4/6 mm).

DDA

Max. flow - press.	Control variant	Materials			Control cube position	Supply voltage	Valve type	Connection/ Installation set	Mains plug	Design	Special variant
		Head	Gaskets	Ball							
7.5-16	AR FC FCM	PP	E V	C	F	3	1 2	U2U2 U7U7 XX I001 I003	F B G I E J L	G A B X C	C3
		PVC	E V	C							
		PV	T								
		SS	T	SS				AA VV XX			
12-10 17-7 30-4	AR FC FCM	PP	E V	C	F	3	1 2	U2U2 U7U7 XX I002 I004			
		PVC	E V	C							
		PV	T								
		SS	T	SS				AA VV XX			

DDC

Max. flow - press.	Control variant	Materials			Control cube position	Supply voltage	Valve type	Connection/ Installation set	Mains plug	Design	Special variant
		Head	Gaskets	Ball							
6-10	A AR	PP	E V	C	F	3	1 2	U2U2 U7U7 XX I001 I003	F B G I E J L	G A B X C	C3
		PVC	E V	C							
		PV	T								
		SS	T	SS				AA VV XX			
9-7 15-4	A AR	PP	E V	C	F	3	1 2	U2U2 U7U7 XX I002 I004			
		PVC	E V	C							
		PV	T								
		SS	T	SS				AA VV XX			


DDE

Max. flow - press.	Control variant	Materials			Control cube position	Supply voltage	Valve type	Connection/ Installation set	Mains plug	Design	Special variant
		Head	Gaskets	Ball							
6-10	B P PR	PP	E V	C	X	3	1 2	U2U2 U7U7 XX I001 I003	F B G I E J L	B C	C3
		PVC	E V	C							
		PV	T								
		SS	T	SS				AA VV XX			
15-4	B P PR	PP	E V	C	X	3	1 2	U2U2 U7U7 XX I002 I004			
		PVC	E V	C							
		PV	T								
		SS	T	SS				AA VV XX			

8. Accessories for small dosing pumps up to 60 l/h

Accessories overview

Grundfos offer a comprehensive range of accessories covering every need when dosing with Grundfos pumps.



TM086938

Dosing pump with accessories

Pos.	Description
1	Injection units, see sections Injection units and Hot-injection units with ball valve
2	Hoses, see section Hoses
3	Multi-function valves, pressure loading valves, pressure relief valves, pressure valves, see sections Multi-function valves, pressure relief valves, pressure loading valves, Pressure relief valves PRV, and Pressure valves
4	Example: SMART Digital dosing pump
5	Cables, see section Cables and plugs
6	E-box, see section E-box for SMART digital S DDA
7	Dosing tanks, see section Adapters
8	Handheld mixer, see section Accessories for dosing tanks
9	Foot valves and rigid suction lances, see sections Foot valves FV and Rigid suction lances RSL
10	Drain valves, see section Accessories for dosing tanks
-	Installation kits: Pump connection kits and inlay kits
-	Adapters T-pieces See section Installation kits for dosing pumps
-	Accessories for hydraulic connection

Related information

Installation kits for dosing pumps

Cables and plugs

E-box for SMART digital S DDA

Hoses

Foot valves FV

Rigid suction lances RSL

Injection units

Hot-injection units with ball valve

Multi-function valves, pressure relief valves, pressure loading valves

Pressure relief valves PRV

Pressure valves

Pump connection kits and inlay kits

Threaded adapters

Union nut adapters

Square tank, 100 litres


Cylindrical tanks

Accessories for dosing tanks

Installation kits for dosing pumps

An installation kit includes the following parts:

- injection unit with spring-loaded non-return valve, see section Injection units
- PE outlet hose, 6 m
- PVC inlet hose, 2 m
- PVC de-aeration hose, 2 m
- PE foot valve with strainer and weight, without or with level indication, see section Foot valves FV.



TM085687

Installation kit with foot valve without level indication



TM085684

Installation kit with foot valve with level indication

Related information

[Foot valves FV](#)

[Injection units](#)

Technical data

Max. flow rate ⁴¹⁾ [l/h]	Max. pressure [bar]	Size		Material of injection unit			Product number	
		Inlet / outlet hose [mm]	De-aeration hose [mm]	Body	Gasket	Ball	Foot valve without level indication	Foot valve with level indication
7.5	13	4/6	4/6	PP	FKM	Ceramic	95730440	95730464
					EPDM	Ceramic	95730441	95730465
				PVC	FKM	Ceramic	95730442	95730466
					EPDM	Ceramic	95730443	95730467
					PTFE	Ceramic	95730444	95730468
				PVDF	FKM	Ceramic	95730445	95730469
					EPDM	Ceramic	95730446	95730470
					PTFE	Ceramic	95730447	95730471
				PP	FKM	Ceramic	95730448	95730472
					EPDM	Ceramic	95730449	95730473
				PVC	FKM	Ceramic	95730450	95730474
					EPDM	Ceramic	95730451	95730475
					PTFE	Ceramic	95730452	95730476
30	12	6/9	4/6	PVDF	FKM	Ceramic	95730453	95730477
					EPDM	Ceramic	95730454	95730478
					PTFE	Ceramic	95730455	95730479
				PP	FKM	Ceramic	95730456	95730480
					EPDM	Ceramic	95730457	95730481
				PVC	FKM	Ceramic	95730458	95730482
					EPDM	Ceramic	95730459	95730483
					PTFE	Ceramic	95730460	95730484
				PVDF	FKM	Ceramic	95730461	95730485
					EPDM	Ceramic	95730462	95730486
					PTFE	Ceramic	95730463	95730487
				PP	FKM	Ceramic	95730456	95730480
					EPDM	Ceramic	95730457	95730481
60	9	9/12	4/6	PVC	FKM	Ceramic	95730458	95730482
					EPDM	Ceramic	95730459	95730483
					PTFE	Ceramic	95730460	95730484
				PVDF	FKM	Ceramic	95730461	95730485
					EPDM	Ceramic	95730462	95730486
					PTFE	Ceramic	95730463	95730487

⁴¹⁾ Viscosity similar to water

Cables and plugs

The listed cables and plugs are suitable for connecting a pump to external control devices, such as process controllers, flow meters, start/stop contacts, or level sensors.



TM048267

Cable and plug

Technical data

- Cable material: PVC, 0.34 mm²
- Plug size: M 12

Socket	Application		Pins	Plug type	Cable length [m]	Product number
	Input	Analog pulse External stop	4	Straight	2	96609014
					5	96609016
					No cable	96698715
				Angled	2	96693246
	Input	Low level Empty tank	4	Straight	No cable	96698715
	Output	Analog	5	Straight	2	96632921
					5	96632922
					No cable	96609031
	Input/Output	GENIbus / Modbus	5	Angled	2	96699697
				Straight	3	98589048
	Output	Relay 1 Relay 2	4	Straight	2	96609017
					5	96609019
					No cable	96696198
				Angled	2	96698716

E-box for SMART digital S DDA

The Grundfos E-box (Extension Box) is a plug-and-play fieldbus communication interface for the integration of SMART Digital S DDA dosing pumps (up to 30 l/h) into a fieldbus network. Fieldbus communication allows for using the DDA dosing pump in industrial automation systems (PLC, SCADA) where advanced remote control and monitoring functions are required:

- remote control of all settings, such as operation mode, flow rate, etc.
- remote monitoring of all parameters, such as measured flow, pressure, faults with cause, etc.

The E-box contains a standard Grundfos CIM (communication interface module) for data transmission between a fieldbus network and a Grundfos pump.


SMART Digital S DDA dosing pumps can be easily retrofitted with the E-box: it is simply placed between the pump and the mounting plate. The E-box has a connecting cable that is plugged directly into the pump.

Description	Product number
E-box 150 Profibus DP	97513994
E-box 200 Modbus RTU	98563350
E-box 500 Ethernet	99171932



E-box

Dimensions



E-box, dimensions

A [mm]	B [mm]	C [mm]	D [mm]
110	150	177	48

General data

Supply voltage		30 VDC, ± 10 % (via M 12 plug of DDA)
Max. power consumption		5 W
Max. relative humidity		96 %
Pollution degree		2
Enclosure class		IP65 according to IEC 60529 Type 4x
Electrical safety class		3
Min./max. ambient temperature		0/45 °C
Approvals		CE, CB, CSA-US, RCM
Weight		0.4 kg
GENIbus connection (E-box to pump)	Data protocol	GENIbus
	GENIbus connection type	Three-wire RS-485
	Transmission speed	9.6 kbits/s
	Cable length	160 mm

E-box 150 Profibus DP

Required pump software for retrofitting	V2.5 or higher
Profibus implementation class	DP-V0
Connection type	RS-485, two-wire (lines: A, B)
Recommended cable type	Screened, double-twisted pair
	Conductor cross-section: 0.34 - 1 mm ² AWG: 22-17
Maximum cable length	100 m at 12000 kbits/s
	1200 m at 9.6 kbits/s
Slave address (set in DDA display)	1-126
Line termination (set via DIP switches)	On/off
Supported data rates	9.6 - 12000 kbits/s
GSD file for system integration: http://net.grundfos.com/qr/i/GRUN0CD9	

E-box 200 Modbus RTU

Required pump software for retrofitting	V2.5 or higher
Connection type	RS-485, two-wire + common
Recommended cable type	Screened, twisted pair
	Conductor cross-section: 0.20 - 0.25 mm ² AWG: 24-23
Maximum cable length	1200 m
Slave address (set in DDA display)	1-247
Line termination (set via DIP switches)	On/off
Supported data rates	9600 / 19200 / 38400 bits/s

E-box 500 Ethernet

Required pump software for retrofitting	V2.5 or higher
Ethernet protocol	PROFINET IO/Modbus TCP (selected via rotary switch)
Application layer	DHCP, HTTP, Ping, FTP, SMTP, SNMP, Modbus TCP
Transport layer	TCP
Internet layer	Internet protocol V4 (IPv4)
Link layer	ARP, media access control (Ethernet)
Recommended cable type	Screened/unscreened, twisted-pair cables, CAT5, CAT5e or CAT6
Maximum cable length	100 m at 10/100 Mbits/s
Supported data rates	10 / 100 Mbits/s

Hoses

Hoses are available in various materials, sizes and lengths for small dosing pumps.



TM048268

Hoses

Technical data

Max. flow rate ⁴²⁾ [l/h]	Size (internal/external diameter) [mm]	Material	Max. pressure at 20 °C [bar]	Length [m]	Product number
7.5	4/6	PE	13	3	91835676
				10	91836504
				50	91835680
		PVC	0.5	3	96701733
				10	96702133
				50	96727418
		ETFE	20	3	95730337
				10	95730338
				50	95730339
17	5/8	PE	13	3	95730888
				10	96727393
				50	95730889
		PE	12	3	96727409
				10	96727412
				50	96727415
		PVC	0.5	3	95730334
				10	95730335
				50	95730336
30	6/9	ETFE	20	3	95730340
				10	95730341
				50	95730342
		PVC, textile-reinforced	23	3	96693751
				10	96653571
				50	91835686
		PE	9	3	96727395
				10	96705657
				50	96727398
60	9/12	PVC	0.5	3	96727434
				10	95730890
				50	95724702
		ETFE	13	3	95730343
				10	95730344
				50	95730345

⁴²⁾ Viscosity similar to water

Foot valves FV

Foot valves are installed at the lower end of the inlet hose. They are available either without level indication or with low-level and empty-tank indication.

Foot valves include:

- weight
- strainer (mesh size approx. 0.8 mm)
- non-return valve
- hose connection set: 4/6 mm, 6/9 mm, 6/12 mm and 9/12 mm
- pipe connection set: threaded, Rp 1/4", internal thread (stainless steel).

Foot valves with low-level and empty-tank indication additionally include:

- reed-switch unit with two floaters
- 5 meters of cable with PE jacket
- M 12 plug to connect DDA, DDC, DDE or DDI dosing pump
- PE cap, Ø58 mm, for assembly in Grundfos cylindrical tanks, or for use with tank adapters.

The contact type of the low-level and empty-tank indication is factory-set to NO. The contact type can be set to NC by turning the floaters upside down.

Electrical data of the level indication:


- max. voltage: 48 V
- max. current: 0.5 A
- max. load: 10 VA.



Foot valves: without level indication (left), with level indication (right)

TM085698


Dimensions



TM086081

FV without level indication, PE/PVDF; with ceramic weight


A [mm]	D	ØF [mm]	I [mm]
71.8	G 5/8	35	5



TM048494

FV without level indication, stainless steel

A [mm]	D	ØF [mm]	I [mm]
30	G 5/8	30	4



TM082553

FV with level indication

A [mm]	D	D1/D2/D3 [mm]	E [mm]	ØF [mm]	G [mm]	H [mm]
204	G 5/8	12/9/6	58	35	101	49

Technical data

Max. flow rate [l/h]	Material			Product number	
	Body	Gasket	Ball	Without level indication	With level indication
60	PE	FKM, EPDM	Ceramic	98070951	98070966
		PTFE	Ceramic	98070952	98070967
	PVDF	FKM, EPDM	Ceramic	98070953	98070968
		PTFE	Ceramic	98070954	98070969
	SS	PTFE	SS	98070963	-

Rigid suction lances RSL

Grundfos offers a comprehensive range of rigid suction lances for a variety of chemical containers.

Rigid suction lances are installed at the lower end of the inlet hose. They are available either without level indication or with low-level and empty-tank indication. Their immersion depth is adjustable.

Rigid suction lances include:

- strainer (mesh size approx. 0.8 mm)
- non-return valve
- hose connection set: 4/6 mm, 6/9 mm, 6/12 mm and 9/12 mm
- adjustable tank connection with holes, for example, relief line.

Rigid suction lances with low-level and empty-tank indication additionally include:

- reed-switch unit with 2 floaters
- 5 meters of cable with PE jacket
- M 12 plug to connect DDA, DDC, DDE or DDI dosing pump.

The contact type of the low-level and empty-tank indication is factory-set to NO. The contact type can be set to NC by turning the floaters upside down.

Electrical data of the level indication:


- max. voltage: 48 V
- max. current: 0.5 A
- max. load: 10 VA.



TM048458

Rigid suction lance

Dimensions



TM048445

RSL with or without level indication

A [mm]	B [mm]	C [mm]	D	E	ØF [mm]	G [mm]	H [mm]	I [mm]
400								
500								
570								
690	110	99	G 5/8	G 2	32	85	25	4.5
820								
980								
1100								
1200								

Dosing tank selection

For dosing tank type	Tank volume	Recommended immersion depth
	[l]	[mm]
Grundfos cylindrical tank, see section Cylindrical tanks	40	400
	60	500
	100	690
	200	690
	300	980
	500	1100
	1000	1200
Grundfos square tank, see section Square tank, 100 litres ⁴³⁾	100	690
L-ring drum ⁴³⁾	120	820
	220	980
Steel drum ⁴³⁾	216	980
Standard jerricans according to EN 12712 ⁴³⁾	12, 33 (large cap)	400
	25, 30, 33	500
	60	690
IBC ⁴³⁾	all sizes	1200

⁴³⁾ For suitable adapters, see section Adapters for containers.

Related information[Adapters for containers](#)[Square tank, 100 litres](#)[Cylindrical tanks](#)**Technical data**

Max. flow rate [l/h]	Max. immersion depth ⁴⁴⁾ [mm]	Material			Product number	
		Body	Gasket	Ball	RSL without level indication	RSL with level indication
60	400	PE	FKM, EPDM	Ceramic	98070978	98071074
			PTFE	Ceramic	98070979	98071075
		PVDF	FKM, EPDM	Ceramic	98070980	98071076
			PTFE	Ceramic	98070981	98071077
	500	PE	FKM, EPDM	Ceramic	98070990	98071086
			PTFE	Ceramic	98070991	98071087
		PVDF	FKM, EPDM	Ceramic	98070992	98071088
			PTFE	Ceramic	98070993	98071089
	570	PE	FKM, EPDM	Ceramic	98071002	98071098
			PTFE	Ceramic	98071003	98071099
		PVDF	FKM, EPDM	Ceramic	98071004	98071100
			PTFE	Ceramic	98071005	98071101
	690	PE	FKM, EPDM	Ceramic	98071014	98071110
			PTFE	Ceramic	98071015	98071111
		PVDF	FKM, EPDM	Ceramic	98071016	98071112
			PTFE	Ceramic	98071017	98071113
	820	PE	FKM, EPDM	Ceramic	98071026	98071122
			PTFE	Ceramic	98071027	98071123
		PVDF	FKM, EPDM	Ceramic	98071028	98071124
			PTFE	Ceramic	98071029	98071125
	980	PE	FKM, EPDM	Ceramic	98071038	98071134
			PTFE	Ceramic	98071039	98071135
		PVDF	FKM, EPDM	Ceramic	98071040	98071136
			PTFE	Ceramic	98071041	98071137
	1100	PE	FKM, EPDM	Ceramic	98071050	98071146
			PTFE	Ceramic	98071051	98071147
		PVDF	FKM, EPDM	Ceramic	98071052	98071148
			PTFE	Ceramic	98071053	98071149
	1200	PE	FKM, EPDM	Ceramic	98071062	98071158
			PTFE	Ceramic	98071063	98071159
		PVDF	FKM, EPDM	Ceramic	98071064	98071160
			PTFE	Ceramic	98071065	98071161

44) Minimum immersion depth for all sizes: approx. 140 mm

Accessories for suction lances and foot valves with level indication

Adapters for containers




These adapters allow the installation of standard rigid suction lances (G 2" thread) and foot valves with level indication (PE cap) on different types of containers.



TM048506

Adapters for containers

Technical data

Adapter type	For container type	Remark	Product number
	Counter nut for tanks without threaded opening, for example, 100-litre square tank or 1000-litre cylindrical tank	PVC, grey	98071170
	Containers with 2" NPT threaded opening	PVC, grey	98156690
	Drums with S 70 x 6 coarse thread (MAUSER 2")	PE, blue	98071171
	Drums with S 56 x 4 coarse thread (TriSure®)	PE, orange	98071172
	Jerricans with small opening (approx. Ø36), according to EN 12713	PE, green	98071173
	Jerricans with medium-sized opening (approx. Ø45), according to EN 12713	PE, yellow	98071174
	Jerricans with large opening (approx. Ø57), according to EN 12713	PE, brown	98071175
	US containers with bung hole of 63 mm (ASTM International)	PE, white	98071176
	IBC (Intermediate Bulk Container) with opening of Ø150 mm, S 160 x 7	PE, black	98071177

Emission protection kits

Gas emitted by liquid in a container can cause bad odour and corrosion. Emission protection kits help avoid such problems.


Rigid suction lances can be retrofitted with emission protection kits.

Two variants are available:

- Emission protection kit with snifting valve: no gas can escape from the container, but air can be drawn in.
- Emission protection kit for use with filter: gas can escape from the container and air can be drawn in. The kit can be connected to a filter by a 4/6 mm hose.

Emission protection kits include:

- gasket for the tank adapter
- snifting valve or hose nipple 4/6 mm (hose is not included)
- gasket for the cable outlet.



TM069068

Emission protection kit

Pos.	Description
1	Gasket for the cable outlet
2	Snifting valve
3	Gasket for the tank adapter

Order data

Variant	Product number
Emission protection kit with snifting valve	98071178
Emission protection kit for use with filter	98071179

M 12-plug-to-flat-plug adapter

The adapter allows for connecting rigid suction lances or foot valves with level indication to pumps with a level input designed for flat plugs, for example, the DMX and the DMH with AR control unit.

Order data


Description	Product number
M 12-plug-to-flat-plug adapter	96635010

Injection units

Injection units connect the dosing line with the process line. They ensure a minimum counterpressure of 0.7 bar and avoid backflow of the dosing liquid.

In general, they include the following:

- injection pipe (PP, PVC and PVDF versions can be shortened)
- spring-loaded non-return valve with Tantal spring
- hose connection set: 4/6 mm, 6/9 mm, 6/12 mm and 9/12 mm
- pipe connection set: threaded, Rp 1/4", internal thread (stainless steel).




TM087076

Standard injection unit


Standard injection units

Dimensions



TM069845

Standard injection unit, PP, PVC, and PVDF version



TM069846

Standard injection unit, stainless-steel version


Material	C	L1 in [mm]	L2 in [mm]	D
PVC	1/2" NPT (G 1/2)	4 / 12 (100 / 300)	1.8 (47)	5/8" NPT (G 5/8)
PP, PVDF	1/2" NPT (G 1/2)	4 (100)	1.8 (47)	5/8" NPT (G 5/8)
Stainless steel	1/2" NPT (G 1/2)	1 (27)	1.9 (50)	5/8" NPT (G 5/8)

Technical data

Max. flow rate [l/h]	Max. pressure [bar]	Material			Dimensions		Product number
		Body	Gasket	Ball	L 1 [mm]	L 2 [mm]	
60	16	PP	FKM	Ceramic	100	47	95730904
			EPDM	Ceramic	100	47	95730908
		PVC	FKM	Ceramic	100	47	95730912
			EPDM	Ceramic	100	47	95730916
			PTFE	Ceramic	100	47	95730920
		PVDF	FKM	Ceramic	100	47	95730924
			EPDM	Ceramic	100	47	95730928
			PTFE	Ceramic	100	47	95730932
	100	Stainless steel	PTFE	Stainless steel	27	50	95730936
	16	PVC	FKM	Ceramic	300	47	95730940
			EPDM	Ceramic	300	47	95730944
			PTFE	Ceramic	300	47	95730948

Injection units with lip valve

Injection units with lip valve are typically used for adding sodium hypochlorite solution to water with a high carbonate content. The FKM lip prevents crystallisation and blocking caused by alkali carbonate reactions at the point of injection.

Dimensions

TM069847

Injection unit with lip valve

C	L1 in [mm]	L2 in [mm]	D
G 1/2	55	49	G 5/8

Technical data

Max. flow rate [l/h]	Max. pressure [bar]	Material			Dimensions		Product number
		Body	Gasket	Ball	L 1 [mm]	L 2 [mm]	
60	16	PVC	FKM	Ceramic	55	59	95730964

Injection units with ball valve


Injection units with ball valve are used for applications where the injection point must be closable. The ball valve is placed between the injection pipe and the spring-loaded non-return valve.

- The dosing line can be completely disconnected from the process.
- The non-return valve can be dismantled and cleaned without stopping the process and emptying the process line.



TM068429

Dimensions



TM068448

Injection unit with ball valve

	C	L1 in [mm]	L2 in [mm]	D
PVC	G 1/2	100	183	G 5/8
Stainless steel	G 1/2	27	138	G 5/8


Technical data

Max. flow rate [l/h]	Max. pressure [bar]	Material			Dimensions		Product number
		Body	Gasket	Ball	L 1 [mm]	L 2 [mm]	
60	16	PVC	FKM	Ceramic	100	183	95730952
			EPDM	Ceramic	100	183	95730956
	64	Stainless steel	PTFE	Stainless steel	27	138	95730960

Injection units with removable injection pipe

Injection units with removable injection pipe are used where regular cleaning of the injection pipe is required. The injection pipe can be removed from the process line without stopping the process water flow. The injection point can be closed with the integrated ball valve. The immersion depth of the injection pipe can be adjusted.

Dimensions



TM068449

Injection unit with removable injection pipe

C	L1 in [mm]	L2 in [mm]	D
G 1/2	185	280	G 5/8


Technical data

Max. flow rate [l/h]	Max. pressure [bar]	Material			Dimensions		Product number
		Body	Gasket	Ball	L 1 [mm]	L 2 [mm]	
60	10	PVC	FKM	Ceramic	185	280	95730968
			EPDM	Ceramic	185	280	95730972

Hot-injection units with ball valve

Hot-injection units with ball valve can be used for direct injection of the dosing medium into processes with a high process water temperature of up to 120 °C. Hot-injection units have a stainless-steel injection pipe and a bendable stainless-steel cooling pipe of 1 metre. The stainless-steel ball valve is installed between the injection pipe and the cooling pipe. The cooling pipe separates the hot parts from the non-return valve and the dosing line.

Dimensions



TM069850

Hot-injection unit with ball valve

C	L1 in [mm]	L2 in [mm]	D
G 1/2	27	1158	G 5/8

Technical data

Max. flow rate [l/h]	Max. pressure [bar]	Material			Dimensions		Product number
		Body	Gasket	Ball	L 1 [mm]	L 2 [mm]	
60	16	PVDF	PTFE	Ceramic	27	1158	95730976
	64	Stainless steel	PTFE	Stainless steel	27	1158	95730980

Multi-function valves, pressure relief valves, pressure loading valves

Multi-function valves combine the functions of pressure relief valves and pressure loading valves. In addition, they allow de-aeration of the pump and emptying of the outlet line for maintenance.

Pressure relief valves protect the pump and the outlet-side installations against excessive pressure. All pressurised dosing installations should include a pressure relief valve.

Pressure loading valves maintain a certain counterpressure for the dosing pump.

They are used in the following cases:

- too low counterpressure or no counterpressure at all
- fluctuating system pressure with outlet-side pulsation damper
- to prevent syphoning when the inlet pressure is higher than the counterpressure.



TM086554


Multi-function valve, pressure relief valve, pressure loading valve

Multi-function valves

A multi-function valve is mounted directly on the pump outlet side. The top connection is for the outlet line, the side connection leads the relief liquid back into the tank.

- Loading pressure, adjustable from 1 to 4 bar, is factory-set to 3 bar.
- Relief pressure, adjustable from 7 to 16 bar, is factory-set to 10 bar or 16 bar.
- Maximum operating pressure: 16 bar.
- Hose connection set: 4/6 mm, 6/9 mm, 6/12 mm, and 9/12 mm.

Dimensions



Multi-function valve

TM089769

L1 in (mm)	L2 in (mm)	H1 in (mm)	H2 in (mm)	H3 in (mm)	Ø D in (mm)	G
139	45	92	47	45	60	G 5/8

Technical data


Max. flow rate [l/h]	Material				Product number	
	Body	Connections	Gasket	Diaphragm	Relief pressure 10 bar	Relief pressure 16 bar
60	PVDF	PP	FKM	PTFE	95704585	95730821
			EPDM	PTFE	95704591	95730822
		PVC	FKM	PTFE	95730807	95730823
			EPDM	PTFE	95730808	95730824
			PTFE	PTFE	95730809	95730825
		PVDF	FKM	PTFE	95730810	95730826
			EPDM	PTFE	95730811	95730827
			PTFE	PTFE	95730812	95730828

Pressure relief valves PRV

Pressure relief valves are installed in the outlet line near the pump, using the 2 in-line connections. The side connection leads the relief liquid back into the tank.

- Relief pressure, adjustable from 5 to 10 bar, is factory-set to 10 bar.
- Relief pressure, adjustable from 7 to 16 bar, is factory-set to 16 bar.
- Maximum operating pressure: 16 bar.
- Hose connection set: 4/6 mm, 6/9 mm, 6/12 mm, and 9/12 mm.
- Pipe connection set: threaded, Rp 1/4", internal thread (stainless steel).

Dimensions



TM087164

Pressure relief valve

Material	L1 in (mm)	L2 in (mm)	L3 in (mm)	H1 in (mm)	H2 in (mm)	D1 in (mm)	Ø D2 in (mm)	G
PP / PVC / PVDF	82	21	48	96	68	78	4.5	G5/8
Stainless steel	82	22	20	40	68	-	-	-

Technical data


Max. flow rate [l/h]	Material			Product number	
	Diaphragm	Body and connections	Gasket	Relief pressure 10 bar	Relief pressure 16 bar
60	PTFE	PP	FKM / EPDM	95730757	95730773
		PVC	FKM / EPDM	95730758	95730774
			PTFE	95730759	95730775
		PVDF	FKM / EPDM	95730760	95730776
			PTFE	95730761	95730777
		Stainless steel	No gaskets	95730771	95730783

Pressure loading valves PLV

Pressure loading valves are installed in the outlet line after the pressure relief valve, and after the pulsation damper, if fitted.

- Loading pressure, adjustable from 1 to 5 bar, is factory-set to 3 bar.
- Maximum operating pressure: 16 bar.
- Hose connection set: 4/6 mm, 6/9 mm, 6/12 mm, and 9/12 mm.
- Pipe connection set: threaded, Rp 1/4", internal thread (stainless steel).

Dimensions



Pressure loading valve

Material	L1 in (mm)	L2 in (mm)	H1 in (mm)	H2 in (mm)	D1 in (mm)	Ø D2 in (mm)	G
PP / PVC / PVDF	82	21	96	68	78	4.5	G5/8
Stainless steel	82	22	40	68	-	-	-

Technical data

Max. flow rate [l/h]	Material			Product number
	Diaphragm	Body and connections	Gasket	
60	PTFE	PP	FKM / EPDM	95730741
		PVC	FKM / EPDM	95730742
			PTFE	95730743
		PVDF	FKM / EPDM	95730744
			PTFE	95730745
		Stainless steel	No gaskets	95730751


Pressure valves

Pressure valves provide a constant counterpressure of 3 bar. They are particularly required for the DDA-FC or DDA-FCM pumps at very small flow rates.

Pressure valves are installed either directly on the pump outlet side, or on the pressure relief valve.

- Loading pressure: 3 bar, not adjustable.
- Maximum system pressure: 16 bar.
- Spring material: Alloy C-4 (NiMo16CrTi, material number 2.4610).
- No connections included.

Dimensions



TM069796

Pressure valve

A in (mm)	B
87	G 5/8

Technical data

Max. flow rate [l/h]	Material			Product number
	Ball	Body	Gaskets	
60	Ceramic	PP	FKM	95730325
			EPDM	95730326
		PVC	FKM	95730327
			EPDM	95730328
			PTFE	95730329
		PVDF	FKM	95730330
			EPDM	95730331
			PTFE	95730332
	Stainless steel	Stainless steel	PTFE	95730333

Pump connection kits and inlay kits

Retrofit pump connection kits and inlay kits are available for the integration of Grundfos standard dosing pumps into installations with various sizes of hoses or pipes.

A pump connection kit includes the following:

- 1 set of inlays
- 1 union nut.

The inlay kits are used for connecting pumps and accessories to pipes or hoses that differ from Grundfos standard sizes.

An inlay kit includes the following:

- 2 sets of inlays.



TM048294



TM048295

Left: pump connection kit; right: inlay kit

Technical data

Connection type	Size	Material	Product number	
			Connection kit	Inlay kit
Hose (cone and ring)	4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm	PP	97691902	-
		PVC	97691903	-
		PVDF	97691904	-
	0.17" x 1/4", 1/4" x 3/8", 3/8" x 1/2"	PP	97691905	-
		PVC	97691906	-
		PVDF	97691907	-

Connection type	Size	Material	Product number	
			Connection kit	Inlay kit
Hose (cone and ring)	4/6 mm, or 0.17" x 1/4"	PP	97702474	95730984
		PVC	97702485	95730720
		PVDF	97702495	95730729
	4/9 mm	PP	98153922	98153977
		PVC	98153944	98154006
		PVDF	98153949	98154029
	5/8 mm	PP	97702475	95730711
		PVC	97702486	95730721
		PVDF	97702496	95730730
	6/8 mm	PP	97702476	95730712
		PVC	97702487	95730722
		PVDF	97702497	95730731
	6/9 mm	PP	97702477	95730713
		PVC	97702488	95730723
		PVDF	97702498	95730732
	6/12 mm	PP	97702478	95730714
		PVC	97702489	95730724
		PVDF	97702499	95730733
	9/12 mm	PP	97702479	95730715
		PVC	97702490	95730725
		PVDF	97702500	95730734
	1/4" x 3/8	PP	97702482	95730718
		PVC	97702492	95730727
		PVDF	97702503	95730737
	3/8" x 1/2"	PP	97702483	95730719
		PVC	97702493	95730728
		PVDF	97702504	95730738
Hose (cutting ring type)	1/8" x 1/4"	PP	97702481	95730717
		PVDF	97702502	95730736
Pipe welding	External diameter 16 mm	PP	97702480	95730716
		PVDF	97702501	95730735
Pipe cementing	Internal diameter 12 mm	PVC	97702491	95730726
	Internal diameter 1/2"	PVC	92502545	-
	Internal diameter 1/2"	CPVC	93124554	-
Pipe, external thread	1/2" NPT	PP	97702484	-
		PVC	97702494	-
		PVDF	97702505	-
		Stainless steel	97702508	-
Pipe, internal thread	Rp 1/4"	Stainless steel	97702472	95730739
	1/4" NPT	Stainless steel	97702473	95730740
Pipe (cutting ring type)	4/6 mm	Stainless steel	97702506	-
	8/10 mm	Stainless steel	97702507	-

Adapters








Threaded adapters

Threaded adapters are used for converting between different threaded connection sizes.

A threaded adapter kit includes the following:

- 1 adapter
- 1 O-ring.


Technical data

Type	Threaded connection size		Material		Product number
	Internal thread	External thread	Body	Gaskets	
	G 3/8"	G 5/8"	PP	FKM / EPDM	95730407
			PVC	FKM / EPDM	95730408
				PTFE	95730409
			PVDF	FKM / EPDM	95730410
	G 5/8"	G 3/8"	PP	FKM / EPDM	95730412
			PVC	FKM / EPDM	95730413
				PTFE	95730414
			PVDF	FKM / EPDM	95730415
	G 5/8"	G 3/4"	PP	FKM / EPDM	95730417
			PVC	FKM / EPDM	95730418
				PTFE	95730419
			PVDF	FKM / EPDM	95730420
	G 5/8"	G 1 1/4"	PP	FKM / EPDM	95730422
			PVC	FKM / EPDM	95730423
				PTFE	95730424
			PVDF	FKM / EPDM	95730425
	G 5/8"	M 20 x 1.5	PP	FKM / EPDM	95730427
			PVC	FKM / EPDM	95730428
				PTFE	95730429
			PVDF	FKM / EPDM	95730430
	G 5/8"	M 30 x 3.5		FKM / EPDM	98154048
			PVDF	PTFE	98154054
	G 1 1/4"	G 5/8"	PP	FKM / EPDM	95730432
			PVC	FKM / EPDM	95730433
				PTFE	95730434
			PVDF	FKM / EPDM	95730435
				PTFE	95730436

Union nut adapters




Union nut adapters consist of a rigid pipe with union nuts on both ends. They have neither gaskets nor glued or welded connections.

Technical data

Type	Threaded connection size		Material	Product number
	Internal thread	Internal thread	Body	
	G 5/8"	G 5/8"	PVC	95730437
			PP	95730438
			PVDF	95730439



Hose-to-hose and hose-to-pipe adapters

Technical data

Type	Description	Connections		Material		Product number
		Side 1	Side 2	Body and connections	Gaskets	
	Valve body with two external threads G 5/8"	For hoses 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm		PP	FKM / EPDM	95730367
				PVC	FKM / EPDM	95730368
					PTFE	95730369
				PVDF	FKM / EPDM	95730370
					PTFE	95730371
		Without		PP	FKM / EPDM	95730356
				PVC	FKM / EPDM	95730357
					PTFE	95730358
				PVDF	FKM / EPDM	95730359
					PTFE	95730360
	Pipe cementing end on one side, external thread G 5/8" on the other side	Without	Threaded Rp 1/4	Stainless steel	PTFE	95730361
		For hoses 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm	Internal Ø12 mm	PVC	FKM / EPDM	95730378
					PTFE	95730379
		Without	Internal Ø12 mm	PVC	FKM / EPDM	95730365
					PTFE	95730366
		Without	Internal Ø12 mm	PVC	FKM / EPDM	95730365
	Pipe welding end on one side, external thread G 5/8" on the other side	For hoses 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm	External Ø16 mm	PP	FKM / EPDM	95730377
				PVDF	FKM / EPDM	95730380
					PTFE	95730381
		Without	External Ø16 mm	PP	FKM / EPDM	95730362
				PVDF	FKM / EPDM	95730363
					PTFE	95730364
		Without	External Ø16 mm	PVDF	FKM / EPDM	95730363
					PTFE	95730364

T-pieces

Technical data

Type	Description	Connections			Material		Product number
		Bottom	Top	Side	Body and connections	Gaskets	
	Three external threads G 5/8"	For hoses 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm			PP	FKM / EPDM	95730387
					PVC	FKM / EPDM	95730388
						PTFE	95730389
					PVDF	FKM / EPDM	95730390
						PTFE	95730391
					PP	FKM / EPDM	95730346
		Without			PVC	FKM / EPDM	95730347
						PTFE	95730348
					PVDF	FKM / EPDM	95730349
						PTFE	95730350
	Two male threads G 5/8", one internal connection with union nut	Union nut G 5/8"	Without	For hoses 4/6 mm, 6/9 mm, 6/12 mm, 9/12 mm	PP	FKM / EPDM	95730397
					PVC	FKM / EPDM	95730398
						PTFE	95730399
					PVDF	FKM / EPDM	95730400
						PTFE	95730401
				Without	PP	FKM / EPDM	95730351
					PVC	FKM / EPDM	95730352
						PTFE	95730353
					PVDF	FKM / EPDM	95730354
						PTFE	95730355

Dosing tanks

Square tank, 100 litres

The closed square tank has a screw cap and a mounting platform for one pump or two pumps in parallel.

The pump mounting platform is higher than the screw cap to protect pumps and connections when filling chemicals into the tank.

Characteristics of the tank:

- Tank material: MDPE
- weight: 15 kg
- wall thickness: 4 mm
- liquid temperature: -20 °C to +45 °C.

SMART Digital S pumps can be fitted directly on the mounting platform by brass inserts moulded into the platform. For other pumps, a bracket is required.

The square tank is prepared for a G 3/4" drain valve.

When using a rigid suction lance in the tank, choose the counter nut for fixing, see section Adapters for containers.




TM048307

Square tank

Related information

[Adapters for containers](#)

Dimensions



Square tank, dimensions

H1 [mm]	H2 [mm]	D1 [mm]	A [mm]	B [mm]	L1 [mm]	W1 [mm]	W2 [mm]	S1
670	540	Ø152	500	500	98	137	192	M 5

Order data

Tank volume [l]	Product number
100	96489271

TM069772

Cylindrical tanks

Dosing tanks are intended for storing and dosing liquids. Different tank accessories can be mounted directly to the tank. Cylindrical tanks are available in transparent or black. They have a litre scale and a black screw cap.

Characteristics of the tank:

- Tank volume: 40-1000 l
- tank material: LLDPE, UV-stabilised
- liquid temperature: -20 °C to +45 °C.

All cylindrical tanks are prepared for a G 3/4 opening for a drain valve, and have a screw plug (PE or EPDM).

The cylindrical tanks with volumes of 60, 100, 200, 300 and 500 litres additionally include the following:

- threaded M 6 inserts for the direct assembly of a dosing pump
- G 2 opening for a rigid suction lance or a foot valve, closed with a screw plug
- threaded M 6 inserts at the bottom part for floor mounting with a set of floor-mounting brackets
- flange for an electric stirrer with threaded inserts.

The cylindrical tanks with volumes of 60, 100, 200, 300, 500 and 1000 litres can optionally be prepared for direct assembly of an electric stirrer:


- with opening for electric stirrer (60-500 l)
- with opening and reinforced beam for holding an electric stirrer (1000 l).



TM048468

Cylindrical tank, 60 litres


Dimensions of cylindrical tank, 40 litres



TM069773

H1 [mm]	H2 [mm]	H3 [mm]	D1 [mm]	D2 [mm]	C1
420	350	45	Ø160	Ø420	Rp 3/4


Dimensions of cylindrical tank, 60 and 100 litres



TM069774

Tank volume: 60 l				Tank volume: 100 l			
H1 [mm]	H2 [mm]	H1 [mm]	H2 [mm]	H1 [mm]	H2 [mm]	H1 [mm]	H2 [mm]
590	545	840	795				
H3 [mm]	H4 [mm]	H5 [mm]	D1 [mm]	D2 [mm]	D3 [mm]	D4 [mm]	D5 [mm]
50	40	150	Ø160	Ø460	Ø95	Ø35	Ø130
C1	C2	L1 [mm]	L2 [mm]	W1 [mm]	S2	S3	S4
G 3/4	G 2	159	174	105	M 6 × 9	M 8 × 12	M 6 × 9


Dimensions of cylindrical tank, 200 and 300 litres



TM086236

Tank volume: 200 l				Tank volume: 300 l			
H1 [mm]	H2 [mm]	H1 [mm]	H2 [mm]	H1 [mm]	H2 [mm]	H1 [mm]	H2 [mm]
810	770	1080	1040				
H3 [mm]	H4 [mm]	H5 [mm]	D1 [mm]	D2 [mm]	D3 [mm]	D4 [mm]	D5 [mm]
50	40	150	Ø160	Ø670	Ø115	Ø35	Ø130
C1 [mm]	C2	L1 [mm]	L2 [mm]	W1 [mm]	S2	S3	S4
G 3/4	G 2	159	174	105	M 6 × 9	M 8 × 12	M 6 × 9


Dimensions of cylindrical tank, 500 litres



TM069776

H1 [mm]	H2 [mm]	H3 [mm]	H4 [mm]	H5 [mm]	D1 [mm]	D2 [mm]	D3 [mm]	D4 [mm]	D5 [mm]
1235	1175	50	40	150	Ø160	Ø790	Ø115	Ø35	Ø130
C1	C2	L1 [mm]	L2 [mm]	W1 [mm]	S2	S3	S4		
G 3/4	G 2	159	174	105	M 6 × 9	M 8 × 12	M 6 × 9		

Dimensions of cylindrical tank, 1000 litres



TM069777

H1 [mm]	H2 [mm]	H3 [mm]	D1 [mm]	D2 [mm]	C1
1260	1150	50	Ø160	Ø1080	G 3/4

Technical data

Tank volume [l]	Prepared for direct assembly of an electric stirrer	Weight [kg]	Product number	
			Transparent	Black
40	-	3.4	96688081	95701166
60	-	5.5	98148805	98149053
	Yes	5.5	98150038	98150040
100	-	7.5	98149057	98149082
	Yes	7.5	98150051	98150052
200	-	11.5	98149215	98149224
	Yes	11.5	98150053	98150054
300	-	13	98149245	98149252
	Yes	13	98150055	98150056
500	-	28	98149266	98149269
	Yes	28	98150057	98150058
1000	-	40	96688086	95706305
	Yes	48	98173675	98173752

Related information

[Accessories for dosing tanks](#)

Collecting tray

The collecting tray is available in several sizes to suit the respective dosing tank size. It collects chemicals that might leak out of the tank, and protects the environment.

- Material: PE.
- Colour: transparent.




TM048316

Collecting tray

For tank size [l]	Volume [l]	Dimensions (diameter x height) [mm]	Product number
60	80	500 x 545	96726831
100	120	500 x 700	96726832
200	210	770 x 595	98150059
300	400	770 x 960	96726834
500	500	860 x 980	95701272
1000	1000	1150 x 1080	96726836

Accessories for dosing tanks



TM069778

Dissolving hopper, dimensions

A [mm]	B [mm]	C [mm]	D [mm]	E [mm]
Ø270	Ø140	283	Ø70	120




TM048477

*Handheld mixer***Technical data**

Description	Specifications	Material	Product number
Drain valve for installation in the threaded sleeve of the dosing tank	Dosing tank connection G 3/4"	PVC	96689132
Ventilation valve	Spring-loaded, opening pressure 0.05 bar	PVC / FKM / glass	96694401
Dissolving hopper for washing powders into the dosing tank	Dosing tank connection: DN 40 through-bolt Water connection: G 5/4", with union nut and inlay for PVC pipe (cementing diameter 25 mm)	PVC	96726979
Handheld mixer for use in dosing tanks	Shaft length 1200 mm, length can be adapted to the corresponding dosing tank with DN 15 through-bolt for connection at the dosing tank	PE	98133793
Set of floor-mounting brackets	4 floor-mounting brackets with fixing screws		98149921
Set of screws for mounting a pump on a 100-litre square tank	For pump types DDA, DDC, DDE	Stainless steel	95730862
Set of screws for mounting a pump on a 60-, 100-, 200-, 300-, or a 500-litre cylindrical tank	For pump types DDA, DDC, DDE, DDI, DMX model 221	Stainless steel	98159495
Set of screws for mounting a pump on a 40-litre or a 1000-litre cylindrical tank	For pump types DDA, DDC, DDE, DDI, DMX model 221	PP	95730864



TM087077

Drain valve for installation in the threaded sleeve of the dosing tank*Ventilation valve*

TM087078

TM087079

Set of floor-mounting brackets

Water meter

The in-line water meter with potential-free pulse signal is suitable for use in flow-proportional dosing applications.

- Qn 1.5 and Qn 2.5 meters are of the multi-jet, dry dial type, for cold water up to 30 °C, or hot water up to 90 °C.
- Qn 15 meters and up are of the helical vane type, for cold water up to 50 °C, or hot water up to 120 °C.
- Max. pressure: 16 bar.

If the water meter is connected directly to the pump pulse input, use a control plug (PN 96698715).

- Qn 1.5 to Qn 15 meters are threaded.
- Qn 40 to Qn 150 meters are flanged.
- Cable length: 3 m.



TM048317

Water meter

Qn [m ³ /h]	Pulse rate [l/pulse]	Maximum short- period capacity [m ³ /h]	Max. pressure [bar]	Transitional capacity with error ± 2 % [l/h]	Minimum capacity with error ± 5 % [l/h]	Product number			
						Maximum water temperature			
						30 °C	50 °C	90 °C	120 °C
1.5 ⁴⁵⁾	1	3	16	120	50	96446846	-	96446897	-
2.5 ⁴⁵⁾	2.5	5	16	200	70	96446847	-	96446898	-
15 ⁴⁵⁾	10	30	16	3000	450	-	96446848	-	96446899
1.5 ⁴⁵⁾	0.25	3	16	120	50	96482640	-	96482643	-
2.5 ⁴⁵⁾	0.25	5	16	200	70	96482641	-	96482644	-
15 ⁴⁵⁾	2.5	30	16	3000	450	96482642	-	96482645	-
40 ⁴⁶⁾	100	80	10	4000	700	-	96446849	-	96446900
60 ⁴⁶⁾	25	120	10	6000	1200	-	96446850	-	96446901
150 ⁴⁶⁾	100	300	10	12000	3000	-	96446851	-	96446902

⁴⁵⁾ Maximum load, Reed contact: 30 VAC/VDC, 0.2 A

⁴⁶⁾ Maximum load, Namur contact: 8-12 VDC, 1 kOhm (requires external power supply)

Dimensions

Size	Connections	Installation kit connection	Port-to-port length [mm]	Port-to-port length incl. kit [mm]
Threaded connection				
Qn 1.5	G 3/4"	G 1/2"	165	245
Qn 2.5	G 1"	G 3/4"	190	288
Qn 15	G 2.5	G 2"	300	438
Flanged connection				
Qn 40	DN 80		225	-
Qn 60	DN 100		250	-
Qn 150	DN 150		300	-

9. Pumped liquids

The resistance table below is intended as a general guide for material resistance (at room temperature), and does not replace testing of the chemicals and pump materials under specific working conditions.

The data shown are based on information from various sources available, but many factors, such as purity, temperature, abrasive particles, may affect the chemical resistance of a given material.

Some of the liquids in this table may be toxic, corrosive or hazardous. Be careful when handling these liquids.

● = Resistant

○ = Limitedly resistant

- = Not resistant

Pumped liquid (20 °C)			Material								
Description	Chemical formula	Concentration %	Dosing head			Gasket			Ball		PE (Accessories)
			PP	PVDF	SS 1.4435	PVC	FKM	EPDM	PTFE	Ceramic	
Acetic acid	CH ₃ COOH	25	●	●	●	●	-	●	●	●	●
		60	●	●	●	●	-	●	●	●	●
		85	●	●	○	-	-	-	●	●	-
Aluminium chloride	AlCl ₃	40	●	●	-	●	●	●	●	●	●
Aluminium sulphate	Al ₂ (SO ₄) ₃	60	●	●	●	●	●	●	●	●	●
Ammonia, aqueous	NH ₄ OH	28	●	-	●	●	-	●	●	●	●
Calcium hydroxide ⁴⁷⁾	Ca(OH) ₂		●	●	●	●	●	●	●	●	●
Calcium hypochlorite	Ca(OCl) ₂	20	○	●	-	●	●	●	●	●	●
Chlorine dioxide	ClO ₂	3	-	●	-	●	●	-	●	●	-
Chromic acid	H ₂ CrO ₄	10	●	●	●	●	●	●	●	●	●
		30	-	●	-	●	●	○	●	●	●
		50	-	●	-	●	●	-	●	●	●
Copper sulphate	CuSO ₄	30	●	●	●	●	●	●	●	●	●
Ferric chloride ⁴⁸⁾	FeCl ₃	60	●	●	-	●	●	●	●	●	●
Ferric sulphate ⁴⁸⁾	Fe ₂ (SO ₄) ₃	60	●	●	○	●	●	●	●	●	●
Ferrous chloride	FeCl ₂	40	●	●	-	●	●	●	●	●	●
Ferrous sulphate	FeSO ₄	50	●	●	●	●	●	●	●	●	●
Fluosilicic acid	H ₂ SiF ₆	40	●	●	○	●	-	○	●	●	●
Hydrochloric acid	HCl	< 25	●	●	-	●	●	●	●	●	●
		25-37	●	●	-	●	●	○	●	●	●
Hydrogen peroxide	H ₂ O ₂	30	●	●	●	●	●	●	●	●	●
Nitric acid	HNO ₃	30	●	●	●	●	●	●	●	●	●
		40	○	●	●	●	●	-	●	●	●
		70	-	●	●	-	●	-	●	●	○
Peracetic acid	CH ₃ COOOH	5-15	○	●	○	○	-	-	●	●	○
Potassium hydroxide	KOH	50	●	-	●	●	-	●	●	●	●
Potassium permanganate	KMnO ₄	10	●	●	●	●	○	●	●	●	●
Sodium chlorate	NaClO ₃	30	●	●	●	●	●	●	●	●	●
Sodium chloride	NaCl	30	●	●	-	●	●	●	●	●	●
Sodium chlorite	NaClO ₂	20	●	●	-	○	●	●	●	●	●
Sodium hydroxide	NaOH	30	●	●	●	●	○	●	●	●	●
		50	●	●	●	●	-	●	●	●	●
Sodium hypochlorite (commercial)	NaClO	12-15	-	●	-	●	●	●	●	●	●
Sodium hypochlorite (produced by electrolysis system)	NaClO	0,8	-	●	-	-	●	●	●	●	○
Sodium sulphide	Na ₂ S	30	●	●	●	●	●	●	●	●	●
Sodium sulphite	Na ₂ SO ₃	20	●	●	●	●	●	●	●	●	●
Sodium thiosulfate	Na ₂ S ₂ O ₃	10	●	●	●	●	●	●	●	●	●
Sulphurous acid	H ₂ SO ₃	6	●	●	●	●	●	●	●	●	●

Pumped liquid (20 °C)			Material							
Description	Chemical formula	Concentration %	Dosing head			Gasket			Ball	PE (Accessories)
			PP	PVDF	SS 1.4435	PVC	FKM	EPDM	PTFE	
Sulphuric acid ⁴⁹⁾	H ₂ SO ₄	< 80	●	●	-	●	●	○	●	●
		80-96	○	●	-	●	●	-	●	-
		98	-	●	●	-	○	-	●	-

⁴⁷⁾ Once the pump stops, calcium hydroxide sediments rapidly.

⁴⁸⁾ There is risk of crystallisation.

⁴⁹⁾ It reacts violently with water and generates much heat. (The pump should be absolutely dry before dosing Sulphuric acid.)

Further information:

<https://product-selection.grundfos.com/pumped-liquid-guide>

10. Grundfos Product Center

Online search and sizing tool to help you make the right choice.

From the international view, you can select your specific country to view the product range available to you.


International view: <https://product-selection.grundfos.com>

All the information you need in one place

Performance curves, technical specifications, pictures, dimensional drawings, motor curves, wiring diagrams, spare parts, service kits, 3D drawings, documents, system parts. The Product Center displays any recent and saved items - including complete projects - right on the main page.

Downloads

On the product pages, you can download installation and operating instructions, data booklets, service instructions, etc., in PDF format.



When you select your country, you will see the menus below. Note that some menus may not be available depending on the country.

Example: <https://product-selection.grundfos.com/uk>

Pos.	Description
1	Products & services enables you to find products and documents by typing a product number or name into the search field.
2	Applications enables you to choose an application to see how Grundfos can help you design and optimise your system.
3	Products A-Z enables you to look through a list of all the Grundfos products.
4	Categories enables you to look for a product category.
5	Liquids enables you to find pumps designed for aggressive, flammable or other special liquids.
6	Product replacement enables you to find a suitable replacement.
7	WWW enables you to select the country, which changes the language, the available product range and the structure of the website.
8	Sizing enables you to size a product based on your application and operating conditions.

95724709	05.2024
ECM: 1394825	

GRUNDFOS Holding A/S
Poul Due Jensens Vej 7
DK-8850 Bjerringbro
Tel: +45 87 50 14 00
www.grundfos.com

