

# UNILIFT CC, KP, AP and KPC

Submersible drainage and effluent pumps 50/60 Hz

Lifting stations UNO-/DUOLIFT

LIFTAWAY



<b>1. Product overview .....</b>	<b>3</b>
<b>2. Product introduction .....</b>	<b>4</b>
Applications .....	4
Installation .....	4
<b>3. Selection guide .....</b>	<b>5</b>
<b>4. Drainage .....</b>	<b>7</b>
KPC 300 A, KPC 600 A .....	7
KPC 24/7 .....	13
UNILIFT CC .....	18
UNILIFT KP .....	26
UNILIFT AP12 .....	35
<b>5. Effluent and sewage .....</b>	<b>43</b>
UNILIFT AP35 .....	43
UNILIFT AP35B .....	51
UNILIFT AP50 .....	57
UNILIFT AP50B .....	64
UNILIFT APG .....	70
<b>6. Accessories .....</b>	<b>77</b>
Lifting stations UNO-/DUOLIFT .....	79
LIFTAWAY .....	80
Controllers .....	81
<b>7. Grundfos Product Center .....</b>	<b>83</b>

## 1. Product overview

Pump type	Description
KPC	 <p>KPC 300 and 600 is a submersible pump designed for pumping clean, non-aggressive water and slightly dirty (grey) wastewater from sanitary appliances such as washbasins, showers, bathtubs, kitchen sinks, floor drains, washing machines, and dishwashers.</p> <p>KPC 24/7 is a submersible pump designed as a fish pond circulator pump.</p> <p>GR-1016116</p>
UNILIFT CC	 <p>UNILIFT CC is our incredibly robust advanced domestic drainage solution for pumping grey to brackish wastewater from washing machines, baths, sinks, wells, and swimming pools. Special versions can pump wastewater from water softeners with salt content. For a long period of submerged operation, the pump is equipped with a cooling jacket and has a dual-outlet to be mounted to an auto coupling. A self-venting hydraulic allows the pump to start safely after a dry period. The pump is also able to drain flooded basements, for example, down to just 3 mm.</p> <p>GR-1015894</p>
UNILIFT KP	 <p>UNILIFT KP is made entirely of stainless steel and is available for manual and automatic operation. This is the original drainage pump from Grundfos and the only wet runner on the market, which makes it special because it has a liquid-filled rotor and water-lubricated bearings. Even if the shaft seal leaks, the pump will still operate without causing a short-circuit. The pump is used in stationary installation, but it is also optimal for mobile usage. The cooling jacket allows the emerged pump to operate continuously.</p> <p>GR-1032563</p>
UNILIFT AP	 <p>UNILIFT AP series is our solution for higher heads on drainage applications with AP12 (12 mm of free passage) or higher flows for effluent applications which allows bypass of larger particles from 35-50 mm with AP35 and 50, mainly used for rainwater, domestic effluents from sludge treating systems, viaducts, and liquids containing fiber from light industries and laundries.</p> <p>GR-1032570</p> <p>It is used in stationary installation and is also optimal for mobile usage. The cooling jacket allows the emerged pump to operate continuously. It is available with a float switch for automatic start/stop or without a float switch to be operated by an external controller or manual.</p>
UNILIFT APB	 <p>UNILIFT AP Basic Series is our solution with higher heads on wastewater applications with AP35B and a free passage of 35 mm for drainage, greywater-like treated water from grease separators, and/or higher flows for effluent applications which allows bypass of larger particles.</p> <p>The same application can also be covered by the AP50B with 50 mm free passage plus the usage to discharge blackwater from toilets. It is approved according to EN12050-1 for use in lifting stations containing fecal matter. AP Basic is used in stationary installation with auto-coupling systems or base stand and is also optimal for mobile usage. It is available with a float switch for automatic start/stop or without a float switch to be operated by an external controller or manual.</p> <p>GR-1032568</p>
UNILIFT APG	 <p>The Grundfos UNILIFT APG pump is a single-stage submersible pump designed for pumping domestic wastewater. The pump is equipped with a grinder system that grinds destructible solids into small pieces to lead them through pipes with a relatively small diameter. UNILIFT APG pumps are ideal for use in sparsely populated areas, where gravity sewage systems are not available. The solution is ideal in, for example, one- or two-family houses, residential building services and areas with large terrain-level differences. The pump is available for two types of installation:</p> <ul style="list-style-type: none"> <li>• submerged installation on auto-coupling systems.</li> <li>• submerged installation, free-standing.</li> </ul> <p>The pump is made of wear-resistant materials, such as cast iron and stainless steel. These materials ensure reliable operation. The surface of the pump is smooth to prevent dirt and impurities from sticking. Four corrosion-resistant screws secure the motor to the pump housing and allow for easy service of the pump.</p> <p>TM081489</p>

## 2. Product introduction

UNILIFT pumps are submersible wastewater pumps used to collect and pump general wastewater types such as:

- drainage
- rainwater collected from surfaces to be guided into ponds, pits, and tanks
- water containing particles and impurities.

They can also be used to discharge greywater or blackwater from sanitary appliances.

### Lifting

Some wastewater needs to be lifted when there is height difference between the location where it is collected and the buildings' drainage system or sewer mains.

### Water transportation

Wastewater can be collected in one location and transported to another, for example, when wastewater collected inside a building must be transported to sewer mains when a free flow drainage system is not in place.

### Backflow protection

When sewer mains are overloaded or blocked, there is a risk of backflow into the basements of connected buildings. Lifting or pumping stations with drainage pumps can be installed to avoid this risk.

## Applications

UNILIFT CC, KP, AP, and KPC are submersible drainage pumps suitable for temporary and permanent free-standing installation. Furthermore, the UNILIFT CC, AP35B, AP50B and APG pumps are suitable for installation on an auto-coupling at the bottom of a collecting tank with guide rails going to the top. The pumps are designed for intermittent operation but can operate continuously if they have a cooling jacket or are fully submerged.

pH values:

- KPC: 4-6
- UNILIFT CC: 4-9
- UNILIFT KP: 4-9
- UNILIFT AP, APB, APG: 4-10.

For permanent installation, level controllers are available.

### Applications for mobile use

Drainage pumps and small effluent pumps are used for portable applications. These include emergencies, for example, flooding events inside and outside buildings, and to pump water or wastewater out of tanks, ponds, or swimming pools.

### Applications for stationary (fixed) installations

Drainage pumps and small effluent pumps are used for fixed, stationary installations:

- on- and under-floor tanks (lifting stations) or simple concrete pump sumps inside the building
- pumping stations and small domestic treatment plants outside the building
- industrial and commercial use.

## Installation

UNILIFT KP, AP12, AP35, AP50 and APG pumps are suitable for free-standing installation. UNILIFT AP35B, AP50B and APG can be installed on an auto-coupling guide rail system, which is available as an accessory.

### 3. Selection guide

This guide helps you select the most suitable UNILIFT product based on wastewater type and application.

Follow the instructions below to determine which product variant is best suited to your needs.

UNILIFT pumps can be used for different types of wastewater:

- drainage
- greywater
- rainwater
- effluent
- blackwater
- domestic sewage

#### Drainage and greywater

Drainage water includes raw, groundwater with small impurities. The same products chosen for this application are also suitable for collecting domestic greywater from appliances such as showers, bathtubs, floor drains, washbasins, kitchen sinks, washing machines, and dishwashers. It is recommended to use submersible pumps with a free passage of 10-12 mm.

#### Effluent and rainwater

Effluent is wastewater with higher volumes that require larger free passage than drainage. This includes greywater from commercial processes such as cleaning or washing with fibers or cooking grease from commercial cooking in canteens and treated by grease separators. These products are also suitable for collecting rainwater from surfaces such as parking lots. It is recommended to use pumps with a free passage of 35 or 50 mm.

#### Domestic sewage and blackwater

Domestic sewage is blackwater collected from households or office buildings. Blackwater is greywater that includes fecal matter and can also include feminine sanitary products. It is recommended to use pumps with a free passage of at least 50 mm, or pumps with an included grinder.

#### 1. Choose the right pump for your wastewater needs.

Wastewater type	Pump	Free passage [mm]	Impeller type
Drainage and greywater	UNILIFT CC	10	Semi-open
	UNILIFT KP	10	Semi-open
	UNILIFT AP12	12	Semi-open
	KPC 300,600 and KPC 24/7	5 / 10	Semi-open
Effluent and rainwater	UNILIFT AP35 and UNILIFT AP35B	35	Vortex
	UNILIFT AP50 and UNILIFT AP50B	50	Vortex
Domestic sewage and blackwater	UNILIFT AP50B	50	Vortex
	UNILIFT APG	-	Vortex

2. Choose the right pump for your application.

Application	UNILIFT pump type								
	CC	KP	AP12	KPC	AP35	AP35B	AP50	AP50B	APG
Non-permanent, light-duty applications (used as a portable pump)	•	•	◦	•	◦	◦	◦	◦	◦
Non-permanent, heavy-duty applications for installers and light industry (used as a portable pump)			•		•	•	•	•	•
Pumping of:									
Water and rainwater in horticulture	•	•	•	•					
Water from rivers and lakes	•	•	•	•	•	•	•	•	•
Rainwater, drainage water, and water from flooding	•	•	•	•	•	•	•	•	•
Water for filling/emptying containers, ponds, tanks, etc.	•	•	•	•	•	•	•	•	•
Effluents from showers, washing machines, and sinks below sewer level	•	•	•	•	•	•	•	•	•
Pool water	•	•	•	•	•	•	•	•	•
Ditch drainage water	•	•	•	•	•	•	•	•	•
Groundwater (lowering applications)	•	•	•	•	•	•	•	•	•
Domestic effluents from septic and sludge-treating systems	◦	•	•	◦	•	•	•	•	•
Liquids containing fibres from light industry, laundries, etc.					•	•	•	•	•
Effluents from viaducts, underpasses, etc.					•	•	•	•	•
Effluents from grease separators					•	•	•	•	•
Domestic wastewater with toilet discharge from pipes and water closets below sewer level, outdoor pump installations							•	•	•

• - Recommended

◦ - Alternative

## 4. Drainage

### KPC 300 A, KPC 600 A



KPC 300 A and 600 A are designed mainly for automatically operated, permanent domestic applications. Thanks to its compact, easy-to-handle design, it can also be used as a portable pump. The integrated level switch allows permanent installation and guarantees automatic pump operation.

The pump is able to handle particles up to 10 mm.

#### Applications

The pump is suitable for the following applications:

- emergencies such as lifting water from tanks or rivers, emptying swimming pools, excavations, and underpasses
- gardening
- pumping rainwater and grey wastewater without fibres
- automatically operated, fixed applications in domestic use, draining basements and garages subject to flooding.

#### Features and benefits of KPC 300 A and KPC 600 A

KPC 300 A and KPC 600 A have many beneficial features:

- KPC is a compact, cost-efficient portable pump
- KPC is a robust and lightweight pump with a mounted handle for easy transport
- built-in thermal motor protection to avoid overheating
- automatic level switch that turns the pump on and off as the water level rises or falls
- cooling jacket
- stainless steel motor.

#### Approvals and markings

##### Approvals



TM075405



98507008\_RCM\_MARK




TM075835

## Construction of UNILIFT KPC

### Pump construction features

Water-resistant technopolymer pump sleeve, impeller and inlet strainer. Stainless steel motor housing, rotor shaft, and screws.

### Materials



Pos.	Description	Material
1	Pump sleeve	Noryl GFN 2
4	Impeller	Noryl GFN 2
29	O-ring	NBR
32	Stop ring	Stainless steel 12E
Motor:		
54	- Motor housing	Stainless steel AISI 304 X5 CrNi 1810
	- Rotor	Stainless steel AISI 304 X5 CrNi 1810
78	Suction disc	Noryl GFN 2
79	Inlet strainer	Noryl GFN 2

### Pump sleeve

KPC has a water-resistant and lightweight technopolymer pump sleeve. The pump can operate partly submerged at intermittent operation and fully submerged when run continuously as the motor is cooled by the pumped media.

### Motor

The motor is a continuous-duty, submersible induction motor. The stator is fitted in an airtight stainless steel motor housing with encased cabling, microswitch, and capacitor. The rotor is mounted on oversized, greased, and sealed-for-life ball bearings selected to guarantee silent running and long life. The pump has built-in thermal current overload protection and a capacitor that is permanently in circuit in the single-phase version.

KPC 300 A:	Supplied as standard with 10 m of H05 RN-F power cable.
KPC 600 A:	Supplied as standard with 10 m of H07 RN-F power cable.

Enclosure class: IP68

Insulation class: F

Standard voltage: 1 x 220-240 V, 50 Hz

### Impeller

KPC has a semi-open technopolymer impeller.

### Inlet strainer

Liquid enters the pump through the holes of the inlet strainer. The holes of the strainer prevent the passage of solids larger than 10 mm.

### Pumped liquids


KPC pumps are designed for pumping drainage, rainwater and grey wastewater without fibres.

The pumps are not suitable for these liquids:

- liquids containing long fibres
- inflammable liquids (such as oil or petrol)
- aggressive liquids.


## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 32 mm and flow of 2 m<sup>3</sup>/h to ensure a self-cleaning velocity of  $v=0,7\text{ m/s}$ . The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve, 4x90° bends and a gate valve are calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements, a calculation is required.



TM057071

## Performance curves KPC 300 A, 600 A 50 Hz



## Product range KPC 300 A 50 Hz

Pump type	Product number	Voltage [V]	Plug type	Float switch type	Cable length [m]	Cable type	Net weight [kg]
KPC 300 A	98851053	1 x 220-240	SCHUKO	Cable guided	10	H05RN-F 3G0.75	4.6
KPC 300 A	98863989 <sup>1)</sup>	1 x 220-240	SCHUKO	Cable guided	10	H05RN-F 3G0.75	4.6
KPC 300 A	98917602	1 x 220-240	UK	Cable guided	10	H05RN-F 3G0.75	4.6

1) Pump produced in Europe.

## Product range KPC 600 A 50 Hz

Pump type	Product number	Voltage [V]	Plug type	Float switch type	Cable length [m]	Cable type	Net weight [kg]
KPC 600 A	98851054	1 x 220-240	SCHUKO	Cable guided	10	H07RN-F 3G1	7.0
KPC 600 A	98864015 <sup>2)</sup>	1 x 220-240	SCHUKO	Cable guided	10	H07RN-F 3G1	7.0
KPC 600 A	98917603	1 x 220-240	UK	Cable guided	10	H07RN-F 3G1	7.0

2) Pump produced in Europe.

## Technical data

### Electrical data

#### KPC 300 A 50 Hz

Pump type	Voltage [V]	P1 [kW]	P2 [kW]	I <sub>1/1</sub> [A]	Speed [rpm]
KPC 300 A	1 x 220-240	0.35	0.22	1.50	2900

#### KPC 600 A 50 Hz

Pump type	Voltage [V]	P1 [kW]	P2 [kW]	I <sub>1/1</sub> [A]	Speed [rpm]
KPC 600 A	1 x 220-240	0.80	0.55	3.40	2900


### Operating conditions

Max. head	10.2 m
Max. flow rate	16 m <sup>3</sup> /h
Liquid temperature range	0-35 °C
Liquid pH range	4-6 pH
Liquid requirements	Grey wastewater without fibres
Max. ambient temperature	40 °C
Max. particle size through the inlet strainer	KPC 300 A 10 mm KPC 600 A 10 mm
Min. water level	KPC 300 A 85 mm KPC 600 A 175 mm
Installation	Permanent or portable in a vertical position
Max. submersion depth	10 m
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

3) IEC 60335-2-41 requires 3 m cable length outside of water.


### Dimensions

#### KPC 300 A




TM028466

Pump type	A [mm]	B [mm]	D [mm]	E [mm]	H [mm]	H1 [mm]	H2 [mm]	Connection [inch]
KPC 300 A	185	140	225	82	275	390	47.5	Rp 1 1/4

**KPC 600 A**


TM028466

Pump type	A [mm]	B [mm]	D [mm]	E [mm]	H [mm]	H1 [mm]	H2 [mm]	Connection [inch]
KPC 600 A	200	160	225	90	376	490	73	Rp 1 1/4

**Installation**

TM029100

Minimum dimension [mm] for the pit for KPC 300 A with automatic float switch



TM029101

Minimum dimension [mm] for the pit for KPC 600 A with automatic float switch

## KPC 24/7



GR-101611

KPC 24/7 is primarily designed for fully submerged long operation in fish ponds, but it can also be used for intermittent operation.

Thanks to its compact, easy-to-handle design, it can also be used as a portable pump.

KPC 24/7 does not come equipped with a float switch. The pump can handle particles up to 10 mm.

### Applications

The pump is suitable for the following applications:

- emergencies such as lifting water from tanks or rivers, emptying swimming pools, fountains, excavations and underpasses
- pumping rainwater and grey wastewater without fibres
- automatically operated, fixed applications in domestic use, draining basements and garages subject to flooding
- permanent installation in a pump pit, or as portable utility pump
- circulating water in ponds.

## Features and benefits of KPC 24/7

KPC 24/7 has many beneficial features:

- KPC is a compact, cost-efficient portable pump
- KPC is a robust and lightweight pump with a mounted handle for easy transport
- built-in thermal motor protection to avoid overheating
- automatic level switch that turns the pump on and off as the water level rises or falls
- cooling jacket
- stainless steel motor
- KPC runs 24/7 when fully submerged.

## Approvals and markings

### Approvals



TM075405



98507008\_RCM\_MARK




TM075835

## Construction of UNILIFT KPC 24/7

### Pump construction features

Water-resistant technopolymer pump sleeve, impeller, and inlet strainer. Stainless steel motor housing, rotor shaft, and screws.

### Materials



Pos.	Description	Materials
1	Pump sleeve	Technopolymer
4	Impeller	Technopolymer
29	O-ring	NBR
32	Stop ring	Stainless steel
Motor:		
54	- Motor housing	Stainless steel AISI 304 X5 CrNi 1810
	- Rotor	Stainless steel AISI 304 X5 CrNi 1810
78	Suction disc	Noryl GFN 2
79	Inlet strainer	Noryl GFN 2

### Pump sleeve

KPC has a water-resistant and lightweight technopolymer pump sleeve. The pump can operate partly submerged at intermittent operation and fully submerged when run continuously as the motor is cooled by the pumped media.

### Motor

The motor is a continuous-duty, submersible induction motor. The stator is fitted in an airtight stainless steel motor housing with encased cabling, microswitch and capacitor. The rotor is mounted on oversized, greased, and sealed-for-life ball bearings selected to guarantee silent running and long life. The pump has built-in thermal current overload protection and a capacitor which is permanently in circuit in the single-phase version.

KPC 24/7

Supplied as standard with 10 m H05 RN-F power cable

Enclosure class: IP68

Insulation class: F

Manufactured according to EN 60335-2-41.

Standard voltage: 1 x 220-240 V, 50 Hz

### Impeller

KPC has a semi-open technopolymer impeller.

### Inlet strainer

Liquid enters the pump through the holes of the inlet strainer. The holes of the strainer prevent the passage of solids larger than 5 mm for KPC 24/7 210 and 10 mm for KPC 24/7 270.

### Pumped liquids


KPC pumps are designed for pumping drainage, rainwater and grey wastewater without fibres.

The pumps are not suitable for these liquids:

- liquids containing long fibres
- inflammable liquids (such as oil or petrol)
- aggressive liquids.


## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 32 mm and flow of 2 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve, 4x90° bends and a gate valve is calculated. The vertical height of the outlet pipe should be measured from the pump stop level. For more flow requirements a calculation is needed.



TM063885

## Performance curves KPC 24/7 50 Hz



## Product range KPC 24/7 50 Hz

Pump type	Product number	Voltage [V]	Plug type	Float switch type	Cable length [m]	Cable type	Net weight [kg]
KPC 24/7 210	98851057	1 x 220-240	SCHUKO	-	10	H05RN-F 3G0.75	4.5
KPC 24/7 270	98851058	1 x 220-240	SCHUKO	-	10	H05RN-F 3G0.75	4.5
KPC 24/7 210	98917605	1 x 220-240	UK	-	10	H05RN-F 3G0.75	4.5
KPC 24/7 270	98917606	1 x 220-240	UK	-	10	H05RN-F 3G0.75	4.5

## Technical data

### Electrical data


Pump type	Voltage [V]	P1 [kW]	P2 [kW]	I <sub>1/1</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
KPC 24/7 210	1 x 220-240	0.35	0.22	1.5	8	2900
KPC 24/7 270	1 x 220-240	0.35	0.22	1.5	8	2900

### Operating conditions

Max. head	6.5 m
Max. flow rate	10 m <sup>3</sup> /h
Liquid temperature range	0-35 °C
Liquid pH range	4-6 pH
Liquid requirements	Grey wastewater without fibres
Max. ambient temperature	40 °C
Max. particle size	KPC 24/7 210 5 mm KPC 24/7 270 10 mm
Min. water level	KPC 24/7 210 8 mm KPC 24/7 270 30 mm
Installation	Permanent or portable in a vertical position
Max. submersion depth	10 m
Special versions on request	Other voltages and/or frequencies

4) IEC 60335-2-41 requires 3 m cable length outside of water.

### Dimensions



TM063861

Pump type	A [mm]	B [mm]	H [mm]	Connection [inch]
KPC 24/7 210	185	140	266	Rp 1 1/4
KPC 24/7 270	185	140	275	Rp 1 1/4

## UNILIFT CC



GR-1017866

The UNILIFT CC pumps are single-stage, highly robust submersible pumps capable of pumping down to a 3 mm water level and handling particles up to 10 mm. The pump body contains a cooling jacket for operating partly submerged. The pumps have both a top and a side outlet, allowing easy adaptation to existing pipes including auto coupling systems.

The pumps are suitable for permanent installation or can be used as portable pumps. Three variations of the pump are available

- with an included float switch for automatic start and stop
- without a float switch to connect to a separate level controller
- manual start and stop of the pump.

### Applications

The pump is suitable for the following applications:

- lifting up greywater to sewer mains from basements of sanitary appliances like wash basins, sinks, showers and bath tubs
- collecting and discharging of rainwater or groundwater in drainage systems around building basements
- emptying of pools, ponds and flooded basements
- backwater prevention to protect the building basement and to discharge greywater from sanitary appliances
- installation in pumping stations and tanks to get a complete lifting station
- special pump version for media containing salt water and chlorinated water.

### Features and benefits of UNILIFT CC

UNILIFT CC has many beneficial features:

- cooling jacket that allows the pump to operate continuously while partially submerged
- comprehensive motor protection
- automatic venting for trouble-free startup after dry periods
- draining of areas, such as flooded basements, down to a level of just 3 mm
- strong composite casing and stainless-steel strainer
- 3 shaft seals with extra V-ring for UNILIFT CC 7 and 9 to protect the shaft seals against sand particles
- ceramic shaft to prolong the lifetime of the pump.

### Type key

Example: UNILIFT CC.9.A1.HG

Description		
UNILIFT	Type range	
CC	Type	
5		
7		Max. head [m]
9		
A1 - automatic operation		
AG - automatic operation, guided arm		Level control
M1 - manual operation		
- standard material		Material
HG - high grade material		

### Approvals and markings

#### Approvals



TM075405



99853271

### Scope of delivery

The delivery includes:

- a non-return flap valve approved according to EN 12050-4 with a 90° bend
- a stepped adapter with outside threads of R ¾", 1" and 1 ¼" to connect to different pipes or hoses when used in mobile applications.

### Pumped liquids

The pumps are suitable for these liquids:


- slightly dirty water such as drainage or greywater from sanitary appliances
- non-aggressive wastewater.

However, special versions with a higher grade material (EN 1.4401/AISI316) on motor parts are suitable for salt media such as brackish water in ports, seawater, water softeners, and chlorinated water less than 20 °C.

The pumps are not suitable for these liquids:

- liquids containing long fibres
- inflammable liquids (such as oil and petrol)
- aggressive liquids.

## Construction of UNILIFT CC



## Materials

Pos.	Component	Material	DIN W. - Nr.
55	Motor sleeve	PP 15 GF	
55a	Pump sleeve	PP 15 GF	
49	Impeller	PP 20 GF	
84	Inlet strainer	Stainless steel, class A2	
-	V-rings	NBR 50	
-	O-rings	NBR 70	
181	Cable	H05RN-F 3G0.75 (CC 5) H07RN-F3G1 (CC 7 - CC 9)	
-	Wetted parts <sup>5)</sup>	Stainless steel, class 2	1.4401

<sup>5)</sup> Only included in special pump variant.

## Cooling jacket

The pump can operate partially submerged because the motor is cooled by the pumped media. This feature allows the pump to operate longer periods with low water levels.

## Shaft seal

UNILIFT CC contains 3 shaft seals. Two face the medium and one is placed in the motor between a grease chamber filled with long-life, high temperature grease. To extend the lifetime of seals, the shaft is ceramic coated. For added safety of the shaft with abrasive media, the shaft seals of UNILIFT CC 7 and UNILIFT CC 9 are protected with a V-ring.

## Strainer

UNILIFT CC has an easily removable strainer composed of stainless steel. The strainer can be clipped off from the pump body to enable a lower suction down to 3 mm.

## Dual outlet

The two outlet options offer maximum flexibility in replacement situations or new installations. These pump types can be placed in small wells using the top outlet connection, or they can be placed in deep pumping stations assembled on auto couplings.

## Self-venting hydraulic

A pit or drainage sump can dry out during summer periods or air can enter into the hydraulic. The self-venting hydraulic enables air to escape when water levels rise which secures a reliable restart.

## Motor

The motor is a single-phase, asynchronous, dry-rotor motor. The axial rotor position is secured with a ball bearing. The motor is cooled by the pumped liquid around the motor.

	Insulation class	Enclosure class
UNILIFT CC 5	B	IP68
UNILIFT CC 7	F	IP68
UNILIFT CC 9	B	IP68

The motor includes automatic overload protection which cuts out the motor in case of overload. When cooled to normal temperatures, the motor will restart automatically.


## Pump and motor sleeve

The pump and motor sleeve are both made of composite material cast in one piece with a 1 1/4" external pipe thread (G) outlet connection. A slot on the handle holds the float switch cable. The mains cable and float switch cables are lead into the motor sleeve through hermetically sealed cable entries.


The inlet strainer is fitted to the pump sleeve by giving it a light push, and it can be removed easily by means of a screwdriver or similar tool. The water enters the pump through the holes of the inlet strainer preventing the passage of large solids. The large holes also ensure a slow flow into the pump. Suction to low water level is obtained by removing the strainer.

## Sizing guide


The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 32 mm and flow of 2 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve, 4x90° bends and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.



TM066945

**Performance curves UNILIFT CC 50 Hz**

TM031346

**Performance curves UNILIFT CC 60 Hz**

TM045662

**Product range UNILIFT CC 50 Hz**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length [m]	Cable type	Net weight [kg]
UNILIFT CC 5	96280965	1 x 220-240	SCHUKO	-	5	H05RN-F 3G0.75	4.3
	96280966	1 x 220-240	SCHUKO	Cable guided	5	H05RN-F 3G0.75	4.5
	98624419	1 x 220-240	SCHUKO	Arm guided	5	H05RN-F 3G0.75	4.7
	96280977	1 x 220-240	No plug	-	5	H05RN-F 3G0.75	4.3
	96280978	1 x 220-240	No plug	Cable guided	5	H05RN-F 3G0.75	4.5
	96280972	1 x 220-240	Australia	Cable guided	5	H05RN-F 3G0.75	4.5
UNILIFT CC 7	96280967	1 x 220-240	SCHUKO	-	10	H07RN-F 3G1	5.0
	96280968	1 x 220-240	SCHUKO	Cable guided	10	H07RN-F 3G1	5.3
	98624464 <sup>6)</sup>	1 x 220-240	SCHUKO	Cable guided	10	H05RN-F 3G0.75	5.4
	98624463	1 x 220-240	SCHUKO	Arm guided	10	H05RN-F 3G0.75	5.4
	96280979	1 x 220-240	No plug	-	10	H07RN-F 3G1	5.0
	96280980	1 x 220-240	No plug	Cable guided	10	H07RN-F 3G1	5.3
UNILIFT CC 9	96280974	1 x 220-240	Australia	Cable guided	10	H07RN-F 3G1	5.3
	96280969	1 x 220-240	SCHUKO	-	10	H07RN-F 3G1	6.6
	96280970	1 x 220-240	SCHUKO	Cable guided	10	H07RN-F 3G1	6.8
	98624466 <sup>6)</sup>	1 x 220-240	SCHUKO	Cable guided	10	H07RN-F 3G1	6.9
	98624465	1 x 220-240	SCHUKO	Arm guided	10	H07RN-F 3G1	6.9
	96280981	1 x 220-240	No plug	-	10	H07RN-F 3G1	6.6
	96280982	1 x 220-240	No plug	Cable guided	10	H07RN-F 3G1	6.8
	96280976	1 x 220-240	Australia	Cable guided	10	H07RN-F 3G1	6.8

<sup>6)</sup> Special version for aggressive media, composed of higher grade stainless steel (AISI 316).

**Product range UNILIFT CC 60 Hz**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length [m]	Cable type	Net weight [kg]
UNILIFT CC 5	97530823	1 x 230	No plug	-	5	H05RN-F 3G0.75	4.5
	97530824	1 x 230	No plug	Cable guided	5	H05RN-F 3G0.75	4.5
UNILIFT CC 7	97530825	1 x 230	No plug	-	10	H07RN-F 3G1	4.7
	97530826	1 x 230	No plug	Cable guided	10	H07RN-F 3G1	4.7
UNILIFT CC 9	97530827	1 x 230	No plug	-	10	H07RN-F 3G1	6.5
	97530828	1 x 230	No plug	Cable guided	10	H07RN-F 3G1	6.5

## Technical data

### Electrical data

#### 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
UNILIFT CC 5	1 x 220-240	0.24	0.108	1.1	1.8	2850
UNILIFT CC 7	1 x 220-240	0.38	0.171	1.7	3.1	2850
UNILIFT CC 9	1 x 220-240	0.78	0.465	3.7	8.2	2850

#### 60 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rppm]
UNILIFT CC 5	1 x 230	0.25	0.101	2.1	2.7	3115
UNILIFT CC 7	1 x 230	0.35	0.179	2.8	5.7	3115
UNILIFT CC 9	1 x 230	0.66	0.42	5.6	18.5	3115

### Operating conditions


#### Liquid temperature

Max. head	5 m
Max. flow rate	6 m <sup>3</sup> /h
Liquid temperature range	0-40 °C
Liquid pH range	4-9
Liquid requirements	Clean, non-aggressive water and grey wastewater
Max. ambient temperature	40 °C
Max. particle size	10 mm
Max. submersion depth	UNILIFT CC5: 2 m UNILIFT CC7 and CC9: 7 m
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

7) At intervals of at least 30 minutes, the pump is allowed to run at maximum +70 °C for periods not exceeding two minutes

8) IEC 60335-2-41 requires 3 m cable length outside of water


### Dimensions



TM060739

## Installation

The pump can be used in vertical position and tilted or horizontal position with the outlet port as the highest point of the pump. The inlet strainer must be covered by the pumped liquid.



TM00111


*Pump installation positions*

### Installation depth

Maximum 10 metres below the water surface.

### Installation in a narrow pit

If the UNILIFT CC pump is to be installed in a narrow pit, it is available with a level arm bracket. The minimum narrow pit dimensions are 300 x 350 mm.



TM060696


Pump type	Start and stop levels for level arm		Cable length [L] min. 100 mm	Cable length [L] min. 200 mm
	Start [mm]	Stop [mm]		
UNILIFT CC	211	89		
UNILIFT CC 7	211	89		
UNILIFT CC 9	247	125		

### Adjustment of cable length for float switch

The difference in level between start and stop can be adjusted by changing the free cable length between the float switch and the pump handle.

- Increasing the free cable length results in fewer starts and stops and a large difference in level.
- Reducing the free cable length results in more frequent starts and stops and a small difference in level.

In order for the float switch to start and stop the pump, the free cable length must be at minimum 100 mm and maximum 200 mm.



TM030829

*Start and stop level, UNILIFT CC*

Pump type	Cable length [L] min. 100 mm		Cable length [L] min. 200 mm	
	Start [mm]	Stop [mm]	Start [mm]	Stop [mm]
UNILIFT CC 5	350	115	400	55
UNILIFT CC 7	350	115	400	55
UNILIFT CC 9	385	150	435	90

## Accessories

The following are recommended accessories for UNILIFT CC.

Product number	Description
98709179	Guide arm for floater, UNILIFT CC
99369644	LC231 (1 pump) without float switch
99369650	LC231 (dual pump controller) without float switch
91427145	Float switch M2 with 5 m cable

## MULTIBOX



GR-1017865

MULTIBOX is an accessory set that is recommended for cellars and buildings prone to flooding. The box prevents particles from disrupting the pump suction side. This accessory set contains:

- UNILIFT CC7 A1 pump
- strainer/transportation box with lid
- Storz C coupling
- 15 m hose
- anti-kink sleeve
- non-return valve.

Pump type	Description
97519841	MULTIBOX UNILIFT

## UNILIFT KP



UNILIFT KP submersible, stainless-steel drainage pump in a compact design with hermetically sealed stator housing (canned motor). It has a service-friendly and sustainable product design. The pump body contains a cooling jacket for partially submerged operation. The pump is able to handle particles up to 10 mm.

The pump is suitable for permanent installation or can be used as a portable pump.

The following options are available:

- with a cable-guided float switch for automatic start/stop
- with a vertical level switch for automatic start in small confined spaces
- without a float switch for manual operation
- connection to a separate level controller.

### Applications

The pump is suitable for the following applications:

- pumping in drainage collecting wells, pits inside and outside the building
- mobile emergency use to drain flooded areas such as basements
- backwater prevention to protect the building basement and to discharge greywater from sanitary appliances
- emptying of swimming pools, ponds and tanks
- industrial and commercial use, for example, evaporative cooling systems
- various applications within agriculture, horticulture and dairies, breweries and the process industry.

### Features and benefits of UNILIFT KP

UNILIFT KP has many beneficial features:

- robust and sustainable stainless-steel design for all hydraulic parts
- service friendly to extend pump lifetime – quick access to replace wear parts, for example, float switch, shaft sealing, impeller and rotor
- cooling jacket that allows the pump to operate continuously while partially submerged
- comprehensive motor protection
- the only wet runner on the market with prolonged pump longevity even on worn shaft seals
- longitudinal, water-tight cables and glass-sealed cable socket on the pump that prevents water from entering the motor at damaged cables and enables easy replacement.

### Type key

Example:

UNILIFT KP.150.A.1

Description	
UNILIFT KP	Type range
150	
250	Rated motor output (P2 [W])
350	
AV - With vertical level switch (automatic operation)	
A - With float switch (automatic operation)	Level control
M - Without level switch (manual operation)	
1 - single-phase	Motor
3 - three-phase	

### Approvals and markings

#### Approvals



TM075405



TM074611



9850708\_RCM\_MARK



TM075835




998593271



TM074619

## Construction of UNILIFT KP



## Materials

Pos.	Component	Material	DIN W.-Nr.	AISI Nr.
	Pump sleeve	Stainless steel	1.4301	304
50	Pump housing	Stainless steel	1.4301	304
84	Inlet strainer	Stainless steel	1.4301	304
49	Impeller	Stainless steel	1.4301	304
172	Shaft	Stainless steel	1.4057	431
	Stator housing	Stainless steel	1.4301	304
-	Guide vanes	Stainless steel	1.4301	304
188	Bearings	Carbon		
-	O-rings	NBR		
37	Seal rings	NBR		
181	Cables	H07RN(8)-F 3G1 H07RN(8)-F 4G1		

## Cooling jacket

The pump has an outer casing that ensures continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid.

## Pump sleeve

The stainless-steel pump sleeve is made in one piece with Rp 1 1/4 outlet port and insulating handle. UNILIFT KP pumps have a watertight vulcanised plug.

## Stator housing

Completely hermetically sealed stator housing eliminates potential entry points for water. A semi-open impeller is designed to avoid solids and fibres jamming the pump.

## Motor

The motor is a single-phase or three-phase, asynchronous canned motor with liquid-filled rotor chamber and water-lubricated bearings. The motor is cooled by the pumped liquid around the motor.

- Enclosure class: IP68
- Insulation class: F

The motor incorporates automatic overload protection. In case of overload, the motor stops automatically. When cooled, the motor restarts automatically.

## Shaft seal

The pump has a double shaft seal consisting of two lip seals that are greased in between.

## Impeller

The sturdy impeller has single-curved vanes. The bevelled front edges prevent fibres from jamming the impeller.

The guide vanes of the pump housing guide the liquid, lifting sand grains into the liquid flow. This prevents sand from blocking the impeller.

## Strainer

Liquid enters the pump through the holes of the inlet strainer. The holes of the strainer prevent the passage of large solids.

## Pumped liquids


The pump is suitable for the following liquids:

- clean, non-aggressive water
- slightly dirty (grey) wastewater.



The open-impeller design ensures free passage of solids up to Ø10.

## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 32 mm and flow of 2 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve, 4x90° bends and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.



TM066946

**Performance curves UNILIFT KP 50 Hz****Performance curves UNILIFT KP 60 Hz****Product range UNILIFT KP 50 Hz****UNILIFT KP 150**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length	Cable type	Net weight [kg]
KP 150	011H1300	1 x 220-230	SCHUKO	-	10 m	H07RN8-F 3G1	6.1
	011H1600	1 x 220-230	SCHUKO	Cable guided	5 m	H07RN8-F 3G1	5.7
	011H1800	1 x 220-230	SCHUKO	Cable guided	10 m	H07RN8-F 3G1	6.3
	011H1400	1 x 220-230	SCHUKO	Vertical	5 m	H07RN8-F 3G1	5.8
	011H1900	1 x 220-230	SCHUKO	Vertical	10 m	H07RN8-F 3G1	6.4
	011H6000	1 x 220-230	No plug	-	5 m	H07RN8-F 3G1	5.4
	011H6300	1 x 220-230	No plug	-	10 m	H07RN8-F 3G1	6.0
	011H6600	1 x 220-230	No plug	Cable guided	5 m	H07RN8-F 3G1	5.6
	011H6800	1 x 220-230	No plug	Cable guided	10 m	H07RN8-F 3G1	6.2
	011H6400	1 x 220-230	No plug	Vertical	5 m	H07RN8-F 3G1	5.7
	011H6900	1 x 220-230	No plug	Vertical	10 m	H07RN8-F 3G1	6.3
	92533101	1 x 220-230	Australia	-	5 m	H07RN-F 3G1	5.5
	92533687	1 x 220-230	Australia	Cable guided	5 m	H07RN-F 3G1	5.7
	92533103	1 x 220-230	Australia	Vertical	5 m	H07RN-F 3G1	5.8

**UNILIFT KP 250**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length	Cable type	Net weight [kg]
KP 250	012H1300	1 x 220-230	SCHUKO	-	10 m	H07RN8-F 3G1	6.3
	012H1600	1 x 220-230	SCHUKO	Cable guided	5 m	H07RN8-F 3G1	5.9
	012H1800	1 x 220-230	SCHUKO	Cable guided	10 m	H07RN8-F 3G1	6.5
	012H1400	1 x 220-230	SCHUKO	Vertical	5 m	H07RN8-F 3G1	6.0
	012H1900	1 x 220-230	SCHUKO	Vertical	10 m	H07RN8-F 3G1	6.6
	012H6000	1 x 220-230	No plug	-	5 m	H07RN8-F 3G1	5.6
	012M6100	3 x 380-415	No plug	-	5 m	H07RN8-F 4G1	6.3
	012M6300	3 x 380-415	No plug	-	5 m	H07RN8-F 4G1	7.0
	012H6300	1 x 220-230	No plug	-	10 m	H07RN8-F 3G1	6.2
	012H6600	1 x 220-230	No plug	Cable guided	5 m	H07RN8-F 3G1	5.8
	012H6800	1 x 220-230	No plug	Cable guided	10 m	H07RN8-F 3G1	6.4
	012H6400	1 x 220-230	No plug	Vertical	5 m	H07RN8-F 3G1	5.9
	012H6900	1 x 220-230	No plug	Vertical	10 m	H07RN8-F 3G1	6.5
	92533641	1 x 220-230	Australia	-	5 m	H07RN-F 3G1	5.7
	92533646	1 x 220-230	Australia	Cable guided	5 m	H07RN-F 3G1	5.9
	92533644	1 x 220-230	Australia	Vertical	5 m	H07RN-F 3G1	6.0

**UNILIFT KP 350**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length	Cable type	Net weight [kg]
KP 350	013N1300	1 x 220-240	SCHUKO	-	10 m	H07RN8-F 3G1	6.7
	013N1600	1 x 220-240	SCHUKO	Cable guided	5 m	H07RN8-F 3G1	6.3
	013N1800	1 x 220-240	SCHUKO	Cable guided	10 m	H07RN8-F 3G1	6.9
	013N1400	1 x 220-240	SCHUKO	Vertical	5 m	H07RN8-F 3G1	6.4
	013N1900	1 x 220-240	SCHUKO	Vertical	10 m	H07RN8-F 3G1	7.0
	013M6100	3 x 380-400	No plug	-	5 m	H07RN8-F 4G1	7.1
	013M6300	3 x 380-400	No plug	-	10 m	H07RN8-F 4G1	7.5
	013N6300	1 x 220-240	No plug	-	10 m	H07RN8-F 3G1	6.6
	013N6600	1 x 220-240	No plug	Cable guided	5 m	H07RN8-F 3G1	6.2
	013N6800	1 x 220-240	No plug	Cable guided	10 m	H07RN8-F 3G1	6.8
	013N7900	1 x 220-240	No plug	Vertical	10 m	H07RN8-F 3G1	6.9
	92533648	1 x 220-240	Australia	-	5 m	H07RN-F 3G1	6.1
	92533666	1 x 220-240	Australia	Cable guided	5 m	H07RN-F 3G1	6.3
	92533662	1 x 220-240	Australia	Vertical	5 m	H07RN-F 3G1	6.4

**Product range UNILIFT KP 60 Hz****UNILIFT KP 250**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length	Cable type	Net weight
KP 250	012G6300	1 x 220-230	No plug	-	10 m	H07RN8-F 3 G 1	5.6
	012G6600	1 x 220-230	No plug	Cable guided	5 m	H07RN8-F 3 G 1	5.6
	012G6800	1 x 220-230	No plug	Cable guided	10 m	H07RN8-F 3 G 1	5.6
	012G6400	1 x 220-230	No plug	Vertical	5 m	H07RN8-F 3 G 1	5.6
	012G6900	1 x 220-230	No plug	Vertical	10 m	H07RN8-F 3 G 1	5.6

**UNILIFT KP 350**

Pump type	Product number	Voltage[V]	Plug type	Float switch	Cable length	Cable type	Net weight
KP 350	013G6600	1 x 220-230	No plug	Cable guided	5 m	H07RN8-F 3 G 1	5.6
	013G6800	1 x 220-230	No plug	Cable guided	10 m	H07RN8-F 3 G 1	5.6

## Technical data

### Electrical data

#### UNILIFT KP 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
KP 150	1 x 220-230	0.30	0.15	1.3	3.3	2666
	1 x 220-230	0.48	0.25	2.3	6.6	2692
KP 250	3 x 380-415	0.48	0.25	0.8	2.9	2568
	1 x 220-240	0.72	0.35	3.2	8.9	2665
KP 350	3 x 380-400	0.70	0.35	1.3	5.2	2674

#### UNILIFT KP 60 Hz

Pump type	Voltage [V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
KP 250	1 x 220-230	0.71	0.25	3.6	7.7	3298
KP 350	1 x 220-230	0.75	0.35	3.2	8.1	3155

### Operating conditions


During continuous operation, the inlet strainer must always be completely covered by liquid.

Max. head	5.5-10 m
Max. flow rate	11.2-14 m <sup>3</sup> /h
Liquid temperature range	0-50 °C
Liquid requirements	Clean, non-aggressive water and grey wastewater
Max. ambient temperature	50 °C
Max. particle size	10 mm
Max. submersion depth	2 m with 5 m cable length 7 m with 10 m cable length
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

<sup>9)</sup> At intervals of at least 30 minutes, the pump is allowed to run at maximum +70 °C for periods not exceeding two minutes. Liquid temperature depends on voltage.

<sup>10)</sup> IEC 60335-2-41 requires 3 m cable length outside of water.

## Dimensions




TM013978

Pump type	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	Connection [inch]
UNILIFT KP 150	214	225	30	148	140	Rp 1 1/4"
UNILIFT KP 250						
UNILIFT KP 350	224	235	30	148	140	Rp 1 1/4"


## Installation

If UNILIFT KP is installed in a collecting well, the minimum well dimensions must be as shown in the figures below.

To avoid loss of air pressure, the pump must be placed as far from the inlet connection as possible.



TM034445

*Minimum well dimensions, UNILIFT KP-A*


TM011109

*Minimum well dimensions, UNILIFT KP-AV*

## Pump positioning

UNILIFT KP-M and UNILIFT KP-A can be used in vertical position with the outlet port facing up or in horizontal or tilted position with the outlet port as the highest point of the pump.

UNILIFT KP-AV must be used in vertical position.




TM001548

## Level switches

A level switch starts and stops the pump between two liquid levels. This type of installation requires a non-return valve in the outlet pipe or the pump. UNILIFT KP pumps are available with two different level switch types.

### UNILIFT KP-A with float switch

A clamp on the pump handle holds the float switch cable. The difference in level between start and stop can be adjusted by changing the free cable length between pump handle and float switch.




TM034446

*Start/stop levels at min. and max. cable lengths, UNILIFT*

Pump type	Cable length		Cable length	
	Start [mm]	Stop [mm]	Start [mm]	Stop [mm]
UNILIFT KP 150 A	290	140	335	100
UNILIFT KP 250 A				
UNILIFT KP 350 A	300	150	345	110

**UNILIFT KP AV with vertical level switch**

For pumps with vertical level switch, the difference in level between start and stop is not adjustable.



*Start/stop levels for UNILIFT KP AV*

Pump type	Vertical level switch	
	Start [mm]	Stop [mm]
UNILIFT KP 150 AV	180	100
UNILIFT KP 250 AV		
UNILIFT KP 350 AV	190	110

Level switch water temperature: 0-50 °C

**Accessories**

Product number	Description
15211	Non-return valve
99369644	LC231 (1 pump) without float switch
99369650	LC231 (2 pump controller) without float switch
91427145	Float switch M2 with 5 m cable

## UNILIFT AP12



UNILIFT AP12 is a submersible pump designed for pumping drainage water or higher flows for effluent applications. The pump allows bypass of larger particles up to 12 mm. The pump has a riser pipe and cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep groove greased-for-life ball bearings. The pump is ready for use as it is fitted with a carrying handle and is supplied with a 10 m mains cable. The mains cable has a plug with a glass-sealing compound in the socket to prevent humidity from entering the stator windings.

The pump is suitable for permanent installations or it can be used as a portable pump. The pump is available with the following options:

- with a float switch fitted for automatic on/off operation between two liquid levels (single-phase pumps)
- with separate level switch and control box for automatic on/off operation between two liquid levels (three-phase pumps)
- without a level switch for manual on/off operation

Pumps fitted with a float switch can also be used for manual on/off operation. In this case, the float switch must be secured in an upward-facing position.

### Applications

The pump is suitable for the following applications:

- pumping in drainage collecting wells, pits inside buildings
- pumping stations and small domestic treatment plants outside of buildings
- industrial and commercial use, for example, evaporative cooling systems
- various applications within agriculture, horticulture, dairies, breweries and the process industry
- emergencies, for example, flooding events inside and outside of buildings, and to pump (waste)water out of tanks, ponds or swimming pools.

## Features and benefits of UNILIFT AP

UNILIFT AP has many beneficial features:

- robust and sustainable stainless-steel design for all hydraulic parts
- service friendly to extend pump lifetime – quick access to replace wear parts, for example, cable, float switch, shaft sealing, impeller and rotor.
- cooling jacket that allows the pump to operate continuously while partially submerged
- included motor protection that reacts to blockage
- longitudinal, water-tight cables and glass-sealed cable socket on the pump that prevents water from entering the motor at damaged cables and enables easy replacement
- highly reliable mechanical shaft seal with an oil chamber that protects the seals and motor.
- Range for frequency drive operation

### Type key

Example:

UNILIFT AP 35.B.50.08.A1V

Description	
UNILIFT AP	Type range
12	
35	Maximum solids size
50	
Blank - AP pump	Pump type
B - AP Basic	
40	Nominal diameter of the outlet port [mm]
50	
	Power output (P2/100[W])
A - automatic operation (with float switch)	
Blank - manual operation (without float switch)	Level control
1 - single-phase	
3 - three-phase	Motor
V - vortex impeller	Impeller

## Approvals and markings

### Approvals



TM075405



TM074611



98/65/EC ROM MARK



TM075335




98/65/EC



TM074619

## Construction of UNILIFT AP12



## Materials

Pos.	Component	Material	DIN W. - Nr.	AISI
6	Pump housing	Stainless steel	1.4301	304
31	Riser pipe	Stainless steel	1.4301	304
49	Impeller	Stainless steel	1.4301	304
55	Pump sleeve	Stainless steel	1.4401	316
-	Pump shaft - wet end	Stainless steel	1.4301	304
188	Bearings	Heavy-duty prelubricated ball bearings		
-	O-rings	NBR rubber		
-	Screws	Stainless steel	1.4301	304
181	Oil	Shell Ondina 15, non-toxic		

## Cooling jacket

The pump has a riser pipe and a cooling jacket for continuous cooling of the motor by the pumped liquid.

## Outlet port

All UNILIFT AP12 pumps have a threaded vertical outlet port.

- UNILIFT AP12.40: Rp 1 1/2
- UNILIFT AP12.50: Rp 2.

## Pump sleeve and housing

The stainless-steel pump sleeve is made in one piece and equipped with an insulated carrying handle. The inlet strainer is clipped onto the pump housing for easy removal in connection with maintenance.

The strainer prevents the passage of large solids and ensures a slow flow into the pump. As a result, most impurities are prevented from entering the pump. The stainless-steel pump housing is fitted with an internal riser pipe ensuring high efficiency.

The riser pipe has a number of holes enabling efficient cooling of the motor during operation. The cable entry has a socket and plug connection for quick and easy dismantling.

## Motor

The motor is a single- or three-phase asynchronous dry-rotor motor.

Enclosure class	IP68
Insulation class	F (155 °C)
Cable type	H07RN(8)-F

Single-phase motors have built-in thermal protection.

Manufactured according to EN 60335-2-41.

## Shaft and bearings

The stainless-steel shaft rotates in maintenance-free pre-lubricated ball bearings.

## Impeller

The stainless-steel impeller is a semi-open impeller with L-shaped blades and a clearance of 12 mm. The blades are curved backwards to reduce any harmful effects from solid particles and to minimise power consumption.

## Shaft seal

The shaft seal is a combination of a mechanical bellows shaft seal and a lip seal with 60 ml oil between. Seal faces are made of silicone carbide.

## Pumped liquids

The pumps are suitable for the following liquids:

- clean, non-aggressive water
- slightly dirty (grey) wastewater.


The open-impeller design ensures free passage of solids up to 12 mm.

## Level switches and control boxes

Level controllers and switches are delivered with the product and are directly connected to the single-phase motors. For three-phase motors, level switch solutions are available with control boxes in between the pump and the level switch. The cable length for the pump and level switch is 10 m. A power supply cable of 0.65 m is connected to the box. The level controller box incorporates a contactor and a motor protection unit. The motor protection unit is preset with the nominal current of the pump.

## Sizing guide



The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 40 mm and a flow of 3.2 m<sup>3</sup>/h for AP12.40, so that a self cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve, 4x90° bends and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.



TM031878

<sup>11)</sup> For AP12.50 pumps it is an inner pipe diameter of 50 mm and a flow of 5 m<sup>3</sup>/h.

<sup>12)</sup> UNILIFT AP12.50.11 3x200-220V, 60 Hz is excluded from this overview. Carry out separate calculations for this variant.

**Performance curves UNILIFT AP12 50 Hz****Performance curves UNILIFT AP12 60 Hz****Product range UNILIFT AP12 50 Hz**

Pump type	Product number(s)	Voltage [V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length [m]	Cable type	Net weight [kg]
AP12.40.04.1	96011016	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	12.1
AP12.40.04.A1	96011017	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	11.7
AP12.40.04.A1	96011018	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	12.3
AP12.40.06.1	96001720	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	12.6
AP12.40.06.A1	96001735	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	12.2
AP12.40.06.A1	96010979	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	12.8
AP12.40.08.1	96001869	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	13.7
AP12.40.08.A1	96001798	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	13.3
AP12.40.08.A1	96010980	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	13.9
AP12.50.11.1	96001958	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	15.6
AP12.50.11.A1	96001965	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	15.2
AP12.50.11.A1	96010981	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	15.8
AP12.40.04.1	96011014	1 x 230	No plug	-	-	10	H07RN8-F 3G1	12.0
AP12.40.04.A1	96011015	1 x 230	No plug	-	Cable guided	5	H07RN8-F 3G1	11.6
AP12.40.04.A1	96404179	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	12.2
AP12.40.04.3	96011024	3 x 400	No plug	-	-	10	H07RN8-F 4G1	12.4
AP12.40.04.3	96011030	3 x 230	No plug	-	-	10	H07RN8-F 4G1	12.4
AP12.40.04.A3	96011025	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	13.6
AP12.40.06.1	96001732	1 x 230	No plug	-	-	10	H07RN8-F 3G1	12.5
AP12.40.06.A1	96404180	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	12.7
AP12.40.06.3	96001652	3 x 400	No plug	-	-	10	H07RN8-F 4G1	12.9
AP12.40.06.3	96010628	3 x 230	No plug	-	-	10	H07RN8-F 4G1	12.9
AP12.40.06.A3	96010923	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	14.1
AP12.40.08.1	96001873	1 x 230	No plug	-	-	10	H07RN8-F 3G1	13.6
AP12.40.08.3	96001791	3 x 400	No plug	-	-	10	H07RN8-F 4G1	14.0
AP12.40.08.3	96010630	3 x 230	No plug	-	-	10	H07RN8-F 4G1	14.0
AP12.40.08.A3	96010925	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	14.2
AP12.40.08.A3	96010958	3 x 230	No plug	✓	Cable guided	10	H07RN8-F 4G1	14.2
AP12.50.11.1	96001962	1 x 230	No plug	-	-	10	H07RN8-F 3G1	15.5
AP12.50.11.A1	96404182	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	15.7
AP12.50.11.3	96010634	3 x 230	No plug	-	-	10	H07RN8-F 4G1	15.9
AP12.50.11.A3	96010927	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.1

Pump type	Product number(s)	Voltage [V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length [m]	Cable type	Net weight [kg]
AP12.50.11.A3	96010959	3 x 230	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.1
AP12.50.11.3	96001975	3 x 400	No plug	-	-	10	H07RN8-F 4G1	15.9
AP12.40.04.A3	96023871	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	12.92
AP12.40.06.A3	96023872	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	14.28
AP12.40.08.A3	96023873	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	16.18
AP12.40.08.A1	96404181	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	13.8
AP12.50.11.A3	96023874	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	17.5
AP12.40.04.1	96011032	1 x 230	Australia	-	-	10	H07RN-F 3G1	11.6
AP12.40.04.A1	96023914	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	10.7
AP12.40.06.1	96001729	1 x 230	Australia	-	-	10	H07RN-F 3G1	12.0
AP12.40.06.A1	96023929	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	12.8
AP12.40.08.1	96001872	1 x 230	Australia	-	-	10	H07RN-F 3G1	13.2
AP12.40.08.A1	96023930	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	13.9
AP12.50.11.1	96001961	1 x 230	Australia	-	-	10	H07RN-F 3G1	15.7
AP12.50.11.A1	96023931	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	15.6

### Product range UNILIFT AP12 50 Hz for frequency drive operation

Pump type	Product number(s)	Voltage [V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length [m]	Cable type	Net weight [kg]
UNILIFT AP12.40.06.3	92747392	3 x 400	No plug	-	-	10	H07RN8-F 4G1	12.9
UNILIFT AP12.40.08.3	92747394	3 x 400	No plug	-	-	10	H07RN8-F 4G1	14.0
UNILIFT AP12.50.11.3	98492741	3 x 400	No plug	-	-	10	H07RN8-F 4G1	15.9

### Product range UNILIFT AP12 60 Hz

Pump type	Product number	Voltage [V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length [m]	Cable type	Net weight [kg]
AP12.40.04.1	96023923	1 x 220 - 230	No plug	-	-	10	H07RN8-F 3G1	12.0
AP12.40.04.A1	96023921	1 x 220 - 230	No plug	-	Cable guided	5	H07RN8-F 3G1	11.4
AP12.40.04.A1	96023922	1 x 220 - 230	No plug	-	Cable guided	10	H07RN8-F 3G1	11.6
AP12.40.04.3	96011027	3 x 200 - 220	No plug	-	-	10	H07RN8-F 4G1	12.4
AP12.40.04.3	96011029	3 x 380 - 440	No plug	-	-	10	H07RN8-F 4G1	12.4
AP12.40.04.A3	96011042	3 x 380 - 440	No plug	✓	Cable guided	10	H07RN8-F 4G1	13.6
AP12.40.06.1	96010659	1 x 220 - 230	No plug	-	-	10	H07RN8-F 3G1	12.5
AP12.40.06.3	96010895	3 x 200 - 220	No plug	-	-	10	H07RN8-F 4G1	12.9
AP12.40.06.3	96001776	3 x 380 - 440	No plug	-	-	10	H07RN8-F 4G1	12.9
AP12.40.06.A3	96010938	3 x 380 - 440	No plug	✓	Cable guided	10	H07RN8-F 4G1	14.1
AP12.40.08.1	96010665	1 x 220 - 230	No plug	-	-	10	H07RN8-F 3G1	13.6
AP12.40.08.A1	98602896	1 x 220 - 230	No plug	-	Cable guided	5	H07RN8-F 3G1	13.8
AP12.40.08.3	96010896	3 x 200 - 220	No plug	-	-	10	H07RN8-F 4G1	14.0
AP12.40.08.3	96010641	3 x 380 - 440	No plug	-	-	10	H07RN8-F 4G1	14.0
AP12.40.08.A3	96010941	3 x 380 - 440	No plug	✓	Cable guided	10	H07RN8-F 4G1	15.2
AP12.40.08.A3	96010940	3 x 200 - 220	No plug	✓	Cable guided	10	H07RN8-F 4G1	15.2
AP12.50.11.1	96010682	1 x 220 - 230	No plug	-	-	10	H07RN8-F 3G1	15.5
AP12.50.11.A1	96010678	1 x 220 - 230	No plug	-	Cable guided	5	H07RN8-F 3G1	15.7
AP12.50.11.3	96010897	3 x 200 - 220	No plug	-	-	10	H07RN8-F 4G1	15.9
AP12.50.11.3	96010642	3 x 380 - 440	No plug	-	-	10	H07RN8-F 4G1	15.9
AP12.50.11.A3	96010944	3 x 380 - 440	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.1
AP12.50.11.A3	96010943	3 x 200 - 220	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.1

## Technical data

### Electrical data

#### UNILIFT AP12 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP12.40.04.1	1 x 230	0.7	0.4	3.0	12.5	2770
AP12.40.04.A1						
AP12.40.04.3	3 x 230	0.7	0.4	2.3	9.5	2800
AP12.40.04.A3						
AP12.40.04.3	3 x 400	0.7	0.4	1.2	5.5	2800
AP12.40.04.A3						
AP12.40.06.1	1 x 230	0.9	0.6	4.4	17.3	2785
AP12.40.06.A1						
AP12.40.06.3	3 x 230	0.9	0.6	3.0	15.0	2815
AP12.40.06.A3						
AP12.40.06.3	3 x 400	0.9	0.6	1.6	8.1	2815
AP12.40.06.A3						
AP12.40.08.1	1 x 230	1.3	0.8	5.9	23.0	2780
AP12.40.08.A1						
AP12.40.08.3	3 x 230	1.2	0.8	2.8	18.8	2810
AP12.40.08.A3						
AP12.40.08.3	3 x 400	1.2	0.8	2.1	10.8	2810
AP12.40.08.A3						
AP12.50.11.1	1 x 230	1.7	1.1	8.5	29.9	2760
AP12.50.11.A1						
AP12.50.11.3	3 x 230	1.9	1.2	5.2	29.9	2785
AP12.50.11.A3						
AP12.50.11.3	3 x 400	1.9	1.2	3.2	16.2	2785
AP12.50.11.A3						

#### UNILIFT AP12 60 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP12.40.04.1	1 x 220-230	0.8	0.5	3.7	13.9	3350
AP12.40.04.A1						
AP12.40.04.3	3 x 200-220	0.8	0.4	2.4	9.8	3350
AP12.40.04.A3						
AP12.40.04.3	3 x 380-440	0.8	0.4	1.5	4.7	3350
AP12.40.04.A3						
AP12.40.06.1	1 x 220-230	1.0	0.6	4.6	20.9	3350
AP12.40.06.A1						
AP12.40.06.3	3 x 200-220	1.0	0.6	3.2	14.6	3300
AP12.40.06.A3						
AP12.40.06.3	3 x 380-440	1.0	0.6	1.6	7.0	3370
AP12.40.06.A3						
AP12.40.08.1	1 x 220-230	1.2	0.8	5.8	30.9	3400
AP12.40.08.A1						
AP12.40.08.3	3 x 200-220	1.2	0.8	3.9	19.9	3350
AP12.40.08.A3						
AP12.40.08.3	3 x 380-440	1.2	0.8	1.8	9.2	3400
AP12.40.08.A3						
AP12.50.11.1	1 x 220-230	1.8	1.3	9.0	39.2	3350
AP12.50.11.A1						
AP12.50.11.3	3 x 200-220	1.8	1.3	5.9	28.6	3350
AP12.50.11.A3						
AP12.50.11.3	3 x 380-440	1.8	1.3	2.7	13.8	3350
AP12.50.11.A3						


## Operating conditions

Max. head	18 m
Max. flow rate	32 m <sup>3</sup> /h
Liquid temperature range	0-55 °C <sup>13)</sup>
Liquid pH range	4-10
Liquid requirements	Clean, non-aggressive water and grey wastewater
Max. ambient temperature	55 °C
Max. particle size	12 mm
Max. submersion depth	2 m with 5 m cable 7 m with 10 m cable <sup>14)</sup>
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

<sup>13)</sup> For UNILIFT AP 12, AP 35 and AP 50 without float switch, where the media cannot touch the cable and the plug: up to + 70 °C every 30 min. for time periods below 3 min.

<sup>14)</sup> IEC 60335-2-41 requires 3 m cable length outside of water.

## Dimensions




TM083259

## UNILIFT AP12

Pump type	W [mm]	W1 [mm]	H [mm]	DN2 [inch]
AP12.40.04	216	38	321	Rp 1 1/2
AP12.40.06	216	38	321	Rp 1 1/2
AP12.40.08	216	38	346	Rp 1 1/2
AP12.50.11	241	46	357	Rp 2

## Installation

### Adjustment of cable length for float switch



*One-pump installation with float switch*

The difference in level between start and stop can be adjusted by changing the free cable length between the float switch and the pump handle.


- Increasing the free cable length results in fewer starts/stops and a large difference in level.
- Reducing the free cable length results in more starts/stops and a small difference in level.

In order for the float switch to start and stop the pump, the free cable length must be at minimum 100 mm and maximum 250 mm.

Pump type	Cable length min. 100 mm		Cable length max. 250 mm	
	Start [mm]	Stop [mm]	Start [mm]	Stop [mm] <sup>15)</sup>
UNILIFT AP12.40	360	230	370	100
UNILIFT AP12.50	410	250	380	110

<sup>15)</sup> Minimum stop level during continuous operation or when using an external controller.

### Two-pump installation



*Two-pump installation with four float switches*

UNILIFT AP pumps can be used for parallel installation together with a controller. The example shows an installation with four float switches. The pumps are controlled by the liquid level in the tank.

When the liquid lifts the second float switch from the bottom, the first pump will start. If the liquid rises faster than one pump can manage, the third float switch rises and starts the second pump.

When the bottom float switch is no longer lifted by the liquid, the settable stop delay will set in and both pumps will stop. When the top float switch is lifted by the liquid, the high-level alarm will activate.

## Accessories

Product number	Description
99369644	LC231 (1 pump) without float switch
99369650	LC231 (2 pump controller) without float switch
91427145	Float switch M2 with 5m cable

## 5. Effluent and sewage

### UNILIFT AP35



UNILIFT AP35 is a single-stage, submersible pump designed for pumping drainage water and effluent. The pump is able to handle particles up to 35 mm.

The pump is suitable for permanent installation or can be used as a portable pump. The pump is available with the following options:

- with a float switch fitted for automatic on/off operation between two liquid levels (single-phase pumps)
- with a separate level switch and control box for automatic on/off operation between two liquid levels (three-phase pumps)
- without a level switch for manual on/off operation.

Pumps that are fitted with a float switch can also be used for manual on/off operation. In this case, the float switch must be secured in an upward-facing position.

#### Applications

The pump is suitable for the following applications:

- groundwater lowering
- pumping in drainage collecting wells
- pumping in surface water collecting wells with inflow from, for example, roof gutters, shafts and tunnels
- emptying of, for example, ponds and tanks
- pumping of fibre-containing wastewater from laundries and industries
- effluents from viaducts and underpasses
- pumping of effluents from septic and sludge-treating systems
- pumping of effluents from regular testing of fire fighting systems.

#### Features and benefits of UNILIFT AP

UNILIFT AP has many features:

- robust and sustainable stainless-steel design for all hydraulic parts

- service friendly to extend pump lifetime – quick access to replace wear parts like cable, float switch, shaft sealing, impeller and rotor
- cooling jacket that allows the pump to operate continuously while partially submerged
- included motor protection that reacts to blockage
- longitudinal, water-tight cables and glass-sealed cable socket on the pump that prevents water from entering the motor at damaged cables and allows easy replacement
- highly reliable mechanical shaft seal with an oil chamber that protects the seals and motor.

#### Type key

Example:

UNILIFT AP 35.B.50.08.A1V

Description	
UNILIFT AP	Type range
12	
35	Maximum solids size
50	
Blank - AP pump	Pump type
B - AP Basic	
40	Nominal diameter of the outlet port [mm]
50	
	Power output (P2/100[W])
A - automatic operation (with float switch)	
Blank - manual operation (without float switch)	Level control
1 - single-phase	
3 - three-phase	Motor
V - vortex impeller	Impeller

#### Approvals and markings

##### Approvals



TM075405



TM074611



98507008\_RCM\_MARK



TM075835




99853271



TM074619

## Construction of UNILIFT AP35



The riser pipe has a number of holes enabling efficient cooling of the motor during operation. The cable entry has a socket and plug connection for quick and easy dismantling.

### Outlet port

All UNILIFT AP35 pumps have a threaded Rp 1 1/2 vertical outlet port.

All UNILIFT AP35B pumps have a threaded R 2 horizontal outlet port.

### Motor

The motor is a single- or three-phase asynchronous dry-rotor motor.

Enclosure class	IP68
Insulation class	F (155 °C)
Cable type	H07RN(8)-F

Single-phase motors have built-in thermal protection.  
Manufactured according to EN 60335-2-41.

### Shaft and bearings

The stainless-steel shaft rotates in maintenance-free pre-lubricated ball bearings.

### Impeller

The stainless-steel impeller is a vortex impeller with L-shaped blades and a clearance of 35 mm in the pump housing. The blades are curved backwards to reduce any harmful effects from solid particles and to minimise power consumption. The impeller has a protective cap to prevent the deposit of long-fibred material.

### Shaft seal

The shaft seal is a combination of a mechanical bellows shaft seal and a lip seal with 60 ml oil between. Seal faces are made of silicone carbide.

### Pumped liquids

The pumps are suitable for the below liquids:

- clean, non-aggressive water
- slightly dirty (grey) wastewater.

The open-impeller design ensures free passage of solids up to 35 mm.

### Level switches and control boxes

Level controllers and switches are delivered with the product and are directly connected to the single-phase motors. For three-phase motors, level switch solutions are available with control boxes in between the pump and the level switch. The cable length for the pump and level switch is 10 m. A power supply cable of 0.65 m is connected to the box. The level controller box incorporates a contactor and a motor protection unit. The motor protection unit is preset with the nominal current of the pump.

## Materials

Pos.	Component	Materials	DIN W. - Nr.	AISI
6	Pump housing	Stainless steel	1.4301	304
31	Riser pipe	Stainless steel	1.4301	304
49	Impeller	Stainless steel	1.4301	304
55	Pump sleeve	Stainless steel	1.4401	316
-	Pump shaft - wet end	Stainless steel	1.4301	304
188	Bearings	Heavy-duty pre-lubricated ball bearings		
-	O-rings	NBR rubber		
-	Screws	Stainless steel	1.4301	304
181	Cable	Neoprene		
-	Oil	Shell Odina 15, non-toxic		


### Pump sleeve and housing

The stainless-steel pump sleeve is made in one piece and equipped with an insulated carrying handle. The inlet strainer is clipped onto the pump housing for easy removal in connection with maintenance.

The strainer prevents the passage of large solids and ensures a slow flow into the pump. As a result, most impurities are prevented from entering the pump. The stainless-steel pump housing is fitted with an internal riser pipe ensuring high efficiency.


## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 40 mm and flow of 3.2 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.




TM031879

## Performance curves UNILIFT AP35 50 Hz



## Performance curves UNILIFT AP35 60 Hz



## Product range UNILIFT AP35 50 Hz

Pump type	Product number	Voltage[V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length[m]	Cable type	Net weight [kg/h]
AP35.40.06.1V	96001796	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	13.1
AP35.40.06.A1V	96001777	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	12.7
AP35.40.06.A1V	96010982	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	13.3
AP35.40.08.1V	96001672	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	13.7
AP35.40.08.A1V	96001897	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	13.3
AP35.40.08.A1V	96010983	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	13.9
AP35.40.06.1V	96001808	1 x 230	No plug	-	-	10	H07RN8-F 3G1	13.0
AP35.40.06.A1V	96404183	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	13.2
AP35.40.06.3V	96000169	3 x 400	No plug	-	-	10	H07RN8-F 4G1	13.4
AP35.40.06.3V	96010629	3 x 230	No plug	-	-	10	H07RN8-F 4G1	13.4
AP35.40.06.A3V	96010929	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	14.6
AP35.40.06.A3V	96010960	3 x 230	No plug	✓	Cable guided	10	H07RN8-F 4G1	14.6
AP35.40.08.1V	96001894	1 x 230	No plug	-	-	10	H07RN8-F 3G1	13.5
AP35.40.08.A1V	96404184	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	13.7
AP35.40.08.3V	96001718	3 x 400	No plug	-	-	10	H07RN8-F 4G1	13.9
AP35.40.08.3V	96010631	3 x 230	No plug	-	-	10	H07RN8-F 4G1	13.9
AP35.40.08.A3V	96010931	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	15.1
AP35.40.08.A3V	96010961	3 x 230	No plug	✓	Cable guided	10	H07RN8-F 4G1	15.1
AP35.40.06.A3V	96023875	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	15.0
AP35.40.08.A3V	96023876	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	15.4
AP35.40.06.1V	96001805	1 x 230	Australia	-	-	10	H07RN-F 3G1	13.1
AP35.40.06.A1V	96023932	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	11.9
AP35.40.08.A1V	96023933	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	13.7

**Product range UNILIFT AP35 60 Hz**

Pump type	Product number	Voltage[V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length [m]	Cable type	Net weight [kg]
AP35.40.06.1V	96010671	1 x 220-230	No plug	-	-	10	H07RN8-F 3G1	13.0
AP35.40.06.A1V	96010666	1 x 220-230	No plug	-	Cable guided	5	H07RN8-F 3G1	12.6
AP35.40.06.3V	96010643	3 x 380-440	No plug	-	-	10	H07RN8-F 4G1	13.4
AP35.40.06.3V	96010898	3 x 200-220	No plug	-	-	10	H07RN8-F 4G1	13.4
AP35.40.08.1V	96010677	1 x 220-230	No plug	-	-	10	H07RN8-F 3G1	13.5
AP35.40.08.3V	96010644	3 x 380-440	No plug	-	-	10	H07RN8-F 4G1	13.9
AP35.40.08.A1V	96010672	1 x 220-230	No plug	-	Cable guided	5	H07RN8-F 3G1	13.1

## Technical data

### Electrical data

#### UNILIFT AP35 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP35.40.06.1.V	1 x 230	0.9	0.6	4.0	17.3	2810
AP35.40.06.A1.V	1 x 230	0.9	0.6	4.0	17.3	2810
AP35.40.06.3.V	3 x 230	0.9	0.6	2.6	15.0	2830
AP35.40.06.A3.V	3 x 230	0.9	0.6	2.6	15.0	2830
AP35.40.06.3.V	3 x 400	0.9	0.6	1.6	8.1	2830
AP35.40.06.A3.V	3 x 400	0.9	0.6	1.6	8.1	2830
AP35.40.08.1.V	1 x 230	1.2	0.7	5.5	23.0	2795
AP35.40.08.A1.V	1 x 230	1.2	0.7	5.5	23.0	2795
AP35.40.08.3.V	3 x 230	1.1	0.7	3.1	18.8	2820
AP35.40.08.A3.V	3 x 230	1.1	0.7	3.1	18.8	2820
AP35.40.08.3.V	3 x 400	1.2	0.7	2.0	10.8	2820
AP35.40.08.A3.V	3 x 400	1.2	0.7	2.0	10.8	2820

#### UNILIFT AP35 60 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP35.40.06.1.V	1 x 220-230	1.2	0.7	5.2	22.0	3330
AP35.40.06.A1.V	1 x 220-230	1.2	0.7	5.2	22.0	3330
AP35.40.06.3.V	3 x 200-220	1.1	0.6	3.2	14.6	3300
AP35.40.06.3.V	3 x 380-440	1.1	0.7	1.4	7.0	3330
AP35.40.08.1.V	1 x 220-230	1.3	0.9	6.0	30.9	3300
AP35.40.08.A1.V	1 x 220-230	1.3	0.9	6.0	30.9	3300
AP35.40.08.3.V	3 x 380-440	1.4	0.9	2.2	9.2	3300


### Operating conditions

Max. head	13 m
Max. flow rate	21.6 m <sup>3</sup> /h
Liquid temperature range	0-55 °C
Liquid pH range	4-10
Liquid requirements	Clean, non-aggressive water and grey wastewater
Max. ambient temperature	55 °C
Max. particle size through the inlet strainer	35 mm
Max. installation depth	2 m with 5 m cable 7 m with 10 m cable
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

16) For UNILIFT AP 12, AP 35 and AP 50 without float switch, where the media cannot touch the cable and the plug: up to + 70 °C every 30 min. for time periods below 3 min.

17) IEC 60335-2-41 requires 3 m cable length outside of water.

## Dimensions




TM083260

### UNILIFT AP35

Pump type	W [mm]	W1 [mm]	H [mm]	DN2 [inch]
AP35.40.06	216	46	376	Rp 1 1/2
AP35.40.08	216	46	410	Rp 1 1/2

## Installation

### Adjustment of cable length for float switch



*One-pump installation with float switch*

The difference in level between start and stop can be adjusted by changing the free cable length between the float switch and the pump handle.


- Increasing the free cable length results in fewer starts/stops and a large difference in level.
- Reducing the free cable length results in more starts/stops and a small difference in level.

In order for the float switch to start and stop the pump, the free cable length must be minimum 100 mm and maximum 250 mm.

Pump type	Cable length min. 100 mm		Cable length max. 250 mm	
	Start [mm]	Stop [mm]	Start [mm]	Stop [mm] <sup>18)</sup>
UNILIFT AP35	440	280	450	155

<sup>18)</sup> Minimum stop level during continuous operation or when using an external controller.

### Two-pump installation



*Two-pump installation with four float switches*

UNILIFT AP pumps can be used for parallel installation together with a controller. The example shows an installation with four float switches. The pumps are controlled by the liquid level in the tank.

When the liquid lifts the second float switch from the bottom, the first pump will start. If the liquid rises faster than one pump can manage, the third float switch rises and starts the second pump.

When the bottom float switch is no longer lifted by the liquid, the settable stop delay will set in and both pumps will stop. When the top float switch is lifted by the liquid, the high-level alarm will activate.

## Accessories

Product number	Description
99369644	LC231 (1 pump) without float switch
99369650	LC231 (2 pump controller) without float switch
91427145	Float switch M2 with 5m cable

## UNILIFT AP35B



The UNILIFT AP35B pump is a single-stage, submersible pump designed for pumping effluent. The pump has a side outlet allowing easy adaptation to existing pipes including auto coupling systems. The pump is able to handle particles up to 35 mm.

The pump is suitable for permanent installation or can be used as a portable pump. The pump is available with the following options:

- with a float switch fitted for automatic on/off operation between two liquid levels (single-phase pumps)
- with a separate level switch and control box for automatic on/off operation between two liquid levels (three-phase pumps)
- without a level switch for manual on/off operation.

Pumps that are fitted with a float switch can also be used for manual on/off operation. In this case, the float switch must be secured in an upward-facing position.

### Applications

The pump is suitable for the following applications:

- groundwater lowering
- pumping in drainage collecting wells
- pumping in surface water collecting wells with inflow from, for example, roof gutters, shafts and tunnels
- emptying of, for example, ponds and tanks
- pumping of fibre-containing wastewater from laundries and industries
- pumping of domestic effluents from septic and sludge-treating systems
- pumping of domestic effluent without discharge from water closets.

### Features and benefits of UNILIFT AP35B

UNILIFT AP35B has many beneficial features:

- designed for more demanding effluent pumping
- high performance, high reliability and low maintenance
- UNILIFT AP35B is designed for effluent applications
- included motor protection on single phase pumps that reacts to blockage
- Service friendly – quick access to change wear parts like cable, shaft sealing, impeller and rotor.

### Type key

Example:

UNILIFT AP 35.B.50.08.A1V

Description	
UNILIFT AP	Type range
12	
35	Maximum solids size
50	
Blank - AP pump	Pump type
B - AP Basic	
40	Nominal diameter of the outlet port [mm]
50	
	Power output (P2/100[W])
A - automatic operation (with float switch)	Level control
Blank - manual operation (without float switch)	
1 - single-phase	Motor
3 - three-phase	
V - vortex impeller	Impeller

### Approvals and markings

#### Approvals



TM075405



TM074611



98507008\_RCM\_MARK



TM075835




9853271



TM074619

## Construction of UNILIFT AP35B



## Materials

Pos.	Component	Materials	DIN W. - Nr.	AISI
6	Pump housing	Stainless steel	1.4301	304
-	Riser pipe	Stainless steel	1.4301	304
49	Impeller	Stainless steel	1.4301	304
150	Motor unit complete	Parts in contact with liquid: Stainless steel	1.4401	316
-	Pump shaft - wet end	Stainless steel	1.4301	304
181	Motor cable	Neoprene		
-	O-rings	NBR rubber		
-	Spring	Stainless steel	1.4310	
50	Pump inlet	Stainless steel	1.4301	304
84	Ring stand	Composite		
-	Oil	Shell Odina 15, non-toxic		

## Pump sleeve and housing

The stainless-steel pump sleeve is made in one piece and equipped with an insulated carrying handle. The inlet strainer is clipped onto the pump housing for easy removal in connection with maintenance.

The strainer prevents the passage of large solids and ensures a slow flow into the pump. As a result, most impurities are prevented from entering the pump. The stainless-steel pump housing is fitted with an internal riser pipe ensuring high efficiency.

The riser pipe has a number of holes enabling efficient cooling of the motor during operation. The cable entry has a socket and plug connection for quick and easy dismantling.

## Outlet port

All UNILIFT AP35B pumps have a threaded R 2 horizontal outlet port.

## Motor

The motor is a single- or three-phase asynchronous dry-rotor motor.

Enclosure class	IP68
Insulation class	F (155 °C)
Cable type	H07RN(8)-F

Single-phase motors have built-in thermal protection.

Manufactured according to EN 60335-2-41.

## Shaft and bearings

The stainless-steel shaft rotates in maintenance-free pre-lubricated ball bearings.

## Impeller

The stainless-steel impeller is a vortex impeller with L-shaped blades and a clearance of 35 mm in the pump housing. The blades are curved backwards to reduce any harmful effects from solid particles and to minimise power consumption. The impeller has a protective cap to prevent the deposit of long-fibred material.

## Shaft seal

The shaft seal is a combination of a mechanical bellows shaft seal and a lip seal with 60 ml oil between. Seal faces are made of silicone carbide.

## Pumped liquids

The pumps are suitable for the below liquids:

- clean, non-aggressive water
- slightly dirty (grey) wastewater.


The open-impeller design ensures free passage of solids up to 35 mm.

## Level switches

Level controllers and switches are delivered with the product and are directly connected to the single-phase motors.


## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 50 mm and a flow of 5 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.




TM066589

### Performance curves UNILIFT AP35B 50 Hz



### Performance curves UNILIFT AP35B 60 Hz



### Product range UNILIFT AP35B 50 Hz

Pump type	Product number	Voltage[V]	Plug type	Float switch type	Cable length [m]	Cable type	Net weight [kg]
AP35B.50.06.1V	96004563	1 x 230	SCHUKO	-	10	H07RN8-F 3G1	10.3
AP35B.50.06.A1V	96004562	1 x 230	SCHUKO	Cable guided	5	H07RN8-F 3G1	9.9
AP35B.50.06.A1V	96468356	1 x 230	SCHUKO	Cable guided	10	H07RN8-F 3G1	10.5
AP35B.50.08.1V	96004575	1 x 230	SCHUKO	-	10	H07RN8-F 3G1	10.8
AP35B.50.08.A1V	96004574	1 x 230	SCHUKO	Cable guided	5	H07RN8-F 3G1	10.4
AP35B.50.08.A1V	96468355	1 x 230	SCHUKO	Cable guided	10	H07RN8-F 3G1	11.0
AP35B.50.06.3V	96004565	3 x 400	No plug	-	5	H07RN8-F 4G1	9.9
AP35B.50.06.3V	96468190	3 x 400	No plug	-	10	H07RN8-F 4G1	10.5
AP35B.50.08.3V	96004577	3 x 400	No plug	-	5	H07RN8-F 4G1	10.5
AP35B.50.08.3V	96468193	3 x 400	No plug	-	10	H07RN8-F 4G1	11.1
AP35B.50.08.3V	96007152	3 x 230	No plug	-	5	H07RN8-F 4G1	10.5

### Product range UNILIFT AP35B 60 Hz

Pump type	Product number	Voltage[V]	Plug type	Float switch type	Cable length [m]	Cable type	Net weight [kg]
AP35B.50.06.1V	96004569	1 x 220-230	SCHUKO	-	10	H07RN8-F 3G1	10.2
AP35B.50.06.A1V	96004568	1 x 220-230	SCHUKO	Cable guided	5	H07RN8-F 3G1	9.8
AP35B.50.06.3V	96004571	3 x 200-220	No plug	-	5	H07RN8-F 4G1	9.9
AP35B.50.08.1V	96004581	1 x 220-230	SCHUKO	-	10	H07RN8-F 3G1	10.7
AP35B.50.08.A1V	96004580	1 x 220-230	SCHUKO	Cable guided	5	H07RN8-F 3G1	9.8
AP35B.50.08.3V	96004583	3 x 200-220	No plug	-	5	H07RN8-F 4G1	10.5

## Technical data

### Electrical data

#### UNILIFT AP35B 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP35B.50.06.1V	1 x 230	1.0	0.66	4.4	13.8	2810
AP35B.50.06.A1V	1 x 230	1.0	0.66	4.4	13.8	2810
AP35B.50.06.3V	3 x 400	1.0	0.63	1.55	8.0	2830
AP35B.50.08.1V	1 x 230	1.25	0.71	5.44	18.4	2795
AP35B.50.08.A1V	1 x 230	1.25	0.71	5.44	18.4	2795
AP35B.50.08.3V	3 x 230	1.25	0.78	3.52	18.8	2820
AP35B.50.08.3V	3 x 400	1.25	0.78	1.98	10.8	2820

#### UNILIFT AP35B 60 Hz


Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP35B.50.06.1V	1 x 220-230	1.29	0.75	5.91	22.0	3330
AP35B.50.06.A1V	1 x 220-230	1.29	0.75	5.91	22.0	3330
AP35B.50.06.3V	3 x 200-220	1.21	0.66	3.71	4.39	3300
AP35B.50.08.1V	1 x 220-230	1.47	1.02	6.74	30.9	3300
AP35B.50.08.A1V	1 x 220-230	1.47	1.02	6.74	30.9	3300
AP35B.50.08.3V	3 x 200-220	1.48	0.95	4.50	4.87	3300

### Operating conditions

Max. head	13 m
Max. flow rate	21.6 m <sup>3</sup> /h
Liquid temperature range	0-40 °C
Liquid pH range	4-10
Liquid requirements	Clean, non-aggressive water and grey wastewater
Max. ambient temperature	40 °C
Max. particle size through the inlet strainer	35 mm
Max. installation depth	2 m with 5 m cable 7 m with 10 m cable <sup>19)</sup>
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

<sup>19)</sup> IEC 60335-2-41 requires 3 m cable length outside of water.

## Dimensions



TM083388

### UNILIFT AP35B

Pump type	L1 [mm]	W1 [mm]	H1 [mm]	H2 [mm]	H3 [mm]	DN2 [inch]
AP35B.50.06	234	210	73	116	443	Rp 2
AP35B.50.08	234	210	73	116	468	Rp 2

## Accessories

The following are recommended accessories for UNILIFT APB pumps.

Product number	Description
96023844	Non-return valve PVC, ball type 2"
97644486	Auto-coupling set Rp 2"
99369644	LC231 (1 pump) without float switch
99369650	LC231 (2 pump controller) without float switch
91427145	Float switch M2 with 5m cable

## UNILIFT AP50



TM079225

UNILIFT AP50 is a submersible pump designed for pumping effluent and sewage. The pump is able to handle particles up to 50 mm.

The pump is suitable for permanent installation or can be used as a portable pump. The pump is available with the following options:

- with a float switch fitted for automatic on/off operation between two liquid levels (single-phase pumps)
- with a separate level switch and control box for automatic on/off operation between two liquid levels (three-phase pumps)
- without a level switch for manual on/off operation.

Pumps that are fitted with a float switch can also be used for manual on/off operation. In this case, the float switch must be secured in an upward-facing position.

### Applications

The pump is suitable for the following applications:

- groundwater lowering
- pumping in drainage collecting wells
- pumping in surface water collecting wells with inflow from, for example, roof gutters, shafts and tunnels
- emptying of, for example, ponds and tanks
- pumping of fibre-containing wastewater from laundries and industries
- pumping of domestic effluents from septic and sludge-treating systems
- pumping of domestic effluent with and without discharge from water closets.

### Features and benefits of UNILIFT AP

UNILIFT AP has many features:

- robust and sustainable stainless-steel design for all hydraulic parts
- service friendly to extend pump lifetime – quick access to replace wear parts like cable, float switch, shaft sealing, impeller and rotor
- cooling jacket that allows the pump to operate continuously while partially submerged

- included motor protection that reacts to blockage
- longitudinal, water-tight cables and glass-sealed cable socket on the pump that prevents water from entering the motor at damaged cables and allows easy replacement
- highly reliable mechanical shaft seal with an oil chamber that protects the seals and motor.

### Type key

Example:

UNILIFT AP 35.B.50.08.A1V

Description	
UNILIFT AP	Type range
12	
35	Maximum solids size
50	
Blank - AP pump	Pump type
B - AP Basic	
40	Nominal diameter of the outlet port [mm]
50	
	Power output (P2/100[W])
A - automatic operation (with float switch)	Level control
Blank - manual operation (without float switch)	
1 - single-phase	Motor
3 - three-phase	
V - vortex impeller	Impeller

### Approvals and markings

#### Approvals



TM075405



TM074611



98507008\_RCM\_MARK



TM075335




98653271



TM074619

## Construction of UNILIFT AP50



## Materials

Pos.	Component	Materials	DIN W. - Nr.	AISI
6	Pump housing	Stainless steel	1.4301	304
31	Riser pipe	Stainless steel	1.4301	304
49	Impeller	Stainless steel	1.4301	304
55	Pump sleeve	Stainless steel	1.4401	316
-	Pump shaft - wet end	Stainless steel	1.4301	304
188	Bearings	Heavy-duty pre-lubricated ball bearings		
-	O-rings	NBR rubber		
-	Screws	Stainless steel	1.4301	304
181	Cable	Neoprene		
-	Oil	Shell Odina 15, non-toxic		

## Outlet port

All UNILIFT AP50 pumps have a threaded Rp 2 vertical outlet port.

## Pump sleeve and housing

The stainless-steel pump sleeve is made in one piece and equipped with an insulated carrying handle. The inlet strainer is clipped onto the pump housing for easy removal in connection with maintenance.

The strainer prevents the passage of large solids and ensures a slow flow into the pump. As a result, most impurities are prevented from entering the pump. The stainless-steel pump housing is fitted with an internal riser pipe ensuring high efficiency.

The riser pipe has a number of holes enabling efficient cooling of the motor during operation. The cable entry has a socket and plug connection for quick and easy dismantling.

## Motor

The motor is a single- or three-phase asynchronous dry-rotor motor.

Enclosure class	IP68
Insulation class	F (155 °C)
Cable type	H07RN(8)-F

Single-phase motors have built-in thermal protection. Manufactured according to EN 60335-2-41.

## Shaft and bearings

The stainless-steel shaft rotates in maintenance-free pre-lubricated ball bearings.

## Impeller

The stainless-steel impeller is a vortex impeller with L-shaped blades and a clearance of 50 mm in the pump housing. The blades are curved backwards to reduce any harmful effects from solid particles and to minimise power consumption. The impeller has a protective cap to prevent the deposit of long-fibred material.

## Shaft seal

The shaft seal is a combination of a mechanical bellows shaft seal and a lip seal with 60 ml oil between. Seal faces are made of silicone carbide.

## Pumped liquids

The pumps are suitable for the following liquids:

- liquids containing fibres from, for example, light industry and laundries
- effluents from, for example, viaducts and underpasses
- domestic wastewater with toilet discharge from pipes and water closets below sewer level, outdoor pump installations.


The open-impeller design ensures free passage of solids up to 50 mm.

## Level switches and control boxes

Level controllers and switches are delivered with the product and are directly connected to the single-phase motors. For three-phase motors, level switch solutions are available with control boxes in between the pump and the level switch. The cable length for the pump and level switch is 10 m. A power supply cable of 0.65 m is connected to the box. The level controller box incorporates a contactor and a motor protection unit. The motor protection unit is preset with the nominal current of the pump.


## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 50 mm and a flow of 5 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.




TM031880

## Performance curves UNILIFT AP50 50 Hz



## Performance curves UNILIFT AP50 60 Hz



## Product range UNILIFT AP50 50 Hz

Pump type	Product number	Voltage[V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length[m]	Cable type	Net weight [kg]
AP50.50.08.1V	96010595	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	15.9
AP50.50.08.A1V	96010584	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	15.5
AP50.50.08.A1V	96010984	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	16.1
AP50.50.11.1V	96010577	1 x 230	SCHUKO	-	-	10	H07RN8-F 3G1	16.8
AP50.50.11.A1V	96010566	1 x 230	SCHUKO	-	Cable guided	5	H07RN8-F 3G1	16.9
AP50.50.11.A1V	96010985	1 x 230	SCHUKO	-	Cable guided	10	H07RN8-F 3G1	16.9
AP50.50.08.1V	96010599	1 x 230	No plug	-	-	10	H07RN8-F 3G1	15.8
AP50.50.08.A1V	96404185	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	16.0
AP50.50.08.3V	96010563	3 x 400	No plug	-	-	10	H07RN8-F 4G1	16.2
AP50.50.08.3V	96010632	3 x 230	No plug	-	-	10	H07RN8-F 4G1	16.2
AP50.50.08.A3V	96010933	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.5
AP50.50.08.A3V	96010962	3 x 230	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.5
AP50.50.11.1V	96010581	1 x 230	No plug	-	-	10	H07RN8-F 3G1	16.6
AP50.50.11.A1V	96404186	1 x 230	No plug	-	Cable guided	10	H07RN8-F 3G1	16.9
AP50.50.11.3V	96010562	3 x 400	No plug	-	-	10	H07RN8-F 4G1	16.7
AP50.50.11.3V	96010633	3 x 230	No plug	-	-	10	H07RN8-F 4G1	16.7
AP50.50.11.A3V	96010935	3 x 400	No plug	✓	Cable guided	10	H07RN8-F 4G1	17.9
AP50.50.08.A3V	96023877	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	17.8
AP50.50.11.A3V	96023878	3 x 400	CEE	✓	Cable guided	10	H07RN8-F 4G1	18.1
AP50.50.08.1V	96010598	1 x 230	Australia	-	-	10	H07RN-F 3G1	15.9
AP50.50.11.1V	96010580	1 x 230	Australia	-	-	10	H07RN-F 3G1	16.8
AP50.50.08.A1V	96023934	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	16.1
AP50.50.11.A1V	96023935	1 x 230	Australia	-	Cable guided	10	H07RN-F 3G1	17.0

**Product range UNILIFT AP50 60 Hz**

Pump type	Product number	Voltage[V]	Plug type	Control box with 0.65 m supply cable	Float switch type	Cable length[m]	Cable type	Net weight [kg]
AP50.50.08.1.V	96010688	1 x 220-230	No plug	-	-	10	H07RN8-F 3G1	15.8
AP50.50.08.3.V	96010647	3 x 380-440	No plug	-	-	10	H07RN8-F 4G1	16.2
AP50.50.08.A1.V	96010684	1 x 220-230	No plug	-	Cable guided	5	H07RN8-F 3G1	15.8
AP50.50.11.1.V	96010694	1 x 220-230	No plug	-	-	10	H07RN8-F 3G1	16.3
AP50.50.11.3.V	96010645	3 x 380-440	No plug	-	-	10	H07RN8-F 4G1	16.7
AP50.50.11.3.V	96010901	3 x 220-220	No plug	-	-	10	H07RN8-F 4G1	16.7
AP50.50.11.A1.V	96010690	1 x 220-230	No plug	-	Cable guided	5	H07RN8-F 3G1	16.5
AP50.50.11.A3.V	96010955	3 x 220-220	No plug	-	Cable guided	10	H07RN8-F 4G1	17.9
AP50.50.11.A3.V	96010956	3 x 380-440	No plug	-	Cable guided	10	H07RN8-F 4G1	17.9

## Technical data

### Electrical data

#### UNILIFT AP50 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP50.50.08.1V	1 x 230	1.3	0.8	5.9	23.0	2790
AP50.50.08.A1V	1 x 230	1.3	0.8	5.9	23.0	2790
AP50.50.08.3V	3 x 230	1.2	0.8	3.3	18.8	2800
AP50.50.08.A3V	3 x 230	1.2	0.8	3.3	18.8	2800
AP50.50.08.3V	3 x 400	1.2	0.8	2.0	10.8	2820
AP50.50.08.A3V	3 x 400	1.2	0.8	2.0	10.8	2820
AP50.50.11.1V	1 x 230	1.6	1.1	8.0	29.9	2800
AP50.50.11.A1V	1 x 230	1.6	1.1	8.0	29.9	2800
AP50.50.11.3V	3 x 230	1.6	1.2	4.9	29.3	2780
AP50.50.11.3V	3 x 400	1.9	1.2	3.0	16.2	2785
AP50.50.11.A3V	3 x 400	1.9	1.2	3.0	16.2	2785

#### UNILIFT AP50 60 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP50.50.08.1V	1 x 220-230	1.4	1.0	6.3	30.9	3400
AP50.50.08.A1V	1 x 220-230	1.4	1.0	6.3	30.9	3400
AP50.50.08.3V	3 x 380-440	1.4	1.0	2.1	9.2	3400
AP50.50.11.1V	1 x 220-230	1.8	1.2	8.4	39.2	3360
AP50.50.11.A1V	1 x 220-230	1.8	1.2	8.4	39.2	3360
AP50.50.11.3V	3 x 200-220	1.6	1.2	6.0	28.6	3360
AP50.50.11.A3V	3 x 200-220	1.6	1.2	5.5	28.6	3360
AP50.50.11.3V	3 x 380-440	1.8	1.3	2.6	13.8	3360
AP50.50.11.A3V	3 x 380-440	1.8	1.3	2.6	13.8	3360


### Operating conditions

Max. head	13 m
Max. flow rate	32 m <sup>3</sup> /h
Liquid temperature range	0-55 °C
Liquid pH range	4-10
Liquid requirements	Liquids containing fibres, effluents and domestic wastewater with toilet discharge
Max. ambient temperature	55 °C
Max. particle size through the inlet strainer	50 mm
Max. submersion depth	2 m with 5 m cable 7 m with 10 m cable
Automatic float switch	Type name extension A
Special versions on request	Other voltages and/or frequencies

20) For UNILIFT AP 12, AP 35 and AP 50 without float switch, where the media cannot touch the cable and the plug: up to + 70 °C every 30 min. for time periods below 3 min.

21) IEC 60335-2-41 requires 3 m cable length outside of water.

## Dimensions



TM083260

## UNILIFT AP50

Pump type	H [mm]	W [mm]	W1 [mm]	DN2 [inch]
AP50.50	436	241	46	Rp 2

## Accessories

Product number	Description
99369644	LC231 (1 pump) without float switch
99369650	LC231 (2 pump controller) without float switch
91427145	Float switch M2 with 5m cable

## UNILIFT AP50B



UNILIFT AP50B is a submersible pump designed for pumping effluent. The pump has a side outlet allowing easy adaptation to existing pipes including auto coupling systems. The pump is able to handle particles up to 50 mm.

The pump is suitable for permanent installation or can be used as a portable pump. The pump is available with the following options:

- with a float switch fitted for automatic on/off operation between two liquid levels (single-phase pumps)
- with a separate level switch and control box for automatic on/off operation between two liquid levels (three-phase pumps)
- without a level switch for manual on/off operation.

Pumps that are fitted with a float switch can also be used for manual on/off operation. In this case, the float switch must be secured in an upward-facing position.

### Applications

The pump is suitable for the following applications:

- groundwater lowering
- pumping in drainage collecting wells
- pumping in surface water collecting wells with inflow from, for example, roof gutters, shafts and tunnels
- emptying of, for example, ponds and tanks
- pumping of fibre-containing wastewater from laundries and industries
- pumping of domestic effluents from septic and sludge-treating systems
- pumping of domestic effluent without discharge from water closets.

### Features and benefits of UNILIFT AP50B

UNILIFT AP50B has many beneficial features:

- designed for more demanding effluent and sewage pumping
- high performance, high reliability and low maintenance
- UNILIFT AP50B is designed for effluent applications
- UNILIFT AP50B is certified EN 12050-1 for sewage applications
- included motor protection that reacts to blockage
- service friendly – quick access to replace wear-parts like cable, shaft sealing, impeller and rotor.

### Type key

Example:

UNILIFT AP 35.B.50.08.A1V

Description	
UNILIFT AP	Type range
12	
35	Maximum solids size
50	
Blank - AP pump	Pump type
B - AP Basic	
40	Nominal diameter of the outlet port [mm]
50	
	Power output (P2/100[W])
A - automatic operation (with float switch)	
Blank - manual operation (without float switch)	Level control
1 - single-phase	Motor
3 - three-phase	
V - vortex impeller	Impeller

### Approvals and markings

#### Approvals



TM075405



TM074611



98507008\_RCM\_MARK



TM075835




99853271



TM074619

## Construction of UNILIFT AP50B



## Materials

Pos.	Component	Materials	DIN W. - Nr.	AISI
6	Pump housing	Stainless steel	1.4301	304
-	Riser pipe	Stainless steel	1.4301	304
49	Impeller	Stainless steel	1.4301	304
150	Motor unit complete	Parts in contact with liquid: Stainless steel	1.4401	316
-	Pump shaft - wet end	Stainless steel	1.4301	304
181	Motor cable	Neoprene		
-	O-rings	NBR rubber		
-	Spring	Stainless steel	1.4310	
50	Pump inlet	Stainless steel	1.4301	304
84	Ring stand	Composite		
-	Oil	Shell Odina 15, non-toxic		

## Pump housing

UNILIFT AP50B has a pump housing with an outstanding design for submersible wastewater pumps resulting in a high head.

The pump housing is made of a steel tube with a smooth surface and a hydraulically correct shape, ensuring free passage of particles.

The ring stand, pump inlet and pump housing are fastened to the motor by means of four springs, enabling quick and easy dismantling.

## Outlet port

All UNILIFT AP50B pumps have a threaded R 2 horizontal outlet port.

## Motor

The motor is a single- or three-phase asynchronous dry-rotor motor.

Enclosure class	IP68
Insulation class	F (155 °C)
Cable type	H07RN(8)-F

Single-phase motors have built-in thermal protection.  
Manufactured according to EN 60335-2-41.

## Shaft and bearings

The stainless-steel shaft rotates in maintenance-free pre-lubricated ball bearings.

## Impeller

The stainless-steel impeller is a vortex impeller with L-shaped blades and a clearance of 50 mm in the pump housing. The blades are curved backwards to reduce any harmful effects from solid particles and to minimise power consumption. The impeller has a protective cap to prevent the deposit of long-fibred material.

## Shaft seal

The shaft seal is a combination of a mechanical bellows shaft seal and a lip seal with 60 ml oil between. Seal faces are made of silicone carbide.

## Pumped liquids

The pumps are suitable for the following liquids:

- liquids containing fibres from, for example, light industry and laundries
- effluents from, for example, viaducts and underpasses
- domestic wastewater with toilet discharge from pipes and water closets below sewer level, outdoor pump installations.


The open-impeller design ensures free passage of solids up to 50 mm.

## Level switches

Level controllers and switches are delivered with the product and are directly connected to the single-phase motors.


## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of 50 mm and a flow of 5 m<sup>3</sup>/h, so that a self-cleaning velocity of v=0, 7 m/s is covered. The overview is only intended as a guide. Grundfos is not liable for installations that do not comply with the overview. Pressure loss of a non-return valve and a gate valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.




TM069500

## Performance curves UNILIFT AP50B 50 Hz



## Performance curves UNILIFT AP50B 60 Hz



## Product range UNILIFT AP50B 50 Hz

Pump type	Product number	Voltage[V]	Plug type	Float switch type	Cable length[m]	Cable type	Net weight [kg]
AP50B.50.08.1V	96004587	1 x 230	SCHUKO	-	10	H07RN8-F 3G1	11.4
AP50B.50.08.A1V	96004586	1 x 230	SCHUKO	Cable guided	5	H07RN8-F 3G1	11.0
AP50B.50.08.A1V	96468354	1 x 230	SCHUKO	Cable guided	10	H07RN8-F 3G1	11.6
AP50B.50.11.1V	96004599	1 x 230	SCHUKO	-	10	H07RN8-F 3G1	11.8
AP50B.50.11.A1V	96004598	1 x 230	SCHUKO	Cable guided	5	H07RN8-F 3G1	11.3
AP50B.50.11.A1V	96468352	1 x 230	SCHUKO	Cable guided	10	H07RN8-F 3G1	12.0
AP50B.50.08.A1V	99972781	1 x 230	No plug	Cable guided	10	H07RN8-F 3G1	11.5
AP50B.50.08.3V	96004589	3 x 400	No plug	-	5	H07RN8-F 4G1	9.3
AP50B.50.08.3V	96007151	3 x 230	No plug	-	5	H07RN8-F 4G1	9.3
AP50B.50.08.3V	96468194	3 x 400	No plug	-	10	H07RN8-F 4G1	10.0
AP50B.50.11.1V	92532143	1 x 230	No plug	-	10	H07RN8-F 3G1	11.7
AP50B.50.11.A1V	99972805	1 x 230	No plug	Cable guided	10	H07RN8-F 3G1	11.9
AP50B.50.11.3V	96004601	3 x 400	No plug	-	5	H07RN8-F 4G1	11.4
AP50B.50.11.3V	96007153	3 x 230	No plug	-	5	H07RN8-F 4G1	11.4
AP50B.50.11.3V	96468195	3 x 400	No plug	-	10	H07RN8-F 4G1	12.1
AP50B.50.15.3V	96004609	3 x 400	No plug	-	5	H07RN8-F 4G1	12.0
AP50B.50.15.3V	96468196	3 x 400	No plug	-	10	H07RN8-F 4G1	12.7

## Product range UNILIFT AP50B 60 Hz

Pump type	Product number	Voltage[V]	Plug type	Float switch type	Cable length[m]	Cable type	Net weight [kg]
AP50B.50.08.A1V	96004593	1 x 220-230	SCHUKO	-	5	H07RN8-F 3G1	10.8
AP50B.50.08.A1V	96004592	1 x 220-230	SCHUKO	Cable guided	10	H07RN8-F 3G1	11.6
AP50B.50.11.1V	96004604	1 x 220-230	SCHUKO	Cable guided	10	H07RN8-F 3G1	12.0
AP50B.50.11.A1V	96004605	1 x 220-230	SCHUKO	-	5	H07RN8-F 3G1	11.2
AP50B.50.08.3V	96004595	3 x 200-220	No plug	-	5	H07RN8-F 4G1	9.3
AP50B.50.11.3V	96004607	3 x 200-220	No plug	-	5	H07RN8-F 4G1	11.4
AP50B.50.15.3V	96004611	3 x 200-220	No plug	-	5	H07RN8-F 4G1	12.0

## Technical data

### Electrical data

#### UNILIFT AP50B 50 Hz

Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP50B.50.08.1V	1 x 230	1.20	0.74	5.37	23.0	2790
AP50B.50.08.A1V	1 x 230	1.20	0.74	5.37	23.0	2790
AP50B.50.08.3V	3 x 230	1.25	0.80	3.53	18.8	2810
AP50B.50.08.3V	3 x 400	1.25	0.80	1.98	10.8	2810
AP50B.50.11.1V	1 x 230	1.75	1.21	8.00	29.9	2760
AP50B.50.11.A1V	1 x 230	1.75	1.21	8.00	29.9	2760
AP50B.50.11.3V	3 x 400	1.75	1.31	2.81	16.2	2785
AP50B.50.15.3V	3 x 400	2.15	1.50	3.70	23.1	2785

#### UNILIFT AP50B 60 Hz


Pump type	Voltage[V]	P1 [kW]	P2 [kW]	I <sub>n</sub> [A]	I <sub>start</sub> [A]	Speed [rpm]
AP50B.50.08.1V	1 x 220-230	1.40	1.00	6.40	30.9	3400
AP50B.50.08.A1V	1 x 220-230	1.40	1.00	6.40	30.9	3400
AP50B.50.08.3V	3 x 200-220	1.31	0.84	4.20	19.9	3400
AP50B.50.11.1V	1 x 220-230	1.80	1.20	8.42	39.2	3360
AP50B.50.11.A1V	1 x 220-230	1.80	1.20	8.42	39.2	3360
AP50B.50.11.3V	3 x 200-220	1.73	1.30	5.60	28.6	3360
AP50B.50.15.3V	3 x 200-220	1.94	1.46	6.90	36.7	3360

### Operating conditions

Max. head	18
Max. flow rate	29 m <sup>3</sup> /h
Liquid temperature range	0-40 °C
Liquid pH range	4-10
Liquid requirements	Liquids containing fibres, effluents and domestic wastewater with toilet discharge
Max. ambient temperature	40 °C
Max. particle size through the inlet strainer	50 mm
Max. installation depth	2 m with 5 m cable 7 m with 10 m cable
Automatic float switch:	Type name extension A
Special versions on request	Other voltages and/or frequencies

<sup>22)</sup> IEC 60335-2-41:2012 requires 3 m cable length outside of water.

## Dimensions



TM083388

## UNILIFT AP50B

Pump type	H1 [mm]	H1 [mm]	H3 [mm]	L1 [mm]	W1 [mm]	DN2 [inch]
AP50B.50	73	116	468	234	210	Rp 2

## Accessories

The following are recommended accessories for UNILIFT APB pumps.

Product number	Description
96023844	Non-return valve PVC, ball type 2"
97644486	Auto-coupling set Rp 2"
99369644	LC231 (1 pump) without float switch
99369650	LC231 (2 pump controller) without float switch
91427145	Float switch M2 with 5m cable

## UNILIFT APG



TM081489

The UNILIFT APG pump is a single-stage submersible pump designed for pumping effluent and sewage. The pump is suitable for the following applications:

- Pumping of domestic wastewater from any sanitary appliances, such as showers, bathtubs, kitchen sinks, washing machines, dishwashers and water closets.
- All greywater and blackwater from households.

### Features and benefits

The main benefits of the UNILIFT APG are the following:

- high pump head
- minimising outlet pipe dimensions due to grinder system
- designed for more demanding effluent and sewage pumping
- high performance, high reliability and low maintenance
- included motor protection that reacts to blockage
- service friendly – quick access to replace wear-parts like cable, impeller and rotating grinder head.

Therefore the product is ideal for use in sparsely populated areas where gravity sewage systems are not available. The solution is ideal in, for example, one- or two-family houses, residential building services and areas with large terrain-level differences.

### Type key, UNILIFT APG

Example: UNILIFT APG.40.10.A1. 1x220-240V SCH

Code	Explanation	Designation
UNILIFT APG	Product name	
40		Nominal diameter of the outlet
10		Power output, P2 / 100 [W]
[ ]	Manual operation without float switch	Level control
A	Automatic operation with float switch	
1	Single-phase	Motor type
3	Three-phase	
1 x 230 V		
1 x 220 - 240 V		
3 x 220 V		Nominal voltage
3 x 380 V		
3 x 400 V		
[ ]	No plug	
SCH	Europe - F type wall plug	
ARG	Argentina - IRAM approved I type wall plug	Plug type
AUS	Australia, New Zealand - I type wall plug	

### Approvals and markings



TM075405




TM074611



9985271

## Construction

### Materials



Po s.	Component	Material	DIN W. - Nr.	AISI
1	Pump housing	Cast iron	EN-GJL-200	-
2	Pump base	Cast iron	EN-GJL-200	-
3	Impeller	Composite	-	-
4	Cutter base	Stainless steel	1.4542	630
5	Cutter	Stainless steel	1.4542	630
6	Shaft seal disc	Stainless steel	1.4301	304
7	Motor connection flange	Stainless steel	1.4301	304
8	Lower bearing support	Aluminium	-	-
9	Double mechanical seal	Pump side - silicone carbide	-	-
		Motor side - carbon/alumina	-	-
10	Motor case	Stainless steel	1.4301	304
11	Motor shaft		1.4057	431
12	Upper bearing support	Aluminium	-	-
13	Top cover	Stainless steel	-	-
14	Handle	Stainless steel and insulating rubber	-	-

Po s.	Component	Material	DIN W. - Nr.	AISI
15	Supply cable	H07RN8-F	-	-
16	Float switch cable	H07RN-F	-	-
17	O-rings	NBR	-	-
18	Cable gland	Nickel-plated brass	-	-

## Design

UNILIFT APG has a semi-open impeller design. Because the knife cuts the debris in the water before entering the hydraulics, the pump performs more efficiently and with higher head, relative to similar open impeller designs.

## Pump housing

UNILIFT APG has a pump housing with an outstanding design for submersible wastewater pumps resulting in a high head. The pump housing is made of cast iron with a hydraulically correct shape, ensuring free passage of ground particles.

## Outlet port

All UNILIFT APG pumps are fitted with a combined Rp 1 1/2" / DN32 / DN40 horizontal outlet port. UNILIFT APG is compatible with the Grundfos SEG guide rail system.

## Shaft and bearings

The stainless-steel shaft rotates in maintenance-free, pre-lubricated ball bearings.

## Impeller

The composite impeller is a semi-open impeller with L-shaped blades. The blades are curved backwards to reduce any harmful effects from solid particles and to minimise power consumption. The impeller has a protective cap to prevent the deposit of long-fibred material.

## Grinder system

The grinder system consists of two parts: a stationary grinder ring and a rotating grinder head. The grinder ring is secured to the pump housing by means of a bayonet coupling and fixed in the right position with a screw. The grinder head is secured to the shaft by means of the screw that keeps the impeller in position.

Both parts are made of hardened stainless steel for optimum durability of the grinder function.

## Shaft seal

The shaft seal is a combination of a mechanical bellows shaft seal and a lip seal with 350 ml oil in between. The seal faces are made of silicone carbide.

## Pumped liquids


The pump is capable of pumping water containing a limited quantity of spherical particles.

The pump is not suitable for the following liquids:

- Liquids containing long fibres
- inflammable liquids (oil, petrol, etc.)
- aggressive liquids.

## Sizing guide

The quick sizing chart below gives an approximate overview of heights and outlet pipe lengths with an inner pipe diameter of DN 32, G 1 1/2" / DN 40, and a flow, so that a self-cleaning velocity of minimum 0.7 m/s is covered. The overview is only intended as a guide. Pressure loss of a non-return valve and an isolating valve is calculated. The vertical height of the outlet pipe must be measured from the pump stop level. For more flow requirements a calculation is needed.




TM081851

APG.40.10, flow of 0.7 m/s ,  $Q = 2.1 - 3.2 \text{ m}^3/\text{h}$


## Performance curves

UNILIFT APG pumps are performance-tested according to the following standard:


- ISO 9906:2012, grade 3B



UNILIFT APG, single-phase motor



UNILIFT APG, three-phase motor



UNILIFT APG, single-phase motor

## Product range, UNILIFT APG

### 50 Hz

Pump type	Product number	Voltage [V]	Plug type	Cable length [m]	Cable type	Net weight [kg]
UNILIFT APG.40.10.A1	92611467	1 x 230	SCHUKO	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.A1	92616874	1 x 230	No plug	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.1	92616890	1 x 230	SCHUKO	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.1	92616891	1 x 230	No plug	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.A1	92616898	1 x 230	ARG	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.1	92616910	1 x 230	ARG	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.A1	92616914	1 x 220-240	AUS	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.1	92616916	1 x 220-240	AUS	10	H07RN8-F 3G1	22.1
UNILIFT APG.40.10.A3	92616892	3 x 400	No plug	10	H07RN8-F 5G1	22.1
UNILIFT APG.40.10.3	92616893	3 x 400	No plug	10	H07RN8-F 5G1	22.1
UNILIFT APG.40.10.A3	92616895	3 x 220	No plug	10	H07RN8-F 5G1	22.1
UNILIFT APG.40.10.3	92616897	3 x 220	No plug	10	H07RN8-F 5G1	22.1
UNILIFT APG.40.10.A3	92616912	3 x 380	No plug	10	H07RN8-F 5G1	22.1
UNILIFT APG.40.10.3	92616913	3 x 380	No plug	10	H07RN8-F 5G1	22.1

23) UNILIFT APG is available with and without a float switch in both single- and three-phase versions. A float switch for single-phase pumps has a direct connection. For three-phase pumps, there is a connection to an external control box including MPU, with a 10 m cable float switch.


### 60 Hz

	Product number	Voltage [V]	Plug type	Cable length [m]	Cable type	Net weight [kg]
UNILIFT APG.40.10.1	92910103	1 x 230	No plug	10	H07RN8-F 3G1	23.2
UNILIFT APG.40.10.A1	92910104	1 x 230	No plug	10	H07RN8-F 3G1	23.2

## Electrical data

Pump type	Voltage [V]	Rated power	Absorbed power	Absorbed current
		[W (hp)]	[W (hp)]	[A]
UNILIFT APG	1 x 220-240	1000 (1.3)	1300 (1.7)	6.8
	3 x 200-220	1000 (1.3)	1300 (1.7)	4.5
	3 x 380-415	1000 (1.3)	1300 (1.7)	2.6

## Dimensions





TM082139

Model	Dimensions [mm]									
	H	H1	D	D1	D2	DN2	DN4	L	W	
UNILIFT APG.40.10.	498	86.5	Ø19	100	110	DN32/DN40	Rp 1 1/2	254	209	

## Accessories

Product number	Dimensions	Description
99369644		LC 231 (1 pump) without float switch
99369650		LC 231 (dual pump controller) without float switch
98538174	2 m	
98538175	3 m	
98538176	4 m	Lifting chain in stainless steel (EN 1.4571/A4) with shackle.
98538177	6 m	Approved up to 500 kg with certificate.
98538178	8 m	
98538179	10 m	
96076063	DN 40/Rp 1 1/2	Auto-coupling system complete, that is upper guide rail bracket, bolts, nuts, gaskets, guide claw and base stand. All parts are in cast iron.
98245789	JIS/KS DN 40	<b>Note:</b> In installations with guide rails longer than 4 m, we recommend that you use an intermediate guide rail bracket.
96887609	DN 40	Intermediate guide rail bracket (guide rails 4 meter and longer) in stainless steel.

## 6. Accessories

Accessory	Description	Related products	Product number
	TM077677 Guide arm for floater, UNILIFT CC	UNILIFT CC	98709179
	TMC01006 Guide arm for floater, UNILIFT KP	UNILIFT KP	96007161
	TM067162 Guide arm for floater, UNILIFT AP and UNILIFT APB	UNILIFT AP UNILIFT APB	96003993
	GR-1022807 Float switch M2 with 5 m cable	LC 231	91427145
	GR-1022807 Float switch M2 with 10 m cable	LC 231	91427146
	GR-1017241 LLC 1000W 300mm, 1 x 230 V, 50Hz SCHUKO plug and socket	UNILIFT KP	98599969
	GR-1031078 LC 231 single pump controller	UNILIFT AP UNILIFT KP UNILIFT CC UNILIFT APB UNILIFT APG	99369644
	GR-1031087 LC 231 dual pump controller	UNILIFT AP UNILIFT KP UNILIFT CC UNILIFT APB UNILIFT APG	99369650
	GR-1029731 Auto coupling with horizontal connection Rp 2" Guide claw Rp 2" without sealing Guide rails pins for 1" pipes with max. length of 1.5 m	UNILIFT APB	96429519
	GR-1031453 Auto coupling with 90° bend and vertical connection Rp 2" Guide claw Rp 2" with sealing Guide rail pins for 1" pipes with max. length of 3 m	UNILIFT APB	97644486
	TM025980 Auto-coupling system complete, that is upper guide rail bracket, bolts, nuts, gaskets, guide claw and base stand. All parts are in cast iron. DN 40 / Rp 1 1/2" <b>Note:</b> In installations with guide rails longer than 4 m, we recommend that you use an intermediate guide rail bracket (96887609).	UNILIFT APG	96076063
	TM057683 Intermediate guide rail bracket, DN40 to extend 1" guide rails	UNILIFT APB UNILIFT APG	96887609

Accessory	Description	Related products	Product number
	TM077908 Non-return valve for 1 1/4" outlet connection	UNILIFT KP	15211
	TM077908 Non-return valve for 1 1/2" outlet connection	UNILIFT AP12.40 UNILIFT AP35.40 UNILIFT APG	96549937
	TM077913 Non-return valve PVC, ball type Rp 1 1/2"	UNILIFT AP12.40 UNILIFT AP35.40	96023843
	TM077913 Non-return valve PVC, ball type Rp 2"	UNILIFT AP12.40 UNILIFT AP50 UNILIFT APB	96023844
	TM078278 Isolating valve Rp 1 1/2"	UNILIFT AP	96023846
	TM078279 Isolating valve Rp 2"	UNILIFT AP UNILIFT APB	96023847
	GR-1019227 Hexagon nipple Rp 1 1/2"	UNILIFT AP12.40 UNILIFT AP35.40	96003632
	GR-1016340 Lifting chain 3 m, 320 kg maximum working load	UNILIFT AP UNILIFT APB	98989664
	GR-1028108 DN 50 outlet hose with Storz C couplings 10 m	UNILIFT AP UNILIFT APB UNILIFT APG	96001987
	Storz coupling C-G R 1 1/2"	UNILIFT AP12.40 UNILIFT AP35.40 UNILIFT APG	96001977
	Storz coupling C-G R 2"	UNILIFT AP12.50 UNILIFT AP50	96003829
	Storz coupling C-G Rp 2"	UNILIFT APB	96001982

## Lifting stations UNO-/DUOLIFT

Accessory	Description	Related products	Product number
	TM049242 DUOLIFT 270.40.CC/KP tank including pipes	UNILIFT CC, KP	97642386
	TM049242 DUOLIFT 270.40.SEG/APG tank including pipes	SEG, UNILIFT APG	97642372
	TM049242 DUOLIFT 270.50.APB tank including pipes	UNILIFT APB	97642388
	TM049241 DUOLIFT 540.40.SEG/APG tank including pipes	SEG, UNILIFT APG	99017729
	TM049241 DUOLIFT 540.50.APB tank including pipes	UNILIFT APB	99017735
	TM049242 UNOLIFT 270.40.CC/KP tank including pipes	UNILIFT CC, KP	97642385
	TM049242 UNOLIFT 270.40.SEG/APG tank including pipes	SEG, UNILIFT APG	97642371
	TM049242 UNOLIFT 270.50.APB tank including pipes	UNILIFT APB	97642387

For further information about UNO-/DUOLIFT, scan the QR code below.



QR98501181

<http://net.grundfos.com/qr/i/98501181>

## LIFTAWAY

Accessory	Description	Related products	Product number
	LIFTAWAY B 120-1, including pipes TM080991	UNILIFT CC, KP, AP12	92613179
	LIFTAWAY B 120-2, including pipes TM080991	UNILIFT CC, KP	92614070

Pumps must be selected separately.

Accessory	Description	Related products	Product number
	LIFTAWAY C 40-1, including pipes LIFT_C40	UNILIFT KP	96003985

For further information about LIFTAWAY C 40-1 and accessories, scan the QR code below.



QR96415568

<http://net.grundfos.com/qr/i/96415568>

Pumps must be selected separately.

## Controllers

### LLC 1000W level controller



*LLC 1000W level controller*

This electrode device controls and monitors 1 x 230 V, 50 Hz pumps with a Schuko plug up to a nominal current of 6 Ampere. It is specially designed to fit in narrow tanks, wells or pump sumps. The device can be assembled directly to UNILIFT KP or UNILIFT CC pumps and be placed beside the pump in a sump. It can also operate with UNILIFT AP pumps. It is a full control unit with a high water-level alarm with integrated buzzer. A potential free contact allows the device to be connected to BMS systems, an external alarm buzzer or lamp. The start, stop, and alarm level can be adjusted by cutting the electrode to the required length. To limit maintenance of the electrodes, it is recommended for use with conductive (waste-)water that does not contain components that build up an isolating layer on contacted surfaces, such as grease or fat.

The level controller consists of the following:

Pos.	Description
1	4 stainless steel rod electrodes (300 or 1000 mm)
2	Electrode bracket
3	Mounting bracket
4	10 m cable
5	Plug-in control box
6	1 1/4" barrel nipple (to be used with UNILIFT KP to mount the bracket on the pump discharge)

The control box houses the evaluation electronics, a safety plug, and a Schuko outlet for connection to the pump.

Product number	Description
98599969	LLC 1000W.230.1.6 300 mm
98599967	LLC 1000W.230.1.6 1000 mm

### LC 231 level-control unit



*LC 231 single pump controller*



*LC 231 dual pump controller*

The LC 231 pump controllers are designed for level control, monitoring and protection of one pump or two pumps starting direct-on-line. Only one controller type is required for single-phase or three-phase pumps and for both 50 and 60 Hz. The controllers are equipped with motor current measurement and motor protection for additional safety. The level-control unit switches the pump on and off according to the liquid level measured by float switches or an analog pressure sensor. When the start level is reached, the pump starts and when the liquid level has been lowered to the stop level, the pump is stopped. An alarm is triggered in instances such as high-water level in the tank and sensor or pump failure. Settings are configured via the operating panel or simply via a Bluetooth connection to a mobile phone through the GRUNDFOS GO Remote app. Full documentation with alarm logs and reports can be extracted via the app as well. LC 231 can also be connected to building management systems with a small add-on card module.

Product number	Description
99369644	LC 231 single pump controller (no float switch), 1 x 110- 240 VAC (50/60 Hz) or 3 x 380-460 VAC (50/60 Hz)
99369650	LC 231 dual pump controller (no float switch), 1 x 110- 240 VAC (50/60 Hz) or 3 x 380-460 VAC (50/60 Hz)

## Accessories for controllers

Description	Product number
Flashing light for external alarm indication (1 x 230 VAC for outdoor installation)	62500020
Alarm horn for external alarm indication (outdoor installation, 1 x 230 VAC)	62500021
Alarm horn for external alarm indication (indoor installation, 1 x 230 VAC)	62500022
25 [A] external mains switch for supply cable	96002511

### Level detection with float switches

Wells, pits, tanks or simple concrete pump sumps for drainage and greywater installations are often small, and float switches should be small as well to operate properly. Float switches can be connected to LC 231.

Description	Product number
Float Switch M2 with 5 m cable (90 mm height, ø60 mm, max. temp. 80 °C)	91427145
Float Switch M2 with 10 m cable (90 mm height, ø60 mm, max. temp. 80 °C)	91427146
Float Switch M2 with 20 m cable (90 mm height, 60 mm, max. temp. 80 °C)	91427147

### Level detection with hydrostatic sensor

Very slim and narrow installations require a level detection with no movable parts in the wastewater. Analog pressure sensors are the right choice under these conditions.

Pressure sensors can be connected to LC 231.

Description	Product number
Level sensor with 10 m cable, 4-20 mA	99488545
Level sensor with junction box to extend the sensor cable	99488577
Level sensor with cable hanger in pits and wells	99488578

## 7. Grundfos Product Center

Online search and sizing tool to help you make the right choice.

From the international view, you can select your specific country to view the product range available to you.

International view: <http://product-selection.grundfos.com>

### All the information you need in one place

Performance curves, technical specifications, pictures, dimensional drawings, motor curves, wiring diagrams, spare parts, service kits, 3D drawings, documents, system parts. The Product Center displays any recent and saved items - including complete projects - right on the main page.

#### Downloads

On the product pages, you can download installation and operating instructions, data booklets, service instructions, etc., in PDF format.



When you select your country, you will see the menus below. Note that some menus may not be available depending on the country.

Example: <https://product-selection.grundfos.com/uk>

#### Pos. Description

- 1 **Products & services** enables you to find products and documents by typing a product number or name into the search field.
- 2 **Applications** enables you to choose an application to see how Grundfos can help you design and optimise your system.
- 3 **Products A-Z** enables you to look through a list of all the Grundfos products.
- 4 **Categories** enables you to look for a product category.
- 5 **Liquids** enables you to find pumps designed for aggressive, flammable or other special liquids.
- 6 **Product replacement** enables you to find a suitable replacement.
- 7 **WWW** enables you to select the country, which changes the language, the available product range and the structure of the website.
- 8 **Sizing** enables you to size a product based on your application and operating conditions.

### **Argentina**

Bombas GRUNDFOS de Argentina S.A.  
Ruta Panamericana km. 37.500 industria  
1619 - Garin Pcia. de B.A.  
Tel.: +54-3327 414 444  
Fax: +54-3327 45 3190

### **Australia**

GRUNDFOS Pumps Pty. Ltd.  
P.O. Box 2040  
Regency Park  
South Australia 5942  
Tel.: +61-8-8461-4611  
Fax: +61-8-8340-0155

### **Austria**

GRUNDFOS Pumpen Vertrieb Ges.m.b.H.  
Grundfosstraße 2  
A-5082 Grödig/Salzburg  
Tel.: +43-6246-883-0  
Fax: +43-6246-883-30

### **Belgium**

N.V. GRUNDFOS Bellux S.A.  
Boomsesteenweg 81-83  
B-2630 Aartselaar  
Tel.: +32-3-870 7300  
Fax: +32-3-870 7301

### **Bosnia and Herzegovina**

GRUNDFOS Sarajevo  
Zmaja od Bosne 7-7A  
BiH-71000 Sarajevo  
Tel.: +387 33 592 480  
Fax: +387 33 590 465  
www.ba.grundfos.com  
E-mail: grundfos@bih.net.ba

### **Brazil**

BOMBAS GRUNDFOS DO BRASIL  
Av. Humberto de Alencar Castelo Branco, 630  
CEP 09850 - 300  
São Bernardo do Campo - SP  
Tel.: +55-11 4393 5533  
Fax: +55-11 4343 5015

### **Bulgaria**

Grundfos Bulgaria EOOD  
Slatina District  
Iztochna Tangenta street no. 100  
BG - 1592 Sofia  
Tel.: +359 2 49 22 200  
Fax: +359 2 49 22 201  
E-mail: bulgaria@grundfos.bg

### **Canada**

GRUNDFOS Canada inc.  
2941 Brighton Road  
Oakville, Ontario  
L6H 6C9  
Tel.: +1-905 829 9533  
Fax: +1-905 829 9512

### **China**

GRUNDFOS Pumps (Shanghai) Co. Ltd.  
10F The Hub, No. 33 Suhong Road  
Minhang District  
Shanghai 201106 PRC  
Tel.: +86 21 612 252 22  
Fax: +86 21 612 253 33

### **Columbia**

GRUNDFOS Colombia S.A.S.  
Km 1.5 via Siberia-Cota Conj. Potrero Chico,  
Parque Empresarial Arcos de Cota Bod. 1A.  
Cota, Cundinamarca  
Tel.: +57(1)-2913444  
Fax: +57(1)-8764586

### **Croatia**

GRUNDFOS CROATIA d.o.o.  
Buzinski prilaz 38, Buzin  
HR-10010 Zagreb  
Tel.: +385 1 6595 400  
Fax: +385 1 6595 499  
www.hr.grundfos.com

### **Czech Republic**

GRUNDFOS Sales Czechia and Slovakia s.r.o.  
Čajkovského 21  
779 00 Olomouc  
Tel.: +420-585-716 111

### **Denmark**

GRUNDFOS DK A/S  
Martin Bachs Vej 3  
DK-8850 Bjerringbro  
Tel.: +45-87 50 50 50  
Fax: +45-87 50 51 51  
E-mail: info\_GDK@grundfos.com  
www.grundfos.com/DK

### **Estonia**

GRUNDFOS Pumps Eesti OÜ  
Peterburi tee 92G  
11415 Tallinn  
Tel.: +372 606 1690  
Fax: +372 606 1691

### **Finland**

OY GRUNDFOS Pumpum AB  
Truukkula 1  
FI-01360 Vantaa  
Tel.: +358-(0) 207 889 500

### **France**

Pompes GRUNDFOS Distribution S.A.  
Parc d'Activités de Chesnes  
57, rue de Malacombe  
F-38290 St. Quentin Fallavier (Lyon)  
Tel.: +33-4 74 82 15 15  
Fax: +33-4 74 94 10 51

### **Germany**

GRUNDFOS GMBH  
Schlüterstr. 33  
40699 Erkrath  
Tel.: +49-(0) 211 929 69-0  
Fax: +49-(0) 211 929 69-3799  
E-mail: infoservice@grundfos.de  
Service in Deutschland:  
kundendienst@grundfos.de

### **Greece**

GRUNDFOS Hellas A.E.B.E.  
20th km. Athinon-Markopoulou Av.  
P.O. Box 711  
GR-19002 Peania  
Tel.: +0030-210-66 83 400  
Fax: +0030-210-66 46 273

### **Hong Kong**

GRUNDFOS Pumps (Hong Kong) Ltd.  
Unit 1, Ground floor, Siu Wai industrial  
Centre  
29-33 Wing Hong Street & 68 King Lam  
Street, Cheung Sha Wan  
Kowloon  
Tel.: +852-27861706 / 27861741  
Fax: +852-27858664

### **Hungary**

GRUNDFOS Hungária Kft.  
Tópark u. 8  
H-2045 Törökbalint  
Tel.: +36-23 511 110  
Fax: +36-23 511 111

### **India**

GRUNDFOS Pumps India Private Limited  
118 Old Mahabalipuram Road  
Thoraipakkam  
Chennai 600 097  
Tel.: +91-44 2496 6800

### **Indonesia**

PT GRUNDFOS Pompa  
Graha intirub Lt. 2 & 3  
Jln. Ciliilitan Besar No.454. Makasar,  
Jakarta Timur  
ID-Jakarta 13650  
Tel.: +62 21-469-51900  
Fax: +62 21-460 6910 / 460 6901

### **Ireland**

GRUNDFOS (Ireland) Ltd.  
Unit A, Merrywell Business Park  
Ballymount Road Lower  
Dublin 12  
Tel.: +353-1-4089 800  
Fax: +353-1-4089 830

### **Italy**

GRUNDFOS Pompe Italia S.r.l.  
Via Gran Sasso 4  
I-20060 Truccazzano (Milano)  
Tel.: +39-02-95838112  
Fax: +39-02-95309290 / 95838461

### **Japan**

GRUNDFOS Pumps K.K.  
1-2-3, Shin-Miyakoda, Kita-ku  
Hamamatsu  
431-2103 Japan  
Tel.: +81 53 428 4760  
Fax: +81 53 428 5005

### **Kazakhstan**

Grundfos Kazakhstan LLP  
7 Kyz-Zhibek Str., Kok-Tobe micr.  
KZ-050020 Almaty Kazakhstan  
Tel.: +7 (727) 227-98-55/66

### **Korea**

GRUNDFOS Pumps Korea Ltd.  
6th Floor, Aju Building 679-5  
Yeoksam-dong, Kangnam-ku, 135-916  
Seoul, Korea  
Tel.: +82-2-5317 600  
Fax: +82-2-5633 725

### **Latvia**

SIA GRUNDFOS Pumps Latvia  
Deglava biznessa centrs  
Augusta Deglava iela 60  
LV-1035, Riga,  
Tel.: + 371 714 9640, 7 149 641  
Fax: + 371 914 9646

### **Lithuania**

GRUNDFOS Pumps UAB  
Smolensko g. 6  
LT-03201 Vilnius  
Tel.: + 370 52 395 430  
Fax: + 370 52 395 431

### **Malaysia**

GRUNDFOS Pumps Sdn. Bhd.  
7 Jalan Peguan U1/25  
Glenmarie Industrial Park  
40150 Shah Alam, Selangor  
Tel.: +60-3-5569 2922  
Fax: +60-3-5569 2866

### **Mexico**

Bombas GRUNDFOS de México  
S.A. de C.V.  
Boulevard TLC No. 15  
Parque Industrial Stiva Aeropuerto  
Apodaca, 66600  
Tel.: +52-81-8144 4000  
Fax: +52-81-8144 4010

### **Netherlands**

GRUNDOFS Netherlands  
Veluwezoom 35  
1326 AE Almere  
Postbus 22015  
1302 CA ALMERE  
Tel.: +31-88-478 6336  
Fax: +31-88-478 6332  
E-mail: info\_gnl@grundfos.com

### **New Zealand**

GRUNDFOS Pumps NZ Ltd.  
17 Beatrice Tinsley Crescent  
North Harbour Industrial Estate  
Albany, Auckland  
Tel.: +64-9-415 3240  
Fax: +64-9-415 3250

### **Norway**

GRUNDFOS Pumper A/S  
Strømsveien 344  
Postboks 235, Leirdal  
N-1011 Oslo  
Tel.: +47-22 90 47 00  
Fax: +47-22 32 21 50

### **Poland**

GRUNDFOS Pompy Sp. z o.o.  
ul. Klonowa 23  
Baranowo k. Poznania  
PL-62-081 Przeźmierowo  
Tel.: (+48-61) 650 13 00  
Fax: (+48-61) 650 13 50

### **Portugal**

Bombas GRUNDFOS Portugal, S.A.  
Rua Calvet de Magalhães, 241  
Apartado 1079  
P-2770-153 Paço de Arcos  
Tel.: +351-21-440 76 00  
Fax: +351-21-440 76 90

### **Romania**

GRUNDFOS Pompe România SRL  
S-PARK BUSINESS CENTER, Clădirea  
A2, etaj 2  
Str. Tipografilor, Nr. 11-15, Sector 1, Cod  
013714  
Bucuresti, Romania  
Tel.: 004 021 2004 100  
E-mail: romania@grundfos.ro

### **Serbia**

Grundfos Srbija d.o.o.  
Omladinski brigada 90b  
11070 Novi Beograd  
Tel.: +381 11 2258 740  
Fax: +381 11 2281 769  
www.rs.grundfos.com

### **Singapore**

GRUNDFOS (Singapore) Pte. Ltd.  
25 Jalan Tukang  
Singapore 619264  
Tel.: +65-6681 9688  
Faxax: +65-6681 9689

### **Slovakia**

GRUNDFOS s.r.o.  
Prievozská 4D 821 09 BRATISLAVA  
Tel.: +421 2 5020 1426  
sk.grundfos.com

### **Slovenia**

GRUNDFOS LJUBLJANA, d.o.o.  
Leskoškova 9e, 1122 Ljubljana  
Tel.: +386 (0) 1 568 06 10  
Fax: +386 (0) 1 568 06 19  
E-mail: tehnika-si@grundfos.com

### **South Africa**

GRUNDFOS (PTY) LTD  
16 Lascelles Drive, Meadowbrook Estate  
1609 Germiston, Johannesburg  
Tel.: (+27) 10 248 6000  
Fax: (+27) 10 248 6002  
E-mail: lgraddige@grundfos.com

### **Spain**

Bombas GRUNDFOS España S.A.  
Camino de la Fuentechilla, s/n  
E-28110 Algete (Madrid)  
Tel.: +34-91-848 8800  
Fax: +34-91-628 0465

### **Sweden**

GRUNDOFS AB  
Box 333 (Lunnagårdsgatan 6)  
431 24 Möndal  
Tel.: +46 31 332 23 000  
Fax: +46 31 331 94 60

### **Switzerland**

GRUNDFOS Pumpen AG  
Bruggacherstrasse 10  
CH-8117 Fällanden/ZH  
Tel.: +41-44-806 8111  
Fax: +41-44-806 8115

### **Taiwan**

GRUNDFOS Pumps (Taiwan) Ltd.  
7 Floor, 219 Min-Chuan Road  
Taichung, Taiwan, R.O.C.  
Tel.: +886-4-2305 0868  
Fax: +886-4-2305 0878

### **Thailand**

GRUNDFOS (Thailand) Ltd.  
92 Chaloem Phrakiat Rama 9 Road  
Dokmai, Pravej, Bangkok 10250  
Tel.: +66-2-725 8999  
Fax: +66-2-725 8998

### **Turkey**

GRUNDFOS POMPA San. ve Tic. Ltd. Sti.  
Gebze Organize Sanayi Bölgesi  
Ihsan dede Caddesi  
2, yol 200. Sokak No. 204  
41490 Gebze/ Kocaeli  
Tel.: +90 - 262-679 7979  
Fax: +90 - 262-679 7905  
E-mail: satis@grundfos.com

### **Ukraine**

ТОВ "ГРУНДФОС УКРАЇНА"  
Бізнес Центр Європа  
Столичне шосе, 103  
м. Київ, 03131, Україна  
Tel.: +(38 044) 237 04 00  
Fax: +(38 044) 237 04 01  
E-mail: ukraine@grundfos.com

### **United Arab Emirates**

GRUNDFOS Gulf Distribution  
P.O. Box 16768  
Jebel Ali Free Zone, Dubai  
Tel.: +971 4 8815 166  
Fax: +971 4 8815 136

### **United Kingdom**

GRUNDFOS Pumps Ltd.  
Grovebury Road  
Leighton Buzzard/Beds. LU7 4TL  
Tel.: +44-1525-850000  
Fax: +44-1525-850011

### **U.S.A.**

Global Headquarters for WU  
856 Koomey Road  
Brookshire, Texas 77423 USA  
Phone: +1-630-236-5500

### **Uzbekistan**

Grundfos Tashkent, Uzbekistan  
The Representative Office of Grundfos  
Kazakhstan in Uzbekistan  
38a, Oybek street, Tashkent  
Tel.: (+998) 71 150 3290 / 71 150 3291  
Fax: (+998) 71 150 3292

**96604141 07.2023**

ECM: 1372695

**GRUNDFOS Holding A/S**  
Poul Due Jensens Vej 7  
DK-8850 Bjerringbro  
Tel: +45 87 50 14 00  
[www.grundfos.com](http://www.grundfos.com)

**GRUNDFOS** 