



## Mamelon d'adaptation PE/laiton avec filetage mâle R COOL-FIT 2.0

### Exécution:

- Raccord avec bout lisse PE100 SDR11 métrique
- Filetage mâle R laiton CuZn40Pb2
- Joint: joint torique EPDM
- Y compris isolation en mousse de NBR

d (mm)	D (mm)	Thread (inch)	Pouces (inch)	DN (mm)	SDR	PN (bar)	Code	pooids (kg)	L1 (mm)	z (mm)
32	70	R	½	25	11	16	<b>738 954 508</b>	0,203	36	130
32	70	R	¾	25	11	16	<b>738 954 518</b>	0,211	36	134
32	70	R	1	25	11	16	<b>738 954 528</b>	0,221	36	134
40	78	R	1 ¼	32	11	16	<b>738 954 509</b>	0,631	40	156
50	88	R	1 ½	40	11	16	<b>738 954 510</b>	1,013	44	168
63	101	R	2	50	11	16	<b>738 954 511</b>	1,467	48	179

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>